

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Metalworking Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)						
Hazard class	Hazard category	Hazard statement				
Eye Irrit.	2	H319-Causes serious eye irritation.				
Aerosol	3	H229-Pressurised container: May burst if heated.				
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure if swallowed (kidneys).				

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851



H319-Causes serious eye irritation. H229-Pressurised container: May burst if heated. H373-May cause damage to organs through prolonged or repeated exposure if swallowed (kidneys).

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251-Do not pierce or burn, even after use. P260-Do not breathe spray. P280-Wear eye protection / face protection.

P314-Get medical advice / attention if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Ethanediol

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Ethanediol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119456816-28-XXXX
Index	603-027-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-473-3
CAS	107-21-1
content %	15-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	STOT RE 2, H373 (kidneys) (oral)

Phosphate ester	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	39464-70-5
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures



Page 3 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product: Solvent Thinners

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Toxic gases Danger of bursting (explosion) when heated

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6 1 2 Ear amorgancy respond

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.



Page 4 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep protected from direct sunlight and temperatures over 50°C.

Observe special regulations for aerosols!

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Ethanediol				Content %:15-20
WEL-TWA: 10 mg/m3 (particulate)	, 52 mg/m3	WEL-STEL: 104 mg/m3 (vapo	ur) (WEL), 40 ppm		
(vapour) (WEL), 20 ppm (52 mg/m3)	(EU)	(104 mg/m3) (EU)			
Monitoring procedures:	-	Draeger - Ethylene Glycol 10 (5) (8	1 01 351)		
	-	Compur - KITA-232 SA (502 342)			
	-	Compur - KITA-232 SB (550 267)			
	-	NIOSH 5500 (ETHYLENE GLYCO	L) - 1993		
	-	NIOSH 5523 (GLYCOLS) - 1996			
		OSHA PV2024 (Ethylene glycol) - 2	1999 - EU project BC/CE	EN/ENTR/	000/2002-16 card
	-	11-2 (2004)			
BMGV:			Other information: S	sk (particul	ate, vapour)
Chemical Name	Propane-1,2-diol				Content %:
WEL-TWA: 150 ppm (474 mg/m3)	(total, vapour and	WEL-STEL:			
particulates), 10 mg/m3 (particulates	3)				
Monitoring procedures:	-	Draeger - Alcohol 100/a (CH 29 70	1)		
BMGV:			Other information:	-	
Ethanediol					



B Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sediment		PNEC	20,9	mg/kg	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	37	mg/kg dry weight	
	Environment - sediment, marine		PNEC	3,7	mg/kg dry weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	53	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	35	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	106	mg/kg bw/d	

Propane-1,2-diol			D			
Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	260	mg/l	
	Environment - marine		PNEC	26	mg/l	
	Environment - sewage treatment plant		PNEC	20000	mg/l	
	Environment - sediment, freshwater		PNEC	572	mg/kg dw	
	Environment - sediment, marine		PNEC	57,2	mg/kg dw	
	Environment - soil		PNEC	50	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	183	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	213	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	85	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	168	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Area of application	Exposure route / Environmental compartment	Environmental		Value	Unit	Note
	Environment - freshwater		PNEC	0,32	mg/l	
	Environment - marine		PNEC	0,032	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	5,12	mg/l	
	Environment - sewage treatment plant		PNEC	10	mg/l	
	Environment - sediment, freshwater		PNEC	1,7	mg/kg	



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

	Environment - sediment, marine		PNEC	0,17	mg/kg
	Environment - soil		PNEC	0,151	mg/kg dry weight
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,66	mg/kg bw/day
Consumer	Human - oral	Long term, systemic effects	DNEL	3	mg/kg bw/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,25	mg/m3
Consumer	Human - inhalation	Long term, local effects	DNEL	0,4	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6,3	mg/kg bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 480 Protective hand cream recommended. The breakthrough times determined in accordance w

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).



Page 7 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

(GB)

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Liquid The propellant is not released when used in accordance with Physical state: the regulations. Colour: Red Odour. Odourless Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: 100 °C (Active substance) Flammability: Does not apply to aerosols. Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: n.a., Active substance (ISO 2592 (Cleveland, open cup)) Auto-ignition temperature: No Decomposition temperature: There is no information available on this parameter. pH: 8,6 (Active substance) ~60 mm2/s (40°C, ISO 3104, Active substance) Kinematic viscosity: Solubility: Mixable, Active substance 20°C Partition coefficient n-octanol/water (log value): Does not apply to mixtures. Vapour pressure: There is no information available on this parameter. Density and/or relative density: 1,068 g/cm3 (15°C, ISO 12185, Active substance) Relative vapour density: Does not apply to aerosols. Particle characteristics Does not apply to aerosols. 9.2 Other information Explosives: Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture. Oxidising liquids: No Bulk density: n.a.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. **10.3 Possibility of hazardous reactions** No dangerous reactions are known. **10.4 Conditions to avoid** Heating, open flame, ignition sources Pressure increase will result in danger of bursting. **10.5 Incompatible materials** Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products



Page 8 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

No decomposition when used as directed.

œ

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Ethanediol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1600	mg/kg	Human being		
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>3500	mg/kg	Mouse		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin				Human being	(Patch-Test)	Negative
sensitisation:				_		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Rat	in vivo	Negative
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat		
Symptoms:						ataxia, breathing difficulties, unconsciousness , cramps, fatigue

Phosphate ester						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Eye Dam. 1
Respiratory or skin						Not sensitizising
sensitisation:						

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>20000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rabbit		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizising



Negative

in vitro

Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Germ cell mutagenicity:

œ

11.2. Information on other hazards

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	Lindpoint	Time	Value	Unit	organishi	rest method	n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complex
							ng organic
							substance)>=
							80%/28d: n.a.
Other information:							According to the
							recipe, contains
							no ÁOX.
Ethanediol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC20	30min	>1995	mg/l	activated sludge	OECD 209	NOLES
Toxicity to bacteria.	L020	3011111	-1995	ilig/i	activated sludge	(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
						Oxidation))	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales	IUCLID Chem.	
12.1. TONICITY TO HOH.	2030	3011	- 10000	iiig/i	promelas	Data Sheet (ESIS)	
12.1. Toxicity to fish:	NOEC/NOEL	7d	15380	mg/l	Pimephales	U.S. EPA	
		/u	15500	iliy/i	promelas	ECOTOX	
					promeias	Database	



Page 10 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL		8590	mg/l	Daphnia magna	U.S. EPA ECOTOX Database	
12.1. Toxicity to algae:	EC50	96h	6500- 7500	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	56	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:		10d	90-100	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	16h	>10000	mg/l	Pseudomonas putida	IUCLID Chem. Data Sheet (ESIS)	
Other information:	BOD5		0,78	g/g		(/	IUCLID

Phosphate ester							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	48h	>100	mg/l	Leuciscus idus		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		-1,07			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	40613	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	18340	mg/l	Ceriodaphnia spec.	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	13020	mg/l	Ceriodaphnia spec.		
12.1. Toxicity to algae:	EC50	48h	19000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81,7	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		0,09			· · · · · · ·	valued
Toxicity to bacteria:	NOEC/NOEL	18h	>20000	mg/l	Pseudomonas putida		

@-



(B)————————————————————————————————————								
Page 11 of 16								
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II								
Revision date / version: 01.11.2021 / 0008								
Replacing version dated / version: 22.02.2019 / 0007								
Valid from: 01.11.2021								
PDF print date: 01.11.2021								
Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851								
500 mi Ait. 6560 5651, Ait. 6564 5651								
Other information: COD 1585 m	ŋ/g							
CECTION 42. Dispessi sensiderations								
SECTION 13: Disposal considerations								
13.1 Waste treatment methods								
For the substance / mixture / residual amounts								
EC disposal code no.: The waste codes are recommendations based on the scheduled use or	this product							
Owing to the user's specific conditions for use and disposal, other waste								
allocated under certain circumstances. (2014/955/EU)	codes may be							
16 05 04 gases in pressure containers (including halons) containing ha	zardous substances							
Recommendation:								
Sewage disposal shall be discouraged.								
Pay attention to local and national official regulations.								
Take full aerosol cans to problem waste collection.								
Take emptied aerosol cans to valuable material collection.								
For contaminated packing material								
Pay attention to local and national official regulations.								
Recommendation: Do not perforate, cut up or weld uncleaned container.								
15 01 04 metallic packaging								
SECTION 14: Transport information								
General statements	1050							
14.1. UN number or ID number:	1950							
Transport by road/by rail (ADR/RID)								
14.2. UN proper shipping name:								
UN 1950 AEROSOLS 14.3. Transport hazard class(es):	2.2							
14.3. Hansport hazard class(es). 14.4. Packing group:	-							
Classification code:	5A							
LQ:	1L							
14.5. Environmental hazards:	Not applicable							
Tunnel restriction code:	E							
Transport by sea (IMDG-code)								
14.2. UN proper shipping name:								
AEROSOLS								
14.3. Transport hazard class(es):	2.2							
14.4. Packing group:	-							
EmS: Marine Pollutant:	F-D, S-U							
Marine Pollutant: n.a 14.5. Environmental hazards: Not applicable								
Transport by air (IATA)								
14.2. UN proper shipping name:								
Aerosols, non-flammable								
14.3. Transport hazard class(es):	2.2							
14.4. Packing group:	<u>-</u>							
14.5. Environmental hazards:	Not applicable							
14.6. Special precautions for user								
Persons employed in transporting dangerous goods must be trained.								
All persons involved in transporting must observe safety regulations.								
Precautions must be taken to prevent damage.								
14.7. Maritime transport in bulk according to IMO	instruments							
Freighted as packaged goods rather than in bulk, therefore not applicat	le.							
Minimum amount regulations have not been taken into account.								
Danger code and packing code on request.								
Comply with special provisions.								
SECTION 15. Pog	ulatory information							



Page 12 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): **REGULATION (EC) No 648/2004** n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Aerosol 3, H229	Classification based on the form or physical state.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Eye Irrit. — Eye irritation Aerosol — Aerosols STOT RE — Specific target organ toxicity - repeated exposure Acute Tox. — Acute toxicity - oral Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

1-16

5 %



Page 13 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Förch SAS ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard 77019 Melun Cedex Frankreich Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr Internet: www.forch.fr

(GB)

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0 Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30 E-Mail: info@foerch.at Internet: www.foerch.at

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be

Förch Polska Sp. z.o.o Międzyrzecze Górne 379 43-392 K/Bielska-Bialej Polen Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.I. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg Tel. +352 269 03267 Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr

Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es

Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82 E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechenland Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien Tel. +40 368 408192 Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien Tel. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711 Fax. +45 86 800617 E-Mail: info@foerch.dk Internet: www.foerch.dk

SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW Russland E-Mail: skynord.office@gmail.com

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

(GB)

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda Rua República da Bolivia No. 69, 1 esq 1500-544 Lisboa Portugal Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland Tel. +353871271473 Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114 Emergency telephone: +614 13 550 330 Email : sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv Förch, s.r.o. Dopravní 1314/1 104 00 Praha 10 – Uhøínìves Tschechien Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583 Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul Türkei Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) Bioconcentration factor BCF BSEF The International Bromine Council body weight bw CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level Derived No Effect Level DNEL DOC Dissolved organic carbon dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g.



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances FN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU European Union EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. general gen. Globally Harmonized System of Classification and Labelling of Chemicals GHS GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc Kow octanol-water partition coefficient International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. no data available n.d.a. NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm **PVC** Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility

These statements were made by:

(GB)



B Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 22.02.2019 / 0007 Valid from: 01.11.2021 PDF print date: 01.11.2021 Thread-cutting Fluid DVGW 300 ml Art.: 6580 5851, Art.: 6584 5851

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{C}}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.