

Page 1 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Car care

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199

Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements



B R

Page 2 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P403+P233-Store in a well-ventilated place. Keep container tightly closed. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

Propan-2-ol

1-methoxy-2-propanol

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Aerosol

. 10.000	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	
content %	60-95
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225
	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	200-661-7
CAS	67-63-0
content %	1-<10



Page 3 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319
	STOT SE 3, H336

1-methoxy-2-propanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119457435-35-XXXX
Index	603-064-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	203-539-1
CAS	107-98-2
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	STOT SE 3, H336

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Vapours may cause drowsiness and dizziness.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

The following may occur:

Irritation of the skin.

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

The following may occur:

Irritation of the eyes

Ingestion

Medical attention necessary.

Do not induce vomiting.

Danger of aspiration.

The following may occur:

Headaches

Nausea

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder

Large fire:

Alcohol resistant foam

Water jet spray

Unsuitable extinguishing media

n.c

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:



Page 4 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Danger of bursting (explosion) when heated

Oxides of carbon

Explosive vapour/air or gas/air mixtures.

Toxic gases

Vapours heavier than air.

5.3 Advice for firefighters

For personal protective equipment see Section 8. Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Only from a specialist.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Keep away from sources of ignition - Do not smoke.

Ensure good ventilation.

Observe directions on label and instructions for use.

Do not use the product in enclosed spaces.

Do not use on hot surfaces.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.



·BR.

Page 5 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1000 mg/m3

Chemical Name	Hydrocarbons, C	C6-C7, n-alkanes, isoalkanes, cyclics	s, <5% n-nexane		Content %:60-
VEL-TWA: 1000 mg/m3		WEL-STEL:			
Monitoring procedures:	-	Compur - KITA-187 S (551 174)	011 : (11	(OF)	DOD (I I
BMGV:			Other information: (paragraphs 84-87, El		o RCP-method,
Chemical Name	Hydrocarbons, 0	C6-C7, n-alkanes, isoalkanes, cyclics	s, <5% n-hexane		Content %:60-
DELV-8h: 100 ppm (573 mg/m3)	("Stoddard solvent	", OELV-15min:			
White spirit])					
Monitoring procedures:	-	Compur - KITA-187 S (551 174)	011 : (11		
BLV:			Other information: -		
Chemical Name	Propan-2-ol				Content %:1-<
VEL-TWA: 400 ppm (999 mg/m3	3)	WEL-STEL: 500 ppm (1250 n	ng/m3)		
Nonitoring procedures:	-	Draeger - Alcohol 25/a i-Propanol	(81 01 631)		
	-	Compur - KITA-122 SA(C) (549 27	' 7)		
	-	Compur - KITA-150 U (550 382)			
		DFG (D) (Loesungsmittelgemische		ktures 6) - 2	2013, 2002 - EU
	-	project BC/CEN/ENTR/000/2002-1			
	-	NIOSH 1400 (ALCOHOLS I) - 199			
	-	NIOSH 2549 (VOLATILE ORGANI		EENING))	- 1996
1101	-	Draeger - Alcohol 100/a (CH 29 70			
MGV:			Other information: -		
Chemical Name	Propan-2-ol				Content %:1-<
DELV-8h: 200 ppm		OELV-15min: 400 ppm			
Ionitoring procedures:	-	Draeger - Alcohol 25/a i-Propanol	(81 01 631)		
Monitoring procedures:		Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27		·	
fonitoring procedures:	- - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382)	77)	·	
Monitoring procedures:	- - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische	(77) e), DFG (E) (Solvent mix	ktures 6) - 2	2013, 2002 - EU
Monitoring procedures:	- - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1	(77) e), DFG (E) (Solvent mix 16 card 66-3 (2004)	ktures 6) - 2	2013, 2002 - EU
Monitoring procedures:	- - - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199	(27) E), DFG (E) (Solvent mix 16 card 66-3 (2004) 4		
fonitoring procedures:	- - - - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI	(27) E), DFG (E) (Solvent mix 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR		
•	- - - - - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199	27) 2), DFG (E) (Solvent mix 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR 21)	EENING))	
•	<u>'</u>	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70	27) 2), DFG (E) (Solvent mix 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR 21)		
LV: 40 mg/l (acetone, U, d) (AC	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70	27) 29), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 21) Other information:	EENING))	- 1996
LV: 40 mg/l (acetone, U, d) (AC	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70	27) 29), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 21) Other information:	EENING))	- 1996
LV: 40 mg/l (acetone, U, d) (AC Chemical Name /EL-TWA: 100 ppm (375 mg/m3	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 panol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU)	e), DFG (E) (Solvent mix 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR 01) Other information: S	Sk	- 1996 Content %:1-
LV: 40 mg/l (acetone, U, d) (AC Chemical Name /EL-TWA: 100 ppm (375 mg/m3	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 panol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: S g/m3) (WEL), 150 ppm ination of glycol ethers (Sk (1-methoxy-	- 1996 Content %:12-propanol, 2-
LV: 40 mg/l (acetone, U, d) (AC Chemical Name /EL-TWA: 100 ppm (375 mg/m3	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 panol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 1C COMPOUNDS (SCR) 11) 1 Other information: Security (SCR) 12(ma) (WEL), 150 ppm 15 ination of glycol ethers (be method / Gas chromation)	Sk (1-methoxy-	- 1996 Content %:12-propanol, 2-
LV: 40 mg/l (acetone, U, d) (AC Chemical Name /EL-TWA: 100 ppm (375 mg/m3	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 1C COMPOUNDS (SCR) 11) 1 Other information: S 12 13 14 15 16 17 17 18 18 19 19 19 10 10 11 11 11 12 13 14 15 16 16 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	Sk (1-methoxy-	- 1996 Content %:12-propanol, 2-
SLV: 40 mg/l (acetone, U, d) (AC Chemical Name VEL-TWA: 100 ppm (375 mg/m3	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS)	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003	Sk (1-methoxy-atography)	- 1996 Content %:12-propanol, 2-
LV: 40 mg/l (acetone, U, d) (AC Chemical Name VEL-TWA: 100 ppm (375 mg/m3) fonitoring procedures:	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromation card 12-1 (2004) - 2003 methyl Ethers/Acetates)	Sk (1-methoxy-atography)	- 1996 Content %:12-propanol, 2-
LV: 40 mg/l (acetone, U, d) (AC Chemical Name VEL-TWA: 100 ppm (375 mg/m3) fonitoring procedures:	1-methoxy-2-pro 3) (WEL, EU) - - -	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003	Sk (1-methoxy-atography)	- 1996 Content %:1- -2-propanol, 2- - 1989 - EU
Chemical Name VEL-TWA: 100 ppm (375 mg/m3 Ionitoring procedures: MGV: Chemical Name	1-methoxy-2-pro	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 01) Other information: S g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chroma) 16 card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: S	Sk (1-methoxy-atography)	- 1996 Content %:1- -2-propanol, 2- - 1989 - EU
Chemical Name Monitoring procedures: Chemical Name Monitoring procedures: Chemical Name Chemical Name Chemical Name Chemical Name Chemical Name	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: S g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromation card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: S mg/m3) (Propylene	Sk (1-methoxy-atography)	- 1996 Content %:1- -2-propanol, 2- - 1989 - EU
Chemical Name VEL-TWA: 100 ppm (375 mg/m3 Monitoring procedures: CMGV: Chemical Name DELV-8h: 100 ppm (375 mg/m3) nonomethyl ether) (OELV-8h, EU)	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 Depanol WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono Depanol OELV-15min: 150 ppm (568 r glycol monomethyl ether) (OEL'	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 11) Other information: S g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromation are card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: S mg/m3) (Propylene V-15min, EU)	Sk (1-methoxy-atography)) - 1993 Sk (WEL)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-
BLV: 40 mg/l (acetone, U, d) (ACC) Chemical Name WEL-TWA: 100 ppm (375 mg/m3 Monitoring procedures: BMGV: Chemical Name DELV-8h: 100 ppm (375 mg/m3) nonomethyl ether) (OELV-8h, EU)	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 DEPART OF THE STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono DEPART OF THE STEL STEL STEL STEL STEL STEL STEL STE	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 IC COMPOUNDS (SCR) 21) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: g/m3) (Propylene V-15min, EU) ination of glycol ethers (Sk (1-methoxy-atography)) - 1993 Sk (WEL)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-
BLV: 40 mg/l (acetone, U, d) (ACC) Chemical Name VEL-TWA: 100 ppm (375 mg/m3/donitoring procedures: BMGV: Chemical Name DELV-8h: 100 ppm (375 mg/m3/donomethyl ether) (OELV-8h, EU)	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 DEPART OF THE STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono DELV-15min: 150 ppm (568 r glycol monomethyl ether) (OEL' INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul glycol monomethyl ether) (OEL' INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul ethoxyethanol) in air - Charcoal tul	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 1C COMPOUNDS (SCR) 21) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromation are card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: mg/m3) (Propylene V-15min, EU) ination of glycol ethers (be method / Gas chromation are card 12-1) ination of glycol ethers (be method / Gas chromation)	Sk (1-methoxy-atography)) - 1993 Sk (WEL)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-
BLV: 40 mg/l (acetone, U, d) (ACC) Chemical Name WEL-TWA: 100 ppm (375 mg/m3 Monitoring procedures: BMGV: Chemical Name DELV-8h: 100 ppm (375 mg/m3) nonomethyl ether) (OELV-8h, EU)	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 DPANOL WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono DPANOL OELV-15min: 150 ppm (568 rg glycol monomethyl ether) (OEL' INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 1C COMPOUNDS (SCR) 21) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: mg/m3) (Propylene V-15min, EU) ination of glycol ethers (be method / Gas chromatic card 12-1 (2004)	Sk (1-methoxy-atography)) - 1993 Sk (WEL)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-
Chemical Name VEL-TWA: 100 ppm (375 mg/m3 Monitoring procedures: BMGV:	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 DPANOL WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono DPANOL OELV-15min: 150 ppm (568 r glycol monomethyl ether) (OEL* INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS)	e), DFG (E) (Solvent mix) 16 card 66-3 (2004) 4 1C COMPOUNDS (SCR 01) Other information: g/m3) (WEL), 150 ppm ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003 methyl Ethers/Acetates) Other information: g/m3) (Propylene V-15min, EU) ination of glycol ethers (be method / Gas chromatic card 12-1 (2004) - 2003	Sk (1-methoxy-atography)) - 1993 Sk (WEL) (1-methoxy-atography)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-
BLV: 40 mg/l (acetone, U, d) (ACC) Chemical Name VEL-TWA: 100 ppm (375 mg/m3/donitoring procedures: BMGV: Chemical Name DELV-8h: 100 ppm (375 mg/m3/donomethyl ether) (OELV-8h, EU)	1-methoxy-2-pro 3) (WEL, EU) 1-methoxy-2-pro (Propylene glycol	Draeger - Alcohol 25/a i-Propanol Compur - KITA-122 SA(C) (549 27 Compur - KITA-150 U (550 382) DFG (D) (Loesungsmittelgemische project BC/CEN/ENTR/000/2002-1 NIOSH 1400 (ALCOHOLS I) - 199 NIOSH 2549 (VOLATILE ORGANI Draeger - Alcohol 100/a (CH 29 70 DPANOL WEL-STEL: 150 ppm (560 mg (568 mg/m3) (EU) INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1 NIOSH 2554 (GLYCOL ETHERS) OSHA 99 (Propylene Glycol Mono DPANOL OELV-15min: 150 ppm (568 rg glycol monomethyl ether) (OEL' INSHT MTA/MA-017/A89 (Determ ethoxyethanol) in air - Charcoal tul project BC/CEN/ENTR/000/2002-1	e), DFG (E) (Solvent mix 16 card 66-3 (2004) 4 16 CCOMPOUNDS (SCR 201) Other information: September 16 card 12-1 (2004) Other information: September 17 (2004) Other information: September 18 (2004) Other information: September 18 (2004) Other information: September 19 (2004) Other informati	Sk (1-methoxy-atography)) - 1993 Sk (WEL) (1-methoxy-atography)	- 1996 Content %:12-propanol, 2 1989 - EU Content %:1-



Page 6 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	733	mg/kg bw/d	

Area of application	Exposure route / Environmental	Effect on health	Descriptor	Value	Unit	Note
	compartment					
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment,		PNEC	552	mg/kg dw	
	freshwater					
	Environment - sediment, marine		PNEC	552	mg/kg dw	
	Environment - soil		PNEC	28	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term, systemic effects	DNEL	319	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	89	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	888	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	500	mg/m3	

Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					11010
	compartment					
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - periodic release		PNEC	100	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	52,3	mg/kg dw	
	Environment - sediment, marine		PNEC	5,2	mg/kg dw	
	Environment - soil		PNEC	4,59	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	33	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	78	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	



Page 7 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Consumer	Human - inhalation	Long term, systemic effects	DNEL	43,9	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	369	mg/m3	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	3,3	mg/kg	
Workers / employees	Human - oral	Long term, systemic effects	DNEL	183	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	553,5	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	553,5	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- © OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE).
- OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).



® (RL)

Page 8 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Skin protection - Hand protection: Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm:

0,3

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0.7

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Solvent resistant protection clothing (EN 13034)

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter AX (EN 14387), code colour brown.

If applicable

Protective respirator with independent air supply.

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Colourless Odour: Characteristic

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

Flammability: Does not apply to aerosols.

Lower explosion limit: 0,6 Vol-% Upper explosion limit: 12 Vol-% Flash point: -9 °C 270 °C Auto-ignition temperature:

Decomposition temperature: There is no information available on this parameter.

Kinematic viscosity: Does not apply to aerosols. Solubility: Soluble

Partition coefficient n-octanol/water (log value):

Does not apply to mixtures. Vapour pressure: 7500 hPa (20°C)

Density and/or relative density: 0,72 g/cm3 (20°C) Relative vapour density: Does not apply to aerosols. Particle characteristics: Does not apply to aerosols.

9.2 Other information

Explosives: Product is not explosive. Possible build up of explosive/highly

flammable vapour/air mixture.

Oxidising liquids: No Bulk density:

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.



Page 9 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021

PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Pressure increase will result in danger of bursting. Keep away from sources of ignition - Do not smoke. Heating, open flame, ignition sources

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Electronic Switch'n'Contact Clean R570						
400 ml Art.: 6710 0880, Art.: 67	14 0880					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	>5840	mg/kg	Rat			
Acute toxicity, by dermal route:	LD50	>2920	mg/kg	Rat			
Acute toxicity, by inhalation:	LC50	25,2	mg/l/4h	Rat		Vapours	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Skin Irrit. 2	
					Dermal		
					Irritation/Corrosion)		
Serious eye damage/irritation:						Slightly irritant	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)	
sensitisation:					Sensitisation)		
Specific target organ toxicity -					·	May cause	
single exposure (STOT-SE):						drowsiness or	
						dizziness.	
Aspiration hazard:						Yes	
Symptoms:						may cause	
						headaches and	
						vertigo.	

Propan-2-ol							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)		
Acute toxicity, by dermal route:	LD50	12800-13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)		
Acute toxicity, by inhalation:	LC50	> 25	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours	
Acute toxicity, by inhalation:	LC50	46600	mg/l/4h	Rat		Aerosol	



Page 10 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:	_				OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s):
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness , vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat	·	Vapours (OECD 451)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	Regulation (EC) 440/2008 B.3 (ACUTE TOXICITY (DERMAL)	
Acute toxicity, by inhalation:	LC0	7	mg/l/6h		OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSI ON)	Not irritant
Serious eye damage/irritation:				Rabbit	Regulation (EC) 440/2008 B.5 (ACUTE EYE IRRITATION/CORROSI ON)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	Not sensitizising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative



Page 11 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Specific target organ toxicity -			May cause
single exposure (STOT-SE):			drowsiness or
onigio exposure (e re r ez).			dizziness.,
			STOT SE 3,
			H336
Symptoms:			drowsiness,
			unconsciousness
			, headaches,
			drowsiness,
			mucous
			membrane
			irritation,
			dizziness,
			nausea and
			vomiting.

11.2. Information on other hazards

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Electronic Switch'n'Con	tact Clean R57	0					
400 ml Art.: 6710 0880, A	rt.: 6714 0880						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							Product is slightly volatile.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect Endpoint Time Value Unit Organism Test method Notes							



Page 12 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

12.7. Other adverse effects:							Product floats on the water surface.
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Goldforelle (Oncorhynchus aguabonita)
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss	QSAR	,
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriell a subcapitata	,	
12.2. Persistence and degradability:		28d	100	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable

Propan-2-ol Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative	BCF	Time	3,2	Oint	Organism	T C St III Ctilou	Low
potential:							LOW
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Slight
12.4. Mobility in soil:	Koc		1,1			,	Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
Other information:	ThOD		2,4	g/g	P = = = =		
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			. 13101011003
Other information:	BOD		1171	mg/g			



Page 13 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	6812	mg/l	Leuciscus idus	DIN 38412 T.15	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		0,2-1				High
12.1. Toxicity to fish:	LC50	96h	20800	mg/l	Pimephales promelas		ASTM
12.1. Toxicity to fish:	LC50	96h	>=1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.3. Bioaccumulative potential:	BCF		<100			,	Low
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.1. Toxicity to algae:	IC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	90	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		~-0,49				Not to be expected
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:						,	Does not contai any organically bound halogens which can contribute to the AOX value in waste water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances Recycling

SECTION 14: Transport information

General statements

14.1. UN number or ID number:



Page 14 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name: UN 1950 AEROSOLS

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

10. 11

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS (NAPHTHA (PETROLEUM))

Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es):
2.1
14.4. Packing group:

14.5. Environmental hazards: Not applicable



Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

99 %

Directive 2010/75/EU (VOC):

U/19/EU (VUC).

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons

Observe incident regulations.









B R

Page 15 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aguatic Chronic — Hazardous to the aguatic environment - chronic

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Eye Irrit. — Eye irritation

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.



Page 16 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Förch SAS

ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard

77019 Melun Cedex Frankreich

Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr Internet: www.forch.fr Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg Tel. +352 269 03267 Fax +352 269 03368 E-Mail: info@forch.fr

Internet: www.forch.fr

S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien Tel. +40 368 408192

Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz Tel. +41 61 8262031

Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien Tel. +385 1 2912900 Fax. +385 1 2912901

Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0

Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30

E-Mail: info@foerch.at Internet: www.foerch.at

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76

Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk

Internet: www.foerch.dk

Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82

E-Mail: sales@ziebe.co.uk

Internet: www.ziebe.co.uk

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be

Internet: www.lhommetools.be

Förch Polska Sp. z.o.o Międzyrzecze Górne 379

43-392 K/Bielska-Bialej Polen Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.I. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien

Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechaland

Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW Russland

E-Mail: skynord.office@gmail.com

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348

Fax. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is



Page 17 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei

Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin

Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492

E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda

Rua República da Bolivia No. 69, 1 esq

1500-544 Lisboa Portugal

Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29

Irland Tel. +353871271473 Förch Sverige AB Brännarevägen 1 151 55 Södertälje

Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114

Emergency telephone: +614 13 550 330

Email: sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland

Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv

Förch, s.r.o. Dopravní 1314/1

104 00 Praha 10 - Uhøínìves

Tschechien

Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd

Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand

Tel: +64 21 081 30780 / +64 21 024 05583

Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3

34524 Beylikdüzü / Istanbul Türkei

Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Article number Art., Art. no.

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

Bioconcentration factor BCF

BSEF The International Bromine Council

body weight bw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level Derived No Effect Level DNEL DOC Dissolved organic carbon

dry weight dw

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.



Page 18 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021 PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570 400 ml Art.: 6710 0880, Art.: 6714 0880

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

European Economic Community EEC

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

FN **Furopean Norms**

EPA United States Environmental Protection Agency (United States of America)

ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera ΕU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax number Fax. general gen.

Globally Harmonized System of Classification and Labelling of Chemicals GHS

GWP Global warming potential

Adsorption coefficient of organic carbon in the soil Koc

Kow octanol-water partition coefficient

International Agency for Research on Cancer **IARC** IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient

Limited Quantities LQ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable not available n.av. not checked n.c. no data available n.d.a.

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic orq.

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PΕ Polyethylene

PNEC Predicted No Effect Concentration

parts per million ppm **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No.

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

Volatile organic compounds VOC

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:



Page 19 of 19

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0023

Replacing version dated / version: 22.02.2019 / 0022

Valid from: 01.11.2021

PDF print date: 01.11.2021

Electronic Switch'n'Contact Clean R570

400 ml Art.: 6710 0880, Art.: 6714 0880 Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90 $\ensuremath{\texttt{©}}$ by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.