

Page 1 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199

Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Resp. Sens. 1 H334-May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430



Danger

H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.

P261-Avoid breathing vapours or spray. P284-Wear respiratory protection.

P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311-If experiencing respiratory symptoms: Call a POISON CENTER / doctor.

EUH204-Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Mixture of non-dangerous components with the substances drawn up in the following.

3.1 Substances

n.a. **3.2 Mixtures**

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226
	Acute Tox. 4, H332
	Acute Tox. 4, H312
	Skin Irrit. 2, H315

4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	202-966-0
CAS	101-68-8
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2 H373



Page 3 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 %
	Eye Irrit. 2, H319: >=5 %
	Resp. Sens. 1, H334: >=0,1 %
	STOT SE 3, H335: >=5 %

o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	227-534-9
CAS	5873-54-1
content %	0,01-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332
	Skin Irrit. 2, H315
	Eye Irrit. 2, H319
	Resp. Sens. 1, H334
	Skin Sens. 1, H317
	Carc. 2, H351
	STOT SE 3, H335
	STOT RE 2, H373
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 %
•	Eye Irrit. 2, H319: >=5 %
	Resp. Sens. 1, H334: >=0,1 %
	STOT SE 3, H335: >=5 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly with soap and water - consult doctor if necessary.

Remove contaminated clothing immediately.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.

Irritation of the respiratory tract

Allergic contact eczema

4.3 Indication of any immediate medical attention and special treatment needed

n.c

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder



- (B

Page 4 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Water jet spray

Unsuitable extinguishing media

n.c.

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Oxides of nitrogen Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Only store at temperatures from > 0° C to < 35° C.



· (B) ·

Page 5 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Environmental compartment

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

•						
® Chemical Name	Xylene			Content ^o	%:1-5	
WEL-TWA: 220 mg/m3 (50 p		VEL-STEL: 100 ppm (441 n	ng/m3 (WEL), 100 ppm			
(221 mg/m3) (EU)		442 mg/m3) (EU)	`			
Monitoring procedures:	- Drae	eger - Xylene 10/a (67 33 161 npur - KITA-143 SA (550 325)			
		npur - KITA-143 SA (550 525 npur - KITA-143 SB (505 998				
		HT MTA/MA-030/A92 (Deterr		carbons (benzene, tol	luene	
		lbenzene, p-xylene, 1,2,4-trin				
- chromatography) - 1992 - EU project BC/CEN/ÉNTR/000/2002-16 card 47-1 (2004)						
- NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003						
	- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999					
BMGV: 650 mmol methyl hip						
, p- or mixed isomers) (BMGV)		ine, post stillt (Aylene, 0-, III-	Other information.	ok (VVEL)		
® Chemical Name	4,4'-methylenedipheny	ul diisocvanate		Content %	.·∩ 1_<1	
WEL-TWA: 0,02 mg/m3 (Iso	cvanates, all (as -NCO)) V	VEL-STEL: 0,07 mg/m3 (Iso	ocvanates, all (as -NCO))).U, I-~I	
Monitoring procedures:		16702 (Workplace air quality		socyanate groups in air	r using	
0 ,	- 2-(1	-methoxyphenylpiperazine ar	d liquid chromatography)	- 2007	•	
		HS 25/4 (Organic isocyanates				
		-methoxyphenylpiperazine co				
		nto impingers and analysis us		id chromatography) - 2	2015 -	
		project BC/CEN/ENTR/000/2 SH 5521 (ISOCYANATES, M				
		SH 5522 (ISOCYANATES) -				
		SH 5525 (ISOCYANATES, T				
		HA 18 (Diisocyanates 2,4-TDI				
	- OSI	HA 47 (Methylene Bisphenyl I				
BMGV: 1 µmol isocyanate-de period of exposure)	erived diamine/mol creatinine	in urine (At the end of the	Other information: S NCO))	Sen (Isocyanates, all (a	is -	
Chemical Name	o-(p-isocyanatobenzyl)phenyl isocyanate		Content %		
WEL-TWA: 0,02 mg/m3 (Iso	cyanates, all (as -NCO)) V	VEL-STEL: 0,07 mg/m3 (Iso	ocyanates, all (as -NCO))			
Monitoring procedures:			0" . (" () (I I I I		
BMGV: 1 µmol isocyanate-doperiod of exposure)	erived diamine/moi creatinine	in urine (At the end of the	NCO))	Sen (Isocyanates, all (a	ıs -	
Chemical Name	Diisononyl phthalate			Conten	nt %:	
WEL-TWA: 5 mg/m3	V	VEL-STEL:				
Monitoring procedures: BMGV:			Other information: -			
			Other information			
© Chemical Name	Carbon black	NEL OTEL 7 ' 0		Conten	nt %:	
WEL-TWA: 3,5 mg/m3		VEL-STEL: 7 mg/m3				
Monitoring procedures: BMGV:			Other information: -			
	O-lain I		Juici information.		-+ 0/	
Chemical Name WEL-TWA: 4 mg/m3 (respiral	Calcium carbonate	VEL-STEL:		Conten	It %:	
(total inhalable dust)	ible dust), to my/ms V	VLL-GILL				
Monitoring procedures:				1		
BMGV:			Other information: -			
Xylene						
Area of application	Exposure route /	Effect on health	Descriptor Value	Unit Note	e	



Page 6 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg	
	Environment - soil		PNEC	2,31	mg/kg	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, marine		PNEC	12,46	mg/kg	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	

4,4'-methylenediphenyl of Area of application	Exposure route /	Descriptor	Value	Unit	Note	
	Environmental	Effect on health				
	compartment					
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dw	
	Environment - sewage		PNEC	1	mg/l	
	treatment plant					
	Environment - water,		PNEC	10	mg/l	
	sporadic (intermittent)					
	release					
Consumer	Human - dermal	Short term, systemic	DNEL	25	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Short term, systemic	DNEL	0,05	mg/m3	
_		effects				
Consumer	Human - oral	Short term, systemic	DNEL	20	mg/kg bw/d	
	<u> </u>	effects	D.V.E.	4=0		
Consumer	Human - dermal	Short term, local	DNEL	17,2	mg/cm2	
Consumor	I luman inhalation	effects	DNE	0.05		
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, systemic	DNEL	0.025	mg/m3	
Consumer	Human - imalation	effects	DINEL	0,025	mg/ms	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic	DNEL	50	mg/kg bw/d	
	23	effects	· · - <u>-</u>			
Workers / employees	Human - inhalation	Short term, systemic	DNEL	0,1	mg/m3	
		effects		']	
Workers / employees	Human - dermal	Short term, local	DNEL	28,7	mg/cm2	
		effects				
Workers / employees	Human - inhalation	Short term, local	DNEL	0,1	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, systemic	DNEL	0,05	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

o-(p-isocyanatobenzyl)phenyl isocyanate



Page 7 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
	Environment - soil		PNEC	1	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	1	mg/l	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg body weight/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm2	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	al DNEL 28,7 mg/cm2		mg/cm2	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

Diisononyl phthalate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - soil		PNEC	30	mg/kg	
	Environment - oral (animal feed)		PNEC	150	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15,3	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	220	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,4	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	366	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	51,72	mg/m3	

Carbon black						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	1	mg/l	
	Environment - marine		PNEC	0,1	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,06	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

^{(8) =} Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the



Page 8 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Rubber gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0.35

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.



Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Solid, Pastelike

Colour: Black

Characteristic Odour:

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: 270 °C Flammability: Flammable Lower explosion limit: 0,4 Vol-% 2,9 Vol-% Upper explosion limit: Flash point: 101 °C

Auto-ignition temperature: 300 °C

Decomposition temperature: There is no information available on this parameter.

Mixture is non-soluble (in water).

Kinematic viscosity: Does not apply to solids.

Solubility: Insoluble Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 1,221 g/cm3

Relative vapour density: Does not apply to solids.

9.2 Other information

Explosives: Product is not explosive.

Oxidizing solids: No 1,1 % Solvents content:

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

None known

10.5 Incompatible materials

See also section 7.

None known

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

ASK-Clean&Stick K106 Windscreen Adhesive

366 g Art.: 6600 6430, Art.: 660	4 6430					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value,
						Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value,
						Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.



Page 10 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

Respiratory or skin	n.d.a.
sensitisation:	
Germ cell mutagenicity:	n.d.a.
Carcinogenicity:	n.d.a.
Reproductive toxicity:	n.d.a.
Specific target organ toxicity -	n.d.a.
single exposure (STOT-SE):	
Specific target organ toxicity -	n.d.a.
repeated exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.

Xylene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2840-3523	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>1700	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	21,7	mg/l/4h	Rat		Vapours, Does
						not conform with
						EU classification.
Skin corrosion/irritation:				Rabbit		Irritant
Serious eye damage/irritation:				Rabbit		Slightly irritant
Respiratory or skin					(Patch-Test)	Negative
sensitisation:						
Symptoms:						breathing
						difficulties,
						drying of the
						skin.,
						drowsiness,
						unconsciousness
						, burning of the
						membranes of
						the nose and
						throat, vomiting,
						skin afflictions,
						heart/circulatory
						disorders,
						coughing,
						headaches,
						drowsiness,
						dizziness,
						nausea

4,4'-methylenediphenyl diisocy	/anate					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC)	
					440/2008 B.1 (ACUTE	
					ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2,24	mg/l/4h	Rat	OECD 403 (Acute	Aerosol
					Inhalation Toxicity)	
Acute toxicity, by inhalation:	LC50	0,368	mg/l/4h	Rat	OECD 403 (Acute	Does not
					Inhalation Toxicity)	conform with EU
						classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Mouse	OECD 429 (Skin	Yes (skin
sensitisation:					Sensitisation - Local	contact),
					Lymph Node Assay)	Analogous
						conclusion



Page 11 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation)
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	4	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.
Symptoms:						respiratory distress, coughing, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract, Target organ(s): respiratory system

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	0,387	mg/l/4h	Rat		Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant, Analogous conclusion
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact), Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (inhalation), Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Limited evidence of a carcinogenic effect.
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative



Page 12 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

Symptoms:		asthmatic symptoms, mucous membrane irritation
Specific target organ toxicity - single exposure (STOT-SE), inhalative:		Target organ(s): respiratory tract, Irritant

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>4,4	mg/l/4h	Rat	Limit-Test	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	Regulation (EC) 440/2008 B.6 (SKIN SENSITISATION)	No (skin contact)
Germ cell mutagenicity:					(Ames-Test)	Negative
Symptoms:						diarrhoea, nausea and vomiting.

Carbon black						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3000	mg/kg			
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Carcinogenicity:				Mouse		Negative
Specific target organ toxicity -	NOEL	0,0011	mg/l			References,
repeated exposure (STOT-RE):						Target organ(s):
						lung90d
Aspiration hazard:						No
Specific target organ toxicity -	NOAEL	137	mg/kg	Mouse		
repeated exposure (STOT-RE),						
oral:						
Specific target organ toxicity -	NOAEL	52	mg/kg	Rat		
repeated exposure (STOT-RE),						
oral:						

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	



Page 13 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Serious eye damage/irritation:	Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:			No (skin contact)
Germ cell mutagenicity:		in vitro	Negative
Carcinogenicity:			Negative, administered as Ca-lactate
Reproductive toxicity:			Negative, administered as Ca-carbonate

11.2. Information on other hazards

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting properties:						Does not apply		
						to mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse effects		
						on health.		

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains
							no AOX.
Other information:							DOC-elimination
							degree(complex
							ng organic
							substance)>=
							80%/28d: n.a.

Xylene										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	86	mg/l	Leuciscus idus					
12.1. Toxicity to fish:	LC50	96h	8,2	mg/l	Oncorhynchus					
					mykiss					
12.1. Toxicity to daphnia:	EC50	24h	75,5	mg/l	Daphnia magna					



Page 14 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

12.1. Toxicity to algae:	IC50	72h	10	mg/l		
12.2. Persistence and	1030	7211	10	1119/1		Readily
degradability:						biodegradable
12.3. Bioaccumulative	Log Pow		>3			
potential:						
12.3. Bioaccumulative	BCF		0,6-15			
potential:						

4,4'-methylenediphenyl of Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC0	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	1,5	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide) According to experience available to date polycarbamide i inert and non-degradable.
12.2. Persistence and degradability:	BOD	28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction produce with a high melting point (polycarbamide According to experience available to date polycarbamide inert and nondegradable.



Page 15 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	Log Pow		4,51- 5,22			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other information:						,,	Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Toxicity to annelids:	EC50	14d	>= 1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	> 1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion



Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide)., Analogous conclusion
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected, Analogous conclusion
12.5. Results of PBT and vPvB assessment						,	No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL	14d	>1000		Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests)	Analogous conclusion

Diisononyl phthalate Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
	LC50	96h	>102				NOTES
12.1. Toxicity to fish:				mg/l	Brachydanio rerio	92/69/EC	
12.1. Toxicity to daphnia:	EC50	48h	>=74	mg/l	Daphnia magna	84/449/EEC C.2	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>=100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	88	mg/l	Scenedesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	>88	mg/l	Scenedesmus subspicatus	84/449/EEC C.3	
12.2. Persistence and degradability:		28d	81	%	activated sludge	Regulation (EC) 440/2008 C.4-C (DETERMINATIO N OF 'READY' BIODEGRADABILI TY - CO2 EVOLUTION TEST)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		8,8-9,7			OECD 117 (Partition Coefficient (n- octanol/water) - HPLC method)	Analogous conclusion
12.3. Bioaccumulative potential:	BCF	14d	<3				Analogous conclusion
12.4. Mobility in soil:	Koc		>5000				
12.4. Mobility in soil:	H (Henry)		0,00000 149	atm*m3/m			



Page 17 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009 Valid from: 21.02.2022

PDF print date: 21.02.2022

Toxicity to bacteria:	EC50	30min	>83,9	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))
Other organisms:	NOEC/NOEL	56d	>982,4	mg/kg	Eisenia foetida	
Other organisms:	LC50	14d	>7372	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)

Carbon black							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:							Insoluble, Product floats on the water surface.
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>5600	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	3d	10000	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Not biodegradable
12.3. Bioaccumulative potential:							Not to be expected
Toxicity to bacteria:	EC0	3h	>=800	mg/l	activated sludge	Regulation (EC) 440/2008 C.22 (SOIL MICROORGANIS MS - CARBON TRANSFORMATI ON TEST)	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.3. Bioaccumulative potential:						,	Not relevant for inorganic substances.



Page 18 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

12.4. Mobility in soil:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)



Page 19 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

n.a.

14.4. Packing group:

n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2010/75/EU (VOC):

13,4 g/l

REGULATION (EC) No 648/2004

n.a

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Resp. Sens. 1, H334	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Resp. Sens. — Respiratory sensitization

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - dermal

Skin Irrit. — Skin irritation Eye Irrit. — Eye irritation



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Skin Sens. — Skin sensitization

Carc. — Carcinogenicity

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

STOT RE — Specific target organ toxicity - repeated exposure

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard

77019 Melun Cedex Frankreich Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr

Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg Tel. +352 269 03267

Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien

Tel. +40 368 408192 Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz

Internet: www.forch.fr

Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch

Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Šofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg

Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien

Tel. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich

Tel. +43 662 875574-0

Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30

E-Mail: info@foerch.at Internet: www.foerch.at Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada)

Spanien

Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711

Fax. +45 86 800617 E-Mail: info@foerch.dk Internet: www.foerch.dk

Lhomme Tools & Fasteners BV

Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien

Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82

E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW

Russland

E-Mail: skynord.office@gmail.com



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

Förch Polska Sp. z.o.o Miêdzyrzecze Górne 379 43-392 K/Bielska-Bialej

Polen

Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.l.

Via Antonio Stradivari 4 39100 Bolzano (BZ)

Italien

Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei

Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A

1236 Trzin Slowenien

Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda

1500-544 Lisboa Portugal

Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt

Rua República da Bolivia No. 69, 1 esq

Total Consumables Ltd Coolnafearagh

Monasterevin Co. Kildare W34 TX29

Irland

Tel. +353871271473

Vardalis SM P.C. Ethnikis Antistasis 62

57007 Chalkidona-Thessaloniki

Griechenland

Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande

Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl

Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden

Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114

Emergency telephone: +614 13 550 330

Email: sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland

Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn

Tel. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

Förch, s.r.o. Dopravní 1314/1

104 00 Praha 10 - Uhříněves

Tschechien

Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive

East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583

Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul

Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to



Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration



Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.02.2022 / 0010

Replacing version dated / version: 01.11.2021 / 0009

Valid from: 21.02.2022 PDF print date: 21.02.2022

ASK-Clean&Stick K106 Windscreen Adhesive 366 g Art.: 6600 6430, Art.: 6604 6430

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.