

Page 1 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP)						
Hazard class	Hazard category	Hazard statement				
Aerosol	1	H222-Extremely flammable aerosol.				
Aerosol	1	H229-Pressurised container: May burst if heated.				

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor. Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed



Page 3 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher.

Unsuitable extinguishing media

None known

(GB)

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Possible build up of explosive/highly flammable vapour/air mixture. Oxides of carbon Formaldehyde Toxic gases Danger of bursting (explosion) when heated

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Full protection, if necessary. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces.



Page 4 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Store product closed and only in original packing. Not to be stored in gangways or stair wells. Observe special regulations for aerosols! Do not store with flammable or self-igniting materials. Keep protected from direct sunlight and temperatures over 50°C. Store in a well ventilated place. Store cool. Observe special storage conditions.

7.3 Specific end use(s)

(GB)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Butane	Content %:
WEL-TWA: 600 ppm (1450 mg/m3) WEL-STEL: 750 ppm (1810 mg/m3)	
Monitoring procedures:	- Compur - KITA-221 SA (549 459)	
	 OSHA PV2010 (n-Butane) - 1993 	
BMGV:	Other information:	
Chemical Name	Propane	Content %:
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:	
Monitoring procedures:	- Compur - KITA-125 SA (549 954)	
	 OSHA PV2077 (Propane) - 1990 	
BMGV:	Other information:	
Chemical Name	Dimethoxymethane	Content %:
WEL-TWA: 1000 ppm (3160 mg/m	3) WEL-STEL: 1250 ppm (3950 mg/m3)	
Monitoring procedures:		
BMGV:	Other information:	
Chemical Name	Isobutane	Content %:
WEL-TWA: 1000 ppm (EX) (ACGI	H) WEL-STEL:	
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)	
BMGV:	Other information:	

Dimethoxymethane	-				1	
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - water		PNEC	14,577	mg/l	
	Environment - sediment,		PNEC	1,4577	mg/l	
	marine					
	Environment - sediment,		PNEC	13,135	mg/kg dry	
	freshwater				weight	
	Environment - sediment,		PNEC	1,3135	mg/kg dry	
	marine				weight	
	Environment - soil		PNEC	4,6538	mg/kg dry	
					weight	
	Environment - sewage		PNEC	10000	mg/l	
	treatment plant				-	



Page 5 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Consumer	Human - oral	Long term, systemic effects	DNEL	9,6	mg/kg body weight/day
Consumer	Human - inhalation	Long term, systemic effects	DNEL	31,5	mg/m3
Consumer	Human - dermal	Long term, systemic effects	DNEL	5,7	mg/kg body weight/day
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	17,9	mg/kg body weight/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	126,6	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

(GB)

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). If applicable Protective gloves in butyl rubber (EN ISO 374). Protective gloves made of fluorocarbon rubber (EN ISO 374). Minimum layer thickness in mm: 0,5 Permeation time (penetration time) in minutes: 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:



Page 6 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

If OES or MEL is exceeded. Filter A P2 (EN 14387), code colour brown, white Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable

(GB)

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other guality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid. Colour: White Odour: Characteristic Melting point/freezing point: There is no information available on this parameter. Boiling point or initial boiling point and boiling range: There is no information available on this parameter. Flammability: Does not apply to aerosols. Lower explosion limit: There is no information available on this parameter. Upper explosion limit: There is no information available on this parameter. Flash point: -60 °C Auto-ignition temperature: Does not apply to aerosols. Decomposition temperature: There is no information available on this parameter. pH: Mixture is non-soluble (in water). Kinematic viscosity: Does not apply to aerosols There is no information available on this parameter. Solubility: Partition coefficient n-octanol/water (log value): Does not apply to mixtures. Vapour pressure: 2200 hPa (20°C) ~0,74 g/cm3 Density and/or relative density: Density and/or relative density: 0,85 g/ml (Active substance) Relative vapour density: Does not apply to aerosols. Particle characteristics Does not apply to aerosols. 9.2 Other information

No information available at present.

SECTION 10: Stability and reactivity

10.1 Reactivity The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. 10.3 Possibility of hazardous reactions No dangerous reactions are known. 10.4 Conditions to avoid See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting. 10.5 Incompatible materials See also section 7. Avoid contact with strong oxidizing agents. 10.6 Hazardous decomposition products See also section 5.2



Page 7 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019
Replacing version dated / version: 01.11.2021 / 0018
Valid from: 18.03.2022
PDF print date: 18.03.2022
Gasket Remover R580
300 ml Art.: 6490 4600, Art.: 6494 4600

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Butane	Endneir (Value	11	Ormoniem	Test methed	Nataa
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
				J	Mammalian	- J
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
Germ cen mutagementy.				Nat	Erythrocyte	Negative
A					Micronucleus Test)	N1
Aspiration hazard:	10150	04.004		5.		No
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Symptoms:					 <i>i</i>	ataxia, breathing
						difficulties,
						drowsiness.
						unconsciousnes
						. frostbite.
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.
Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		



Vapours

Vapours

Not irritant

Not irritant Not sensitizising

Negative

Negative

Negative

No

Page 8 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019
Replacing version dated / version: 01.11.2021 / 0018
Valid from: 18.03.2022
PDF print date: 18.03.2022
Gasket Remover R580
300 ml Art.: 6490 4600, Art.: 6494 4600

Acute toxicity, by inhalation:

Acute toxicity, by inhalation:

Serious eye damage/irritation:

Skin corrosion/irritation:

Germ cell mutagenicity:

Respiratory or skin sensitisation:

Carcinogenicity: Reproductive toxicity:

Aspiration hazard:

LOAEL

NOAEL

1000

2000

Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous
Skin corrosion/irritation:						conclusion Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:					, en eereening veel,	No
Symptoms:						breathing difficulties, unconsciousnes , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Dimethoxymethane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	6423	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	57	mg/l	Mouse	OECD 403 (Acute Inhalation Toxicity)	
A suite texisity, by inhelations		4000	(1/0)	D.1	• ·	\/

mg/l/6h

mg/l/6h

Rat

Rat

Salmonella

typhimurium

(Ames-Test)



Page 9 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Symptoms:		acidosis,
		respiratory
		distress,
		drowsiness,
		unconsciousness
		, diarrhoea,
		coughing,
		headaches,
		drowsiness,
		mucous membrane
		irritation, nausea and vomiting.,
		dizziness

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	-
Aspiration hazard:						No
Symptoms:						unconsciousne , frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

11.2. Information on other hazards

Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Endocrine disrupting properties:						Does not apply	
						to mixtures.	
Other information:						No other	
						relevant	
						information	
						available on	
						adverse effects	
						on health.	

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600 Toxicity / effect Value Unit Endpoint Time Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: 12.1. Toxicity to algae: n.d.a. n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a.



 Page 10 of 16
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019
 Replacing version dated / version: 01.11.2021 / 0018
 Valid from: 18.03.2022
 PDF print date: 18.03.2022
 Gasket Remover R580
 300 ml Art.: 6490 4600, Art.: 6494 4600

12.5. Results of PBT and vPvB assessment				n.d.a.
12.6. Endocrine disrupting properties:				Does not apply to mixtures.
12.7. Other adverse effects:				No information available on other adverse
				effects on the environment.
Other information:				DOC-elimination degree(complexi ng organic
				substance)>= 80%/28d: No
Other information:	AOX	0	%	According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LC50	96h	> 1000	mg/l	Brachydanio rerio	OECD 203 (Fish,	
,				5	,,	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	EC10	96h	>500	mg/l	Scenedesmus		
					subspicatus		
12.2. Persistence and			>80	%	·		Readily
degradability:							biodegradable
12.3. Bioaccumulative	Log Pow		0				0
potential:							
Toxicity to bacteria:	EC10	17h	3000	mg/l	Pseudomonas		
					putida		
Water solubility:			32,3	%			
,							
Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes



Page 11 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

12.3. Bioaccumulative potential:					A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l	
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l	
12.2. Persistence and degradability:					Readily biodegradable
12.5. Results of PBT					No PBT
and vPvB assessment					substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

(GB)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging Recycling

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements 14.1. UN number or ID number:	1950	
Transport by road/by rail (ADR/RID)	1900	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	•
14.4. Packing group:	-	•
Classification code:	5F	
LQ:	1L	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		
AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	•
EmS:	F-D, S-U	
Marine Pollutant:	n.a	
14.5. Environmental hazards:	Not applicable	
Transport by air (IATA)		
14.2. UN proper shipping name:		
Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	-
14.5. Environmental hazards:	Not applicable	



Page 12 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations. Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request. Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

	Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
			dangerous substances as	dangerous substances as
			referred to in Article 3(10) for the	referred to in Article 3(10) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
İ.	P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity	
			(tonnes) for the	(tonnes) for the	
			application of - Lower-tier	application of - Upper-tier	
			requirements	requirements	
18	Liquefied flammable	19	50	200	
	gases, Category 1 or 2				
	(including LPG) and				
	natural gas				

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

REGULATION (EC) No 648/2004

30 % and more aliphatic hydrocarbons

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2, 4, 5, 6, 7, 8, 9, 10, 13, 15

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

98,46 %



Page 13 of 16

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Aerosol — Aerosols

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard 77019 Melun Cedex Frankreich Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr Internet: www.forch.fr

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0 Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30 E-Mail: info@foerch.at Internet: www.foerch.at Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg Tel. +352 269 03267 Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr

Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien Tel. +40 368 408192 Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien Tel. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711 Fax. +45 86 800617 E-Mail: info@foerch.dk Internet: www.foerch.dk



Page 14 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be

(GB)

Förch Polska Sp. z.o.o Międzyrzecze Górne 379 43-392 K/Bielska-Bialej Polen Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.I. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Förch Slovensko s.r.o. Rosinská cesta 8 010 08 Žilina Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda Rua República da Bolivia No. 69, 1 esq 1500-544 Lisboa Portugal Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82 E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechenland Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl

Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114 Emergency telephone: +614 13 550 330 Email : sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW Russland E-Mail: skynord.office@gmail.com

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

Förch, s.r.o. Dopravní 1314/1 104 00 Praha 10 – Uhříněves Tschechien Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583 Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul Türkei Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr



Page 15 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland Tel. +353871271473

(GB)

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) Acute Toxicity Estimate ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BSEF The International Bromine Council bw body weight Chemical Abstracts Service CAS CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw drv weight for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances EN European Norms EPA United States Environmental Protection Agency (United States of America) $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. FU European Union EVAL Ethylene-vinyl alcohol copolymer Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Koc Adsorption coefficient of organic carbon in the soil octanol-water partition coefficient Kow IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code including, inclusive incl IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Log Kow, Log Pow Logarithm of octanol-water partition coefficient



(GB) Page 16 of 16 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 18.03.2022 / 0019 Replacing version dated / version: 01.11.2021 / 0018 Valid from: 18.03.2022 PDF print date: 18.03.2022 Gasket Remover R580 300 ml Art.: 6490 4600, Art.: 6494 4600 10 Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. no data available n.d.a. NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development org. organic OSHA Occupational Safety and Health Administration (USA) persistent, bioaccumulative and toxic PBT ΡE Polyethylene PNEC Predicted No Effect Concentration ppm parts per million Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Telephone Tel TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods VOC Volatile organic compounds very persistent and very bioaccumulative vPvB wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax:

+49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.