

Page 1 of 23
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.06.2022 / 0022
Replacing version dated / version: 01.11.2021 / 0021
Valid from: 01.06.2022
PDF print date: 04.06.2022
Plastic Adhesion Agent L246
400 ml Art.: 6220 2555, Art.: 6224 2555

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Plastic Adhesion Agent L246
400 ml Art.: 6220 2555, Art.: 6224 2555

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Adhesion promotor

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555



Danger

H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H315-Causes skin irritation. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / eye protection / face protection.

P314-Get medical advice / attention if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

Ethylbenzene

Xylene

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Dimethyl ether	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119472128-37-XXXX
Index	603-019-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-065-8
CAS	115-10-6
content %	50-<100
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

Xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	601-022-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	215-535-7
CAS	1330-20-7
content %	10-<30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

GB

Page 3 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Specific Concentration Limits and ATE	ATE (oral): >2000 mg/kg ATE (dermal): 1467 mg/kg ATE (as inhalation): 12,09 mg/l
--	--

n-butyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119485493-29-XXXX
Index	607-025-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	204-658-1
CAS	123-86-4
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336

Ethylbenzene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119489370-35-XXXX
Index	601-023-00-4
EINECS, ELINCS, NLP, REACH-IT List-No.	202-849-4
CAS	100-41-4
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (organs of hearing) Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Toluene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471310-51-XXXX
Index	601-021-00-3
EINECS, ELINCS, NLP, REACH-IT List-No.	203-625-9
CAS	108-88-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

Page 4 of 23
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.06.2022 / 0022
Replacing version dated / version: 01.11.2021 / 0021
Valid from: 01.06.2022
PDF print date: 04.06.2022
Plastic Adhesion Agent L246
400 ml Art.: 6220 2555, Art.: 6224 2555

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Product removes fat.

Repeated exposure may cause skin dryness or cracking.

Skin resorption

Vapours may cause drowsiness and dizziness.

Inhalation of fumes may have narcotic effect.

Effect on the central nervous system

Headaches

Dizziness

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO₂/dry extinguisher

Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 Prevent from entering drainage system.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
 Active substance:
 Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid inhalation of the vapours.
 Keep away from sources of ignition - Do not smoke.
 Do not use on hot surfaces.
 Take precautions against electrostatic charges.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Use working methods according to operating instructions.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Ensure sufficient ventilation.
 Solvent resistant floor
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Only store at temperatures from 5°C to 35°C.
 Protect from direct sunlight.
 Store in a dry place.
 Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Dimethyl ether		
WEL-TWA: 400 ppm (766 mg/m ³) (WEL), 1000 ppm (1920 mg/m ³) (EU)	WEL-STEL: 500 ppm (958 mg/m ³) (WEL)	---	
Monitoring procedures:	- Compur - KITA-123 S (549 129)		
BMGV: ---	Other information: ---		
Chemical Name	Xylene		
WEL-TWA: 220 mg/m ³ (50 ppm) (WEL), 50 ppm (221 mg/m ³) (EU)	WEL-STEL: 100 ppm (441 mg/m ³) (WEL), 100 ppm (442 mg/m ³) (EU)	---	
Monitoring procedures:	- Draeger - Xylene 10/a (67 33 161)		

GB

Page 6 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

- Compur - KITA-143 SA (550 325)
- Compur - KITA-143 SB (505 998)
- INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)
- NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003
- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
- OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999

BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV) Other information: Sk (WEL)

Chemical Name	n-butyl acetate
WEL-TWA: 150 ppm (724 mg/m3) (WEL), 50 ppm (241 mg/m3) (EU)	WEL-STEL: 200 ppm (966 mg/m3) (WEL), 150 ppm (723 mg/m3) (EU)
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-138 U (548 857) - Compur - KITA-139 SB(C) (549 731) - NIOSH 1450 (ESTERS 1) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007
BMGV: ---	Other information: ---

Chemical Name	Ethylbenzene
WEL-TWA: 441 mg/m3 (100 ppm) (WEL), 442 mg/m3 (100 ppm) (EU)	WEL-STEL: 552 mg/m3 (125 ppm) (WEL), 884 mg/m3 (200 ppm) (EU)
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Ethyl Benzene 30/a (67 28 381) - Compur - KITA-179 S (549 228) INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 3-1 (2004) - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003
BMGV: ---	Other information: Sk (WEL)

Chemical Name	Toluene
WEL-TWA: 191 mg/m3 (50 ppm) (WEL), 192 mg/m3 (50 ppm) (EU)	WEL-STEL: 384 mg/m3 (100 ppm) (WEL, EU)
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Toluene 100/a (81 01 731) - Draeger - Toluene 5/b (81 01 661) - Draeger - Toluene 50/a (81 01 701) - Compur - KITA-124 SA (550 226) - Compur - KITA-124 SB (551 398) - Compur - KITA-124 SH (509 834) DFG Meth. Nr. 1 (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 1) - 2014, 2002 INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 17-1 (2004) - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - NIOSH 4000 (TOLUENE (diffusive sampler)) - 1994 - OSHA 1021 (Instantaneous Whole Air Sampling) - 2017 - OSHA 111 (TOLUENE) - 1998
BMGV: ---	Other information: Sk (WEL, EU)

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	

	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m ³	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m ³	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m ³	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	

n-butyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,18	mg/l	
	Environment - marine		PNEC	0,018	mg/l	
	Environment - periodic release		PNEC	0,36	mg/l	
	Environment - sediment, freshwater		PNEC	0,981	mg/kg	
	Environment - sediment, marine		PNEC	0,0981	mg/kg	
	Environment - soil		PNEC	0,0903	mg/kg	
	Environment - sewage treatment plant		PNEC	35,6	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	3,4	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	300	mg/m ³	

Page 8 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Consumer	Human - inhalation	Long term, systemic effects	DNEL	35,7	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	300	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	35,7	mg/m ³	
Consumer	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	600	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	300	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	7	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	600	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	300	mg/m ³	

Ethylbenzene

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,1	mg/l	
	Environment - marine		PNEC	0,01	mg/l	
	Environment - sewage treatment plant		PNEC	9,6	mg/l	
	Environment - sediment, freshwater		PNEC	13,7	mg/kg	
	Environment - sediment, marine		PNEC	1,37	mg/kg	
	Environment - soil		PNEC	2,68	mg/kg	
	Environment - water	Long term	PNEC	0,1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,1	mg/l	
	Environment - oral (animal feed)		PNEC	20	mg/kg feed	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	15	mg/m ³	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	293	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	293	mg/m ³	

Toluene

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,68	mg/kg	
	Environment - sediment, freshwater		PNEC	16,39	mg/kg dw	
	Environment - soil		PNEC	2,89	mg/kg dw	
	Environment - sewage treatment plant		PNEC	13,61	mg/l	

9B

Page 9 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

	Environment - marine		PNEC	0,68	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,68	mg/l	
	Environment - sediment, marine		PNEC	16,39	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	56,5	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	226	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	226	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	56,5	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	226	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	8,13	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	384	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	192	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	192	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	384	mg/kg body weight/day	

9B WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU), (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Solvent resistant protective gloves (EN ISO 374).
 Recommended
 Protective nitrile gloves (EN ISO 374).

Page 10 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

>480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	According to specification
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	1,1 Vol-%
Upper explosion limit:	18,6 Vol-%
Flash point:	< 0 °C (Active substance)
Auto-ignition temperature:	235 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	3400 hPa (20°C)
Density and/or relative density:	0,75 g/cm ³ (20°C)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	There is no information available on this parameter.
Evaporation rate:	n.a.
Solvents content:	97,68

SECTION 10: Stability and reactivity

10.1 Reactivity

Page 11 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

See also Subsection 10.2 to 10.6.
 The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
 Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
 Possible build up of explosive/highly flammable vapour/air mixture.

10.4 Conditions to avoid

See also section 7.
 Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.
 Electrostatic charge

10.5 Incompatible materials

See also section 7.
 Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
 See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Plastic Adhesion Agent L246

400 ml Art.: 6220 2555, Art.: 6224 2555

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Dimethyl ether

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

GB

Page 12 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No
Symptoms:						unconsciousness, headaches, mucous membrane irritation, dizziness, nausea and vomiting., frostbite, gastrointestinal disturbances, respiratory distress, circulatory collapse

Xylene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat		Does not conform with EU classification.
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	27	mg/l/4h	Rat		Vapours, Does not conform with EU classification.
Skin corrosion/irritation:				Rabbit	(Draize-Test)	Irritant
Serious eye damage/irritation:				Rabbit		Irritant
Respiratory or skin sensitisation:					(Patch-Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes

96

Page 13 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Symptoms:						breathing difficulties, drying of the skin., drowsiness, unconsciousness , burning of the membranes of the nose and throat, vomiting, skin afflictions, heart/circulatory disorders, coughing, headaches, drowsiness, dizziness, nausea
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

n-butyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10760	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>14112	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	21,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEC	9640	mg/m3		OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Symptoms:						drowsiness, unconsciousness , headaches, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	500	ppm	Rat		

Ethylbenzene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

GB

Page 14 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Acute toxicity, by oral route:	LD50	3500	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	15354	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	17,2	mg/l/4h	Rat		Vapours
Respiratory or skin sensitisation:				Human being	(Patch-Test)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Symptoms:						ataxia, respiratory distress, abdominal pain, drowsiness, unconsciousness, heart/circulatory disorders, coughing, headaches, cramps, fatigue, intoxication, drowsiness, mucous membrane irritation, shock, dizziness, nausea and vomiting., Reddening, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:				Mouse	OECD 412 (Subacute Inhalation Toxicity - 28-Day Study)	

Toluene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5580	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	> 5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	25,7	mg/l/4h	Rat		Aerosol
Acute toxicity, by inhalation:	LC50	49	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Slightly irritant, Not relevant for classification.
Respiratory or skin sensitisation:				Rat	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Rat	in vivo	Negative, References
Reproductive toxicity:						Repr. 2
Aspiration hazard:						Yes

06

Page 15 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Symptoms:						respiratory distress, drowsiness, unconsciousness, headaches, cramps, circulatory collapse, intoxication, drowsiness, mucous membrane irritation, dizziness, sweating, nausea and vomiting.
-----------	--	--	--	--	--	---

11.2. Information on other hazards

Plastic Adhesion Agent L246 400 ml Art.: 6220 2555, Art.: 6224 2555						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

n-butyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Plastic Adhesion Agent L246 400 ml Art.: 6220 2555, Art.: 6224 2555							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Page 16 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.06.2022 / 0022

Replacing version dated / version: 01.11.2021 / 0021

Valid from: 01.06.2022

PDF print date: 04.06.2022

Plastic Adhesion Agent L246

400 ml Art.: 6220 2555, Art.: 6224 2555

Other information:	AOX						According to the recipe, contains no AOX.
Other information:	DOC						DOC-elimination degree (complexing organic substance) \geq 80%/28d: n.a.

Dimethyl ether							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	Poecilia reticulata		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	Chlorella vulgaris		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m ³ /mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	Pseudomonas putida		
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water. DIN EN 1485
Water solubility:			45,60	mg/l			25°C

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:			>60	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.3. Bioaccumulative potential:	BCF		25,9				
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	2,2	mg/l			
12.1. Toxicity to algae:	NOEC/NOEL		0,44	mg/l			

n-butyl acetate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

96

Page 17 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

12.7. Other adverse effects:							Product floats on the water surface.
12.1. Toxicity to fish:	LC50	96h	18	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	44	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	23	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	397	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	200	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		28d	98	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		1,78-2,3				Low
12.3. Bioaccumulative potential:	BCF		15,3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		959	mg/l	Pseudomonas putida		

Ethylbenzene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	0,96	mg/l	Ceriodaphnia spec.	U.S. EPA-600/4-91-003	
12.1. Toxicity to algae:	EC50	72h	3,6-4,6	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		6d	100	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.3. Bioaccumulative potential:	Log Kow		3,15-3,2				
12.3. Bioaccumulative potential:	BCF		15				fish
12.4. Mobility in soil:	Koc		518				Slightestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	ThOD		3,17	mg/l			
Other information:	BOD		1,78	g/g			

Toluene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	3,78	mg/l			Ceriodaphnia dubia
12.1. Toxicity to fish:	LC50	96h	5,5	mg/l			Oncorhynchus kisutch

95

Page 18 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

12.1. Toxicity to fish:	NOEC/NOEL		1,39	mg/l			Oncorhynchus kisutch
12.1. Toxicity to fish:	LC50	96h	13	mg/l	Pimephales promelas		
12.1. Toxicity to fish:	LC50	96h	24	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	11,5	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	0,74	mg/l	Ceriodaphnia spec.		
12.1. Toxicity to algae:	IC50	72h	12	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		20d	86	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,69-2,73				
12.3. Bioaccumulative potential:	BCF	3d	90				Leuciscus idus melanotus
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	COD		700	mg/g			
Other information:	BOD5		860	mg/g			
Toxicity to bacteria:	EC50	30min	20	mg/l	Photobacterium phosphoreum		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

Classification code: -

LQ: 5F

14.5. Environmental hazards: 1 L

Tunnel restriction code: Not applicable

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1



GB

Page 19 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

14.4. Packing group: -
 EmS: F-D, S-U
 Marine Pollutant: n.a
 14.5. Environmental hazards: Not applicable
Transport by air (IATA)
 14.2. UN proper shipping name: Aerosols, flammable
 14.3. Transport hazard class(es): 2.1
 14.4. Packing group: -
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Regulation (EC) No 1907/2006, Annex XVII
 Toluene
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 725 g/l
 Directive 2010/75/EU (VOC): 96,7 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT RE 2, H373	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

- H361d Suspected of damaging the unborn child.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H220 Extremely flammable gas.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- STOT RE — Specific target organ toxicity - repeated exposure
- Eye Irrit. — Eye irritation
- Skin Irrit. — Skin irritation
- Asp. Tox. — Aspiration hazard
- Aerosol — Aerosols
- Flam. Gas — Flammable gases - Flammable gas
- Flam. Liq. — Flammable liquid
- Acute Tox. — Acute toxicity - dermal
- Acute Tox. — Acute toxicity - inhalation
- STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
- Aquatic Chronic — Hazardous to the aquatic environment - chronic
- STOT SE — Specific target organ toxicity - single exposure - narcotic effects
- Repr. — Reproductive toxicity

Key literature references and sources for data:

- Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
- Guidelines for the preparation of safety data sheets as amended (ECHA).
- Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
- Safety data sheets for the constituent substances.
- ECHA Homepage - Information about chemicals.
- GESTIS Substance Database (Germany).
- German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
- EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
- National Lists of Occupational Exposure Limits for each country as amended.
- Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
 ZAE Le Marchais Renard
 CS 50125 Montereau-sur-le-Jard
 77019 Melun Cedex
 Frankreich
 Tel. +33 1 64 14 48 48
 Fax. +33 1 64 14 48 49
 E-Mail: info@forch.fr
 Internet: www.forch.fr

S.C. Foerch S.R.L.
 Str. Zizinului nr.110
 500407 Brasov
 Rumänien
 Tel. +40 368 408192
 Fax. +40 368 408193
 E-Mail: info@foerch.ro
 Internet: www.foerch.ro

Foerch AG
 Muttenerstrasse 143
 4133 Pratteln
 Schweiz
 Tel. +41 61 8262031
 Fax. +41 61 8262039
 E-Mail: info@foerch.ch
 Internet: www.foerch.ch

Page 21 of 23
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.06.2022 / 0022
Replacing version dated / version: 01.11.2021 / 0021
Valid from: 01.06.2022
PDF print date: 04.06.2022
Plastic Adhesion Agent L246
400 ml Art.: 6220 2555, Art.: 6224 2555

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.
Mikdzyrzecze Górne 379
43-392 K/Bielska-Białej
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 8
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetínives
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Page 22 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.06.2022 / 0022
 Replacing version dated / version: 01.11.2021 / 0021
 Valid from: 01.06.2022
 PDF print date: 04.06.2022
 Plastic Adhesion Agent L246
 400 ml Art.: 6220 2555, Art.: 6224 2555

Troscoe Ltd
 Unit 6, 13 Highbrook Drive
 East Tamaki 2013, New Zealand
 Tel: +64 21 081 30780 / +64 21 024 05583
 Email:sales@forchnz.co.nz
 Internet: www.forchnz.co.nz

Förch Portugal Lda
 Centro Empresarial Sintra-Estoril III
 Rua Pé de Mouro, Nº 33, Armazém J
 2710-335 Sintra
 Portugal
 Tel. +351 917314442
 E-Mail: info@forch.pt
 Internet: www.forch.pt

Trigers SIA
 Straupes iela 3
 1073 Riga
 Lettland
 Tel. +371 6 7 90 25 15
 Fax. +371 67 90 24 96
 E-Mail: trigers@trigers.lv
 Internet: www.trigers.lv

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti.
 Haramidere Mevkii Beysan Sanayi
 Sitesi Birlik Caddesi No:6/3
 34524 Beylikdüzü / Istanbul
 Türkei
 Tel. +90 (0)212 422 8744-45
 Fax. +90 (0)212 422 8788
 E-Mail: info@forch.com.tr
 Internet: www.forch.com.tr

Total Consumables Ltd
 Coolnafearagh
 Monasterevin
 Co. Kildare
 W34 TX29
 Irland
 Tel. +353871271473

Venus Arma d.o.o.
 Partner Theo Förch GmbH & Co. KG
 Batajnicki drum 18a
 11080 Zemun
 Republika Srbija
 Tel. +381 11 407-20-91
 Fax. +381 11 407-20-91
 E-Mail: office@foerch.rs
 Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.