

Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

# **Construction-Silicone Neutral Medium viscosity transparent** 310 ml Art.: 6810 2100, Art.: 6814 2100

## 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Silicone sealant

# Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 - 15 74196 Neuenstadt Tel.: 07139/95-0

Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

**SECTION 2: Hazards identification** 

# 1.4 Emergency telephone number

**Emergency information services / official advisory body:** 

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (TFC)

# 2.1 Classification of the substance or mixture

# Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH208-Contains 2-Octyl-2H-isothiazol-3-one. May produce an allergic reaction. EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).



Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

# n.a. **3.2 Mixtures**

· — ·······	
Hydrocarbons, C15-C19, n-alkanes, isoalkanes, <2% aromatics	
Registration number (REACH)	01-2120081657-46-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	940-730-5
CAS	(1437281-01-0)
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Asn Toy 1 H304

O,O',O"-(methylsilylidyne)trioxime-2-pentanone	
Registration number (REACH)	01-2120004323-76-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	484-460-1
CAS	
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Eye Irrit. 2, H319

2-Octyl-2H-isothiazol-3-one	
Registration number (REACH)	
Index	613-112-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	247-761-7
CAS	26530-20-1
content %	0,00015-<0,0015
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071
	Acute Tox. 2, H330
	Acute Tox. 3, H301
	Acute Tox. 3, H311
	Skin Corr. 1, H314
	Eye Dam. 1, H318
	Skin Sens. 1A, H317
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 1, H410 (M=100)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,0015 %
	ATE (oral): 125 mg/kg
	ATE (dermal): 311 mg/kg
	ATE (as inhalation, Mist): 0,27 mg/l/4h

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

# Skin contact



Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Wipe off residual product carefully with a soft, dry cloth.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a

doctor

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

# 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Formaldehyde

Toxic gases

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Or

Allow product to harden.



Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Pick up mechanically and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store at room temperature.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Chemical Name	Silica, amorphous	3				Content %:
WEL-TWA: 6 mg/m3 (total inh. dus		WEL-STEL:				
(resp. dust)						
Monitoring procedures:						
BMGV:			(	Other information:	-	
Chemical Name	Methanol					Content %:
WEL-TWA: 200 ppm (266 mg/m3)	(WEL), 200 ppm	WEL-STEL:	250 ppm (333 mg/m	3 (WEL)		
(260 mg/m3) (EU)	. ,			, ,		
Monitoring procedures:	-	Draeger - Alcoho	ol 25/a Methanol (81 (	01 631)		
	-	Compur - KITA-1	119 SA (549 640)			
	-	Compur - KITA-1	119 U (549 657)			
		DFG Meth. Nr. 6	(D) (Loesungsmittelg	gemische 6), DFG (E)	(Solvent	mixtures 6) - 2013,
	-	2002 - EU projec	ct BC/CEN/ENTR/000	1/2002-16 card 65-1 (	2004)	
	-	NIOSH 2000 (MI	ETHANOL) - 1998			
			OLATILE ORGANIC (			
		NIOSH 3800 (OF	RGANIC AND INORG	SANIC GASES BY EX	TRACTIV	E FTIR
	_	<b>SPECTROMET</b>	RY) - 2016			
		Draeger - Alcoho	ol 100/a (CH 29 701)			
BMGV:			(	Other information: S	k (WEL, E	EU)

O,O',O"-(methylsilylidyne)trioxime-2-pentanone								
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note		
	Environmental		-					
	compartment							
	Environment - freshwater		PNEC	0,1	mg/l			
	Environment - marine		PNEC	0,01	mg/l			
	Environment - sediment,		PNEC	0,269	mg/kg			
	freshwater							



Page 5 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

	Environment - sediment, marine		PNEC	0,057	mg/kg	
	Environment - sewage treatment plant		PNEC	2,15	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,057	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,033	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,2292	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,065	mg/kg bw/d	

Silica, amorphous									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Environment - oral (animal		PNEC	60000	mg/kg feed				
	feed)								
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3				

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment,		PNEC	570,4	mg/kg	
	freshwater		TIVEO	070,4	mg/kg	
	Environment - sediment,		PNEC	57,04	mg/kg	
	marine		11120	07,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water,		PNEC	1540	mg/l	
	sporadic (intermittent)		TIVEO	1540	1119/1	
	release					
	Environment - sewage		PNEC	100	mg/l	
	treatment plant			'00	111971	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m3	
Consumer	Human - inhalation	Short term, local	DNEL	50	mg/m3	
Concurren	Traman imalation	effects	DIVLL		mg/mo	
Consumer	Human - dermal	Short term, systemic	DNEL	8	mg/kg	
		effects			body	
		0.10010			weight/day	
Consumer	Human - inhalation	Short term, systemic	DNEL	50	mg/m3	
		effects				
Consumer	Human - oral	Short term, systemic	DNEL	8	mg/kg	
		effects			body	
					weight/day	
Consumer	Human - dermal	Long term, systemic	DNEL	8	mg/kg	
		effects			body	
					weight/day	
Consumer	Human - inhalation	Long term, systemic	DNEL	50	mg/m3	
		effects				
Consumer	Human - oral	Long term, systemic	DNEL	8	mg/kg	
		effects			body	
					weight/day	
Workers / employees	Human - dermal	Short term, systemic	DNEL	40	mg/kg	
• •		effects			body	
					weight/day	
Workers / employees	Human - inhalation	Short term, systemic	DNEL	260	mg/m3	
		effects			_	1



Œ

Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective gloves made of butyl (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

240

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.



Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Paste, solid.

Colour: According to specification

Odour: Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

Flammability: Not combustible.

Lower explosion limit:

Does not apply to solids.

Upper explosion limit:

Does not apply to solids.

Flash point:

Does not apply to solids.

Auto-ignition temperature:

Does not apply to solids.

There is no information available on this parameter.

pH: Mixture is non-soluble (in water).

Kinematic viscosity: Does not apply to solids.

Solubility: Insoluble

Partition coefficient n-octanol/water (log value): Does not apply to mixtures.

Vapour pressure: There is no information available on this parameter.

Density and/or relative density: 0,99 g/cm3

Relative vapour density: Does not apply to solids.

9.2 Other information

Explosives: Product is not explosive.

Oxidizing solids: No

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

# 10.4 Conditions to avoid

See also section 7.

Strong heat

Moisture

#### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

### **SECTION 11: Toxicological information**



Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Construction-Silicone Neutral I	Medium visco	sity transpare	ent			
310 ml Art.: 6810 2100, Art.: 681	14 2100					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C15-C19, n-alka	nes, isoalkan	es, <2% arom	atics			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	5213	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	53	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Symptoms:						fever, coughing, chest pain (thorax pain), breathing difficulties, respiratory distress, increased blood pressure

2-Octyl-2H-isothiazol-3-one						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	125	mg/kg			
Acute toxicity, by dermal route:	ATE	311	mg/kg			
Acute toxicity, by inhalation:	ATE	0,27	mg/l/4h			Dust, Mist
Symptoms:						ataxia, diarrhoea

Silica, amorphous	Fuelmaint	Value	I I m i 4	Oueraniam	To at weath and	Mataa
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References,
						Maximum
						achievable
						concentration.
Skin corrosion/irritation:				Rabbit		Not irritant,
						References
Serious eye damage/irritation:				Rabbit		Not irritant,
-						Mechanical
						irritation
						possible.,
						References



Page 9 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Respiratory or skin	Guinea pig	Not sensitizising
sensitisation:		
Germ cell mutagenicity:		Negative
Carcinogenicity:		No indications of
		such an effect.
Reproductive toxicity		No indications of
(Developmental toxicity):		such an effect.
Symptoms:		eyes, reddened

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on
A suite terrisity, but democal moutes	LDEO	17100		Rabbit		persons.  Does not
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		conform with El
A	1.050	0.5		D-4		classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for
						classification.,
0					0505 405 44 4 5	Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
				<u> </u>	Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Carcinogenicity:				Mouse	OECD 453 (Combined	Negative
					Chronic	
					Toxicity/Carcinogenicity	
					Studies)	
Reproductive toxicity:	NOAEL	1,3	mg/l	Mouse	OECD 416 (Two-	
,					generation `	
					Reproduction Toxicity	
					Study)	
Specific target organ toxicity -	NOAEL	0.13	mg/l	Rat	OECD 453 (Combined	
repeated exposure (STOT-RE):		', '			Chronic	
(					Toxicity/Carcinogenicity	
					Studies)	
Symptoms:					0.00.00)	abdominal pain
Symptome.						vomiting,
						headaches.
						gastrointestinal
						disturbances,
						drowsiness,
						visual
						disturbances,
						watering eyes,
						nausea, mental
						confusion,
						intoxication,
				<u> </u>		dizziness

# 11.2. Information on other hazards

Construction-Silicone Neutral Medium viscosity transparent 310 ml Art.: 6810 2100, Art.: 6814 2100									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Endocrine disrupting properties:						Does not apply			
						to mixtures.			
Other information:						No other			
						relevant			
						information			
						available on			
						adverse effects			
						on health.			



Page 10 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

**Construction-Silicone Neutral Medium viscosity transparent** 310 ml Art.: 6810 2100, Art.: 6814 2100 Toxicity / effect Endpoint Time Value Unit Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: n.d.a. 12.1. Toxicity to algae: n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment 12.6. Endocrine Does not apply disrupting properties: to mixtures. No information 12.7. Other adverse effects: available on other adverse effects on the environment. Other information: DOC-elimination degree(complexi ng organic substance)>= 80%/28d: n.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and		28d	73	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
12.3. Bioaccumulative						Respirometry Test)	To be expected
potential:							To be expected
12.1. Toxicity to daphnia:	EL50	48h	> 100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
10.1 T : ''	E1 50	701	. 100		B 11:1 : 1	Test)	
12.1. Toxicity to algae:	EL50	72h	> 100	mg/l	Pseudokirchneriell	OECD 201 (Alga, Growth Inhibition	
					a subcapitata	Test)	
Toxicity to bacteria:	EC50	3h	> 100	mg/l	activated sludge	OECD 209	Analogous
Toxiony to bacteria.	2000	011	100	ling/i	dolivated sladge	(Activated Sludge,	conclusion
						Respiration	CONGIGORON
						Inhibition Test	
						(Carbon and	
						Àmmonium	
						Oxidation))	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
40.4. Malailiteein aaile							vPvB substance
12.4. Mobility in soil:							Product floats o
							the water surface.,
							Adsorption in
							ground.
Ozone depletion							No
potential (ODP):							



Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,047	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOEC/NOEL	35d	0,0085	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,003	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,32	mg/l	Daphnia magna	,	
12.1. Toxicity to algae:	ErC10	48h	0,00022 4	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	0,00129	mg/l	Navicula pelliculosa	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			25	%		,	Not readily biodegradable
Toxicity to bacteria:	EC50		30,2	mg/l	activated sludge		
Toxicity to bacteria:	EC20	3h	7,3	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Silica, amorphous Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						,	Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT	-						No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis		EPA-660/3-75-
•					macrochirus		009
12.1. Toxicity to daphnia:	EC50	96h	18260	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	



Page 12 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

12.1. Toxicity to algae:	EC50	96h	22000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		28400		Chlorella vulgaris	·	Not to be expected
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		-0,77			,,	
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

# For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 02 17 waste containing silicones other than those mentioned in 07 02 16

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

Hardened product:

Can be disposed of with household rubbish.

# For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 02 plastic packaging

### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number or ID number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

# Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a

14.5. Environmental hazards: Not applicable

**Transport by air (IATA)** 



Page 13 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

14.4. Packing group:

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.5. Environmental hazards:

n a Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

# **SECTION 15: Regulatory information**

n.a.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

3,22 %

Treated goods as per Regulation (EU) No. 528/2012 must display specific information on the label.

Please note Article 58 paragraph (3) subparagraph 2 of Regulation (EU) No. 528/2012.

Approval of the biocidal active substance may mean that special conditions are required for marketing the treated goods.

These are indicated in the approval of the active substance.

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

# **SECTION 16: Other information**

1-16

Revised sections:

# Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.

H317 May cause an allergic skin reaction.

H314 Causes severe skin burns and eye damage.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH071 Corrosive to the respiratory tract.

Asp. Tox. — Aspiration hazard Acute Tox. — Acute toxicity - oral

Eye Irrit. — Eye irritation

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - dermal Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

Skin Sens — Skin sensitization

Aguatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic



Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS ZAE Le Marchais Renard

CS 50125 Montereau-sur-le-Jard 77019 Melun Cedex

Frankreich Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49

E-Mail: info@forch.fr Internet: www.forch.fr Förch SAS

17 rue de Marbourg 9764 MARNACH Luxemburg

Tel. +352 269 03267 Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien

Tel. +40 368 408192 Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz

Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg

Buzinska cesta 58 10010 Zagreb Kroatien Tel. +385 1 2912900

Förch d.o.o.

Fax. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0

Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30

E-Mail: info@foerch.at Internet: www.foerch.at

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada)

Spanien

Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark

Tel. +45 86 823711 Fax. +45 86 800617 E-Mail: info@foerch.dk Internet: www.foerch.dk

Lhomme Tools & Fasteners BV

Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien

Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82

E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW

Russland

E-Mail: skynord.office@gmail.com

Förch Polska Sp. z.o.o Międzyrzecze Górne 379 43-392 K/Bielska-Bialej

Polen

Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechenland

Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu



Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Förch S.r.l. Via Antonio Stradivari 4 39100 Bolzano (BZ)

Italien

Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420

E-Mail: info@foerch.nl Internet: www.foerch.nl

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei

Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A

1236 Trzin Slowenien Tel. +386 1 2442490

Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda

Rua República da Bolivia No. 69, 1 esq

1500-544 Lisboa Portugal

Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden

Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114

Emergency telephone: +614 13 550 330

Email: sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland

Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv

Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

AB varahlutir ehf

Förch, s.r.o. Dopravní 1314/1

104 00 Praha 10 - Uhříněves

**Tschechien** 

Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd

Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583

Email:sales@forchnz.co.nz

Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul

Türkei

Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland

Tel. +353871271473

# Any abbreviations and acronyms used in this document:

according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATF Acute Toxicity Estimate

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)



-(GB)

Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80,

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil cotanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern



Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0002

Replacing version dated / version: 07.04.2021 / 0001

Valid from: 01.11.2021 PDF print date: 01.11.2021

Construction-Silicone Neutral Medium viscosity transparent

310 ml Art.: 6810 2100, Art.: 6814 2100

Telephone Tel.

TOC Total organic carbon

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

# These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.