

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

#### Uses advised against:

No information available at present.

# 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199

Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

# 1.4 Emergency telephone number

**Emergency information services / official advisory body:** 

---

# Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

#### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Aerosol 3 H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



®

Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

# Warning

H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251-Do not pierce or burn, even after use

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH208-Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

# n.a. 3.2 Mixtures

OIZ IIIIXUU OO	
Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 μm)	
Registration number (REACH)	
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP). M-factors	Carc. 2. H351 (as inhalation)

N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide)	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	204-613-6
CAS	123-26-2
content %	0,1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Sens. 1B, H317
	Aquatic Chronic 3, H412

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**



Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder Alcohol resistant foam

Water jet spray

### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

# 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# **SECTION 7: Handling and storage**



Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

In addition to information given in this section, relevant information can also be found in section 8 and 6.1. **7.1 Precautions for safe handling** 

# 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep protected from direct sunlight and temperatures over 50°C.

# 7.3 Specific end use(s)

No information available at present.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

, , , , , , , , , , , , , , , , , , ,				
© Chemical Name	aerodynamic dian	in powder form containing 1 % or more of par neter <= 10 μm)	ticles with	Content %:10- <20
WEL-TWA: 10 mg/m3 (total inhala (respirable dust)	ble dust), 4 mg/m3	WEL-STEL:		
Monitoring procedures:				
BMGV:		Other in	formation:	
Chemical Name	China stone			Content %:
WEL-TWA: 2 mg/m3 (res. dust)		WEL-STEL:		
Monitoring procedures:			•	
BMGV:		Other in	formation:	
	Quartz			Content %:
WEL-TWA: 0,1 mg/m3 (silica, resp	irable, crystalline)	WEL-STEL:		
Monitoring procedures:		INSHT MTA/MA-036/A00 (Determination of C	Quartz in Air – Membraı	ne Filter Method/
		Xray Diffraction) - 2000, 2004		
		MDHS 101/2 (Crystalline silica in respirable a		n-filter analysis by
		infrared spectroscopy and X-ray diffraction) -		
		BC/CEN/ENTR/000/2002-16 card 52-1 (2004		Ell andicat
		NIOSH 7500 (Crystalline Silica, by XRD (filte BC/CEN/ENTR/000/2002-16 card 52-6 (2004)		- EU project
		NIOSH 7601 (SILICA, CRYSTALLINE, by VI		
		NIOSH 7601 (SILICA, CRYSTALLINE, by VI NIOSH 7602 (Crystalline Silica, by IR (KBr pe		
		NIOSH 7603 (QUARTZ in coal mine dust, by		17
		OSHA ID-142 (Quartz and Cristobalite in Wo		
BMGV:			formation:	2010
Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e		WEL-STEL:		Content %.
working fluids, ACGIH)	saddully metal	WLL-51LL		
Monitoring procedures:	-	Draeger - Oil Mist 1/a (67 33 031)	•	
BMGV:		Other in	formation:	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)									
Area of application	Exposure route / Effect on health Descriptor Value Unit Note								
	Environmental								
	compartment								
	Environment - freshwater		PNEC	0,184	mg/l				
	Environment - marine		PNEC	0,0184	mg/l				



Œ

Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Distillates (petroleum), hydrotreated heavy paraffinic									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Environment - oral (animal		PNEC	9,33	mg/kg feed				
	feed)								

trans-1,3,3,3-tetrafluoroprop-1-ene									
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note			
	Environmental								
	compartment								
	Environment - freshwater		PNEC	0,1	mg/l				
Consumer	Human - inhalation	Long term, systemic	DNEL	830	mg/m3				
		effects							
Workers / employees	Human - inhalation	Long term, systemic	DNEL	3902	mg/m3				
		effects							

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

# 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

# 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.



Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

If applicable

Protective gloves made of butyl (EN ISO 374).

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective PVC gloves (EN ISO 374). Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0.4

Permeation time (penetration time) in minutes:

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives:

Paste, liquid. The propellant is not released when used in accordance

with the regulations.

White

There is no information available on this parameter. There is no information available on this parameter.

Does not apply to aerosols.

There is no information available on this parameter. There is no information available on this parameter.

>60 °C

Does not apply to aerosols.

There is no information available on this parameter.

Mixture is non-soluble (in water). Does not apply to aerosols.

Insoluble

Does not apply to mixtures.

There is no information available on this parameter.

1,25 g/cm3

Does not apply to aerosols. Does not apply to aerosols.

There is no information available on this parameter.



Œ

Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Oxidising liquids:

There is no information available on this parameter.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

# 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

# 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

# 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Titanium diavida (in nowder form containing 1.9/ or more of partialog with paradynamic diameter -- 10 um)

Possibly more information on health effects, see Section 2.1 (classification).

Professional Ceramic Paste HT	- Anti Seize					
200 ml Art.: 6510 5115, Art.: 651	14 5115					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral	
					Toxicity - Up-and-Down	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
-					Irritation/Corrosion)	Mechanical
					,	irritation possible.
Respiratory or skin				Mouse	OECD 429 (Skin	Not sensitizising
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	,



Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
com con matagornoity.				Modeo	Erythrocyte	rioganio
					Micronucleus Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
ů ,					Mammalian `	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
				typhimurium		
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	No indications of
(Developmental toxicity):					Developmental Toxicity	such an effect.
0 15 1 1 1 1 1					Study)	N
Specific target organ toxicity -						Not irritant
single exposure (STOT-SE):						(respiratory tract).
Symptoms:						mucous membrane
						irritation.
						coughing,
						respiratory
						distress, drying
						of the skin.
Specific target organ toxicity -	NOAEL	3500	mg/kg/d	Rat		90d
repeated exposure (STOT-RE),			gg. «			""
oral:						
Specific target organ toxicity -	NOAEC	10	mg/m3	Rat		90d
repeated exposure (STOT-RE),						
inhalat.:						

China stone									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral				
					Toxicity)				
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat					
Skin corrosion/irritation:						Not irritant			
Serious eye damage/irritation:						Not irritant,			
						Mechanical			
						irritation possible.			
Aspiration hazard:						No			

Quartz						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						respiratory
						distress,
						coughing,
						mucous
						membrane
						irritation

# 11.2. Information on other hazards

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Endocrine disrupting properties:						Does not apply	
, 5, .						to mixtures.	
Other information:						No other	
						relevant	
						information	
						available on	
						adverse effects	
						on health.	



(B)

Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

# **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Professional Ceramic Pa 200 ml Art.: 6510 5115, A							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-elimination
							degree(complexi
							ng organic
							substance)>=
							80%/28d: n.a.
Other information:	AOX			%			Does not contain
							any organically
							bound halogens
							which can
							contribute to the
							AOX value in
							waste water.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell	U.S. EPA-600/9-	
					a subcapitata	78-018	
12.2. Persistence and							Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative	BCF	42d	9,6				Not to be
potential:							expected
12.3. Bioaccumulative	BCF	14d	19-352				Oncorhynchus
potential:							mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas		
					fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C



Œ

Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT	•						No PBT
and vPvB assessment							substance, No
							vPvB substance
12.2. Persistence and							Inorganic
degradability:							products canno
							be eliminated
							from water
							through
							biological
							purification
							methods.,
							Mechanical
							precipitation
							possible.
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l			
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	Analogous
					mykiss	Acute Toxicity	conclusion
						Test)	
12.1. Toxicity to daphnia:		48h	>1100	mg/l	Daphnia magna		References
12.1. Toxicity to algae:	IC50		>1000	mg/l			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus	OECD 201 (Alga,	Analogous
					subspicatus	Growth Inhibition	conclusion
						Test)	
12.2. Persistence and							Not
degradability:							biodegradable
12.3. Bioaccumulative							Not to be
potential:							expected,
							Analogous
							conclusion
Water solubility:							Insoluble

Quartz							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and							Not relevant for
degradability:							inorganic
							substances.
12.3. Bioaccumulative							Not to be
potential:							expected
12.4. Mobility in soil:							Low
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

# For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.



Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

15 01 04 metallic packaging

# **SECTION 14: Transport information**

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS 14.3. Transport hazard class(es):

14.3. Transport hazard class(es):2.214.4. Packing group:-Classification code:5ALQ:1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.2

14.4. Packing group:

EmS: F-D, S-U Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, non-flammable

14.3. Transport hazard class(es): 2.2

14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

# 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): < 3 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):









Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 3, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H351 Suspected of causing cancer by inhalation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Aerosol - Aerosols Carc. — Carcinogenicity Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

### **Key literature references and sources for data:**

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHÁ Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard 77019 Melun Cedex Frankreich

Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr

Internet: www.forch.fr

Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg

Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr

Str. Zizinului nr.110 500407 Brasov Rumänien Tel. +352 269 03267 Tel. +40 368 408192

Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Foerch AG Muttenzerstrasse 143 4133 Pratteln Schweiz

Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86

10010 Zagreb Kroatien Tel. +385 1 2912900 E-Mail: info@foerch.bg Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0

Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900

Verkauf Fax +43 662 875574-30 E-Mail: info@foerch.at Internet: www.foerch.at

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76

Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es

Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711 Fax. +45 86 800617 E-Mail: info@foerch.dk

Internet: www.foerch.dk

S.C. Foerch S.R.L.

Förch d.o.o.

Buzinska cesta 58



Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien

Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be

Förch Polska Sp. z.o.o Międzyrzecze Górne 379 43-392 K/Bielska-Bialej

Polen

Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.I. Via Antonio Stradivari 4 39100 Bolzano (BZ)

Italien

Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina

Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien

Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda Rua República da Bolivia No. 69, 1 esq 1500-544 Lisboa

Portugal

Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt Ziebe Limited

7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK)

Grossbritannien Tel +44 12 96 65 52 82 E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki

Griechenland

Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr

Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420

E-Mail: info@foerch.nl

Internet: www.foerch.nl

Förch Sverige AB Brännarevägen 1 151 55 Södertälje

Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114 Emergency telephone: +614 13 550 330

Email: sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland

Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW

Russland

E-Mail: skynord.office@gmail.com

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355

E-Mail: info@foerch.hu Internet: www.foerch.hu AB varahlutir ehf

Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

Förch, s.r.o. Dopravní 1314/1 104 00 Praha 10 – Uhříněves Tschechien

Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583

Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul Türkei

Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr



Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland

Tel. +353871271473

# Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number

Fax. Fax numbe gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

ncl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient



Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0009

Replacing version dated / version: 31.08.2021 / 0008

Valid from: 01.11.2021 PDF print date: 01.11.2021

Professional Ceramic Paste HT - Anti Seize 200 ml Art.: 6510 5115, Art.: 6514 5115

**Limited Quantities** 10

**MARPOL** International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. n.av. not available not checked n.c. no data available n.d.a.

NIOSH National Institute for Occupational Safety and Health (USA)

NI P No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

persistent, bioaccumulative and toxic PBT

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million Polyvinylchloride **PVC** 

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wet weight wwt

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

# These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.