

Page 1 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0014
Replacing version dated / version: 01.11.2021 / 0013
Valid from: 21.09.2022
PDF print date: 23.09.2022
Cavity Wax Transparent Plus L264
1 | Art.: 6620 6095, Art.: 6624 6095

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Cavity Wax Transparent Plus L264
1 | Art.: 6620 6095, Art.: 6624 6095

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Cavity protection

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095



Warning

H226-Flammable liquid and vapour. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray.
 P312-Call a POISON CENTRE / doctor if you feel unwell.
 P403+P233-Store in a well-ventilated place. Keep container tightly closed.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119471843-32-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	927-241-2
CAS	---
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0014
Replacing version dated / version: 01.11.2021 / 0013
Valid from: 21.09.2022
PDF print date: 23.09.2022
Cavity Wax Transparent Plus L264
1 | Art.: 6620 6095, Art.: 6624 6095

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.
Danger of aspiration.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
The following may occur:

Drying of the skin.
Dermatitis (skin inflammation)
On vapour formation:
Irritation of the respiratory tract
Ingestion:
Gastrointestinal disturbances
Nausea
Vomiting
Danger of aspiration.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

None known

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Dry extinguisher
Sand
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Oxides of nitrogen
Oxides of sulphur
Toxic gases
Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0014
Replacing version dated / version: 01.11.2021 / 0013
Valid from: 21.09.2022
PDF print date: 23.09.2022
Cavity Wax Transparent Plus L264
1 | Art.: 6620 6095, Art.: 6624 6095

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Ensure sufficient supply of air.
Avoid formation of oil mist.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.
Oil binder
Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid inhalation of the vapours.
Avoid formation of oil mist.
Keep away from sources of ignition - Do not smoke.
Avoid contact with eyes.
Avoid long lasting or intensive contact with skin.
Do not carry cleaning cloths soaked in product in trouser pockets.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Protect against moisture and store closed.
Observe special storage conditions.
Observe special storage conditions.
Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Chemical Name		Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	
WEL-TWA: 800 mg/m3		WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) 		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name		Paraffin wax and hydrocarbon wax	
WEL-TWA: 2 mg/m3 (paraffin wax, fume)		WEL-STEL: 6 mg/m3 (paraffin wax, fume)	---
Monitoring procedures:	---		
BMGV: ---	Other information: ---		

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Page 6 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Skin protection - Hand protection:
 Protective gloves, oil resistant (EN ISO 374).
 If applicable
 Protective gloves made of fluorocarbon rubber (EN ISO 374).
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 >= 0,4
 Permeation time (penetration time) in minutes:
 >= 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective PVC gloves (EN ISO 374).
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If OES or MEL is exceeded.
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Transparent
Odour:	Mineral oil
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	30 °C (ISO 2719 (Pensky-Martens, closed cup))
Auto-ignition temperature:	~240 °C (DIN 51794)
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	>20,5 mm ² /s (40°C)
Kinematic viscosity:	~20 s (25°C, ISO 2431 (4 mm))
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,82 g/cm ³ (15°C, DIN 51757)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No
Bulk density:	n.a.

Page 7 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Cavity Wax Transparent Plus L264

1 | Art.: 6620 6095, Art.: 6624 6095

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4951	mg/m ³ /4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)

Page 8 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 478 (Genetic Toxicology - Rodent dominant Lethal Test)	Negative, Analogous conclusion
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion Chinese hamster
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:				Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:				Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours, No indications of such an effect., Analogous conclusion

Paraffin wax and hydrocarbon wax

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

9B

Page 9 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	NOAEL	1,5	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3600	mg/kg	Rabbit	IUCLID Chem. Data Sheet (ESIS)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Human being		Dust
Skin corrosion/irritation:					(Patch-Test)	Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Reproductive toxicity (Developmental toxicity):	NOAEL	>1000	mg/kg	Rat		
Symptoms:						diarrhoea

11.2. Information on other hazards

Cavity Wax Transparent Plus L264 1 Art.: 6620 6095, Art.: 6624 6095						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Cavity Wax Transparent Plus L264 1 Art.: 6620 6095, Art.: 6624 6095							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>10-<30	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,182	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,317	mg/l	Daphnia magna		

12.1. Toxicity to daphnia:	EL50	48h	>22-<46	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOELR	72h	<1	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50		>1000	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	89	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.2. Persistence and degradability:	ThOD	28d	53-55	%			Biodegradable
12.3. Bioaccumulative potential:	Log Pow		4-5,7				
12.4. Mobility in soil:							Product floats on the water surface.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l			
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.
Water solubility:			~ 0,04	g/l			Insoluble 20°C

Paraffin wax and hydrocarbon wax

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL		10	mg/l			
12.2. Persistence and degradability:		28d	>50	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LL50		>100	mg/l			
12.1. Toxicity to daphnia:	EL50		>10000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	NOEC/NOEL		>100	mg/l			
Water solubility:							Insoluble

SECTION 13: Disposal considerations
13.1 Waste treatment methods
For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

13 02 08 other engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

GB

Page 11 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Pay attention to local and national official regulations.
 E.g. dispose at suitable refuse site.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 15 01 01 paper and cardboard packaging
 15 01 02 plastic packaging
 15 01 04 metallic packaging
 Empty container completely.
 Untampered packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1268

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 1268 PETROLEUM PRODUCTS, N.O.S.

14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 Classification code: F1
 LQ: 5 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 PETROLEUM PRODUCTS, N.O.S.

14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 EmS: F-E, S-E
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Petroleum products, n.o.s.

14.3. Transport hazard class(es): 3
 14.4. Packing group: III
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Page 12 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Directive 2010/75/EU (VOC): 65 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Asp. Tox. — Aspiration hazard

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
 ZAE Le Marchais Renard
 CS 50125 Montereau-sur-le-Jard
 77019 Melun Cedex
 Frankreich
 Tel. +33 1 64 14 48 48
 Fax. +33 1 64 14 48 49
 E-Mail: info@forch.fr
 Internet: www.forch.fr

S.C. Foerch S.R.L.
 Str. Zizinului nr.110
 500407 Brasov
 Rumänien
 Tel. +40 368 408192
 Fax. +40 368 408193
 E-Mail: info@foerch.ro
 Internet: www.foerch.ro

Foerch AG
 Muttenerstrasse 143
 4133 Pratteln
 Schweiz
 Tel. +41 61 8262031
 Fax. +41 61 8262039
 E-Mail: info@foerch.ch
 Internet: www.foerch.ch

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o
Mikdyrzecze Górne 379
43-392 K/Bielska-Bialej
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 8
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetínives
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Page 14 of 15
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0014
 Replacing version dated / version: 01.11.2021 / 0013
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 Cavity Wax Transparent Plus L264
 1 | Art.: 6620 6095, Art.: 6624 6095

Troscoe Ltd
 Unit 6, 13 Highbrook Drive
 East Tamaki 2013, New Zealand
 Tel: +64 21 081 30780 / +64 21 024 05583
 Email: sales@forchnz.co.nz
 Internet: www.forchnz.co.nz

Förch Portugal Lda
 Centro Empresarial Sintra-Estoril III
 Rua Pé de Mouro, Nº 33, Armazém J
 2710-335 Sintra
 Portugal
 Tel. +351 917314442
 E-Mail: info@forch.pt
 Internet: www.forch.pt

Trigers SIA
 Straupes iela 3
 1073 Riga
 Lettland
 Tel. +371 6 7 90 25 15
 Fax. +371 67 90 24 96
 E-Mail: trigers@trigers.lv
 Internet: www.trigers.lv

Förch Otom. Ins. ve San. Ürün. Paz. Ltd. Sti.
 Haramidere Mevkii Beysan Sanayi
 Sitesi Birlik Caddesi No:6/3
 34524 Beylikdüzü / Istanbul
 Türkei
 Tel. +90 (0)212 422 8744-45
 Fax. +90 (0)212 422 8788
 E-Mail: info@forch.com.tr
 Internet: www.forch.com.tr

Total Consumables Ltd
 Coolnafearagh
 Monasterevin
 Co. Kildare
 W34 TX29
 Irland
 Tel. +353871271473

Venus Arma d.o.o.
 Partner Theo Förch GmbH & Co. KG
 Batajnicksi drum 18a
 11080 Zemun
 Republika Srbija
 Tel. +381 11 407-20-91
 Fax. +381 11 407-20-91
 E-Mail: office@foerch.rs
 Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.09.2022 / 0014

Replacing version dated / version: 01.11.2021 / 0013

Valid from: 21.09.2022

PDF print date: 23.09.2022

Cavity Wax Transparent Plus L264

1 | Art.: 6620 6095, Art.: 6624 6095

Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.