

Page 1 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 21.09.2022 / 0014  
Replacing version dated / version: 01.11.2021 / 0013  
Valid from: 21.09.2022  
PDF print date: 24.09.2022  
Diesel Conditioning and Anti - Gel  
300 ml Art.: 6750 7023, Art.: 6754 7023

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Diesel Conditioning and Anti - Gel**  
**300 ml Art.: 6750 7023, Art.: 6754 7023**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Additive

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG  
Theo-Förch-Str. 11 – 15  
74196 Neuenstadt  
Tel.: 07139/95-0  
Fax: 07139/95-199  
Email: [info@foerch.de](mailto:info@foerch.de)  
Homepage: [www.foerch.com](http://www.foerch.com)

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (TFC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Carc.	2	H351-Suspected of causing cancer.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023



**Danger**

H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H351-Suspected of causing cancer. H412-Harmful to aquatic life with long lasting effects.

P201-Obtain special instructions before use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.  
 P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P308+P313-IF exposed or concerned: Get medical advice / attention. P331-Do NOT induce vomiting.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, >1% naphthalene  
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

**2.3 Other hazards**

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Hazardous to drinking water, on escape of even small quantities.

Product can compose a film on the water surface, which can prevent oxygen exchange.

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

n.a.

**3.2 Mixtures**

<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b>	
<b>Registration number (REACH)</b>	01-2119457273-39-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	918-481-9
<b>CAS</b>	(64742-48-9)
<b>content %</b>	50-<70
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Asp. Tox. 1, H304
<b>Hydrocarbons, C10, aromatics, &gt;1% naphthalene</b>	
<b>Registration number (REACH)</b>	01-2119463588-24-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	919-284-0
<b>CAS</b>	(64742-94-5)
<b>content %</b>	20-<25
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

**1,2,4-trimethylbenzene**

**Substance for which an EU exposure limit value applies.**

Page 3 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

<b>Registration number (REACH)</b>	---
<b>Index</b>	601-043-00-3
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	202-436-9
<b>CAS</b>	95-63-6
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.  
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
 Danger of aspiration.  
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Drying of the skin.  
 Dermatitis (skin inflammation)  
 Oil acne  
 On vapour formation:  
 Irritation of the respiratory tract  
 Ingestion:  
 Nausea  
 Vomiting  
 Danger of aspiration.  
 Lung damage  
 Oedema of the lungs  
 Chronic toxicity:  
 Effects/damages the central nervous system  
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 21.09.2022 / 0014  
Replacing version dated / version: 01.11.2021 / 0013  
Valid from: 21.09.2022  
PDF print date: 24.09.2022  
Diesel Conditioning and Anti - Gel  
300 ml Art.: 6750 7023, Art.: 6754 7023

## 5.1 Extinguishing media

### Suitable extinguishing media

CO2  
Foam  
Dry extinguisher

### Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Toxic pyrolysis products.  
Flammable vapour/air mixtures  
Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

Avoid all contact with product.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Do not breathe in vapours and atomized spray.

Keep away from sources of ignition - Do not smoke.

Take measures against electrostatic charging, if appropriate.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

GB

Page 5 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.  
 Exposed employees should have regular medical check-ups.  
 Do not carry cleaning cloths soaked in product in trouser pockets.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Solvent resistant floor  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store in a dry place.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 600 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene		
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name	1,2,4-trimethylbenzene		
WEL-TWA: 125 mg/m <sup>3</sup> (25 ppm) (Trimethylbenzenes, all isomers or mixtures) (WEL), 20 ppm (100 mg/m <sup>3</sup> ) (EU)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-111 U(C) (549 178)</li> <li>- INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 2008 - EU project BC/CEN/ENTR/000/2002-16 card 54-1 (2004)</li> <li>- OSHA PV2091 (Trimethylbenzenes) - 1987</li> </ul>		
BMGV: ---	Other information: ---		

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	

Ⓢ

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	

Hydrocarbons, C10, aromatics, >1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m <sup>3</sup>	

1,2,4-trimethylbenzene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,12	mg/l	
	Environment - marine		PNEC	0,12	mg/l	
	Environment - sewage treatment plant		PNEC	2,41	mg/l	
	Environment - sediment, freshwater		PNEC	13,56	mg/kg dry weight	
	Environment - sediment, marine		PNEC	13,56	mg/kg dry weight	
	Environment - soil		PNEC	2,34	mg/kg dry weight	
Consumer	Human - inhalation	Short term, local effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	9512	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	29,4	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	15	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	29,4	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	16171	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - blood	Long term, local effects	DNEL	100	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	100	mg/m <sup>3</sup>	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit



Page 7 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 21.09.2022 / 0014  
Replacing version dated / version: 01.11.2021 / 0013  
Valid from: 21.09.2022  
PDF print date: 24.09.2022  
Diesel Conditioning and Anti - Gel  
300 ml Art.: 6750 7023, Art.: 6754 7023

value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. EN 14042.  
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Solvent resistant protective gloves (EN ISO 374).  
Recommended  
Protective nitrile gloves (EN ISO 374).  
Minimum layer thickness in mm:  
0,5  
Permeation time (penetration time) in minutes:  
120  
Protective hand cream recommended.  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
If OES or MEL is exceeded.  
Gas mask filter AX (EN 14387), code colour brown.  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

## 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	0,6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Upper explosion limit:	6,5 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Flash point:	62 °C
Auto-ignition temperature:	>200 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	12,7 mm <sup>2</sup> /s (40°C)
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	0,84-0,86 g/ml
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

## 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Possible build up of flammable vapour/air mixture.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No decomposition if used as intended.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Electrostatic charge

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.  
 Avoid contact with other chemicals.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Diesel Conditioning and Anti - Gel 300 ml Art.: 6750 7023, Art.: 6754 7023						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.



Page 9 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						positive, the real Naphthalene content is >=1%
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	>5	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Analogous conclusion
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking., Product removes fat.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEC	>= 5220	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion inhalation
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes

GB

Page 10 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Symptoms:						unconsciousness , headaches, dizziness, Dermatitis (skin inflammation), Reddening, drying of the skin., mucous membrane irritation, nausea and vomiting., diarrhoea, lower abdominal pain
-----------	--	--	--	--	--	---

Hydrocarbons, C10, aromatics, >1% naphthalene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	6318	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEL	>450	mg/kg	Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion

Page 11 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Symptoms:						drowsiness, headaches, drowsiness, dizziness
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative, Analogous conclusion

1,2,4-trimethylbenzene						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	18	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (ACUTE DERMAL IRRITATION/CORROSION)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:				Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause respiratory irritation., STOT SE 3, H335

GB

Page 12 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

Symptoms:						drowsiness, unconsciousness, headaches, fatigue, dizziness, nausea
-----------	--	--	--	--	--	--

## 11.2. Information on other hazards

Diesel Conditioning and Anti - Gel 300 ml Art.: 6750 7023, Art.: 6754 7023						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Diesel Conditioning and Anti - Gel 300 ml Art.: 6750 7023, Art.: 6754 7023							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							Concentration in organisms possible.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree(complexing organic substance) $\geq$ 80%/28d: n.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,10	mg/l	Oncorhynchus mykiss	QSAR	

Page 13 of 18

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.09.2022 / 0014

Replacing version dated / version: 01.11.2021 / 0013

Valid from: 21.09.2022

PDF print date: 24.09.2022

Diesel Conditioning and Anti - Gel

300 ml Art.: 6750 7023, Art.: 6754 7023

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.7. Other adverse effects:							Product floats on the water surface.
Water solubility:			~10	mg/l			Slight

#### Hydrocarbons, C10, aromatics, >1% naphthalene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous conclusion
12.3. Bioaccumulative potential:	BCF		99-5780				High
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriella subcapitata		
12.2. Persistence and degradability:		28d	58	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

#### 1,2,4-trimethylbenzene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	7,72	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	3,6	mg/l	Daphnia magna		
12.3. Bioaccumulative potential:	BCF		275	%			
12.3. Bioaccumulative potential:	Log Kow		3,63	%			Lowcalculated

### SECTION 13: Disposal considerations

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 13 07 03 other fuels (including mixtures)

Recommendation:

Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Implement substance recycling.  
 E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Classification code: n.a.  
 LQ: n.a.  
 14.5. Environmental hazards: Not applicable  
 Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 Marine Pollutant: n.a.  
 14.5. Environmental hazards: Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:  
 14.3. Transport hazard class(es): n.a.  
 14.4. Packing group: n.a.  
 14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 78,84 %

### REGULATION (EC) No 648/2004

n.a.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 2  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Carc. — Carcinogenicity  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Flam. Liq. — Flammable liquid  
 Acute Tox. — Acute toxicity - inhalation  
 Skin Irrit. — Skin irritation  
 Eye Irrit. — Eye irritation  
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).  
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.



Page 16 of 18  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 21.09.2022 / 0014  
Replacing version dated / version: 01.11.2021 / 0013  
Valid from: 21.09.2022  
PDF print date: 24.09.2022  
Diesel Conditioning and Anti - Gel  
300 ml Art.: 6750 7023, Art.: 6754 7023

Förch SAS  
ZAE Le Marchais Renard  
CS 50125 Montereau-sur-le-Jard  
77019 Melun Cedex  
Frankreich  
Tel. +33 1 64 14 48 48  
Fax. +33 1 64 14 48 49  
E-Mail: [info@forch.fr](mailto:info@forch.fr)  
Internet: [www.forch.fr](http://www.forch.fr)

S.C. Foerch S.R.L.  
Str. Zizinului nr.110  
500407 Brasov  
Rumänien  
Tel. +40 368 408192  
Fax. +40 368 408193  
E-Mail: [info@foerch.ro](mailto:info@foerch.ro)  
Internet: [www.foerch.ro](http://www.foerch.ro)

Foerch AG  
Muttenerstrasse 143  
4133 Pratteln  
Schweiz  
Tel. +41 61 8262031  
Fax. +41 61 8262039  
E-Mail: [info@foerch.ch](mailto:info@foerch.ch)  
Internet: [www.foerch.ch](http://www.foerch.ch)

Foerch Bulgaria EOOD  
475 Botevgradsko Shose Blvd.  
BG 1517 Sofia, Bulgaria  
Tel. 00359 2 981 2841  
Fax. 00359 982 10 30 86  
E-Mail: [info@foerch.bg](mailto:info@foerch.bg)

Förch d.o.o.  
Buzinska cesta 58  
10010 Zagreb  
Kroatien  
Tel. +385 1 2912900  
Fax. +385 1 2912901  
E-Mail: [info@foerch.hr](mailto:info@foerch.hr)  
internet: [www.foerch.hr](http://www.foerch.hr)

Theo Förch GmbH  
Röcklbrunnstraße 39A  
5020 Salzburg  
Österreich  
Tel. +43 662 875574-0  
Fax +43 662 878677-21  
Verkauf Tel. +43 662 875574-900  
Verkauf Fax +43 662 875574-30  
E-Mail: [info@foerch.at](mailto:info@foerch.at)  
Internet: [www.foerch.at](http://www.foerch.at)

Förch Componentes para Taller S.L.  
Camino de San Antón, S/N  
18102 Ambroz (Granada)  
Spanien  
Tel. +34 958 40 17 76  
Fax. +34 958 40 17 87  
E-Mail: [info@forch.es](mailto:info@forch.es)  
Internet: [www.forch.es](http://www.forch.es)

Förch A/S  
Hagemannsvej 3  
8600 Silkeborg  
Dänemark  
Tel. +45 86 823711  
Fax. +45 86 800617  
E-Mail: [info@foerch.dk](mailto:info@foerch.dk)  
Internet: [www.foerch.dk](http://www.foerch.dk)

Lhomme Tools & Fasteners BV  
Seinhuisstraat 5 B4  
Poort 0331  
3600 Genk  
Belgien  
Tel. +32 89 71 66 61  
E-Mail: [info@lhommetools.be](mailto:info@lhommetools.be)  
Internet: [www.lhommetools.be](http://www.lhommetools.be)

Ziebe Limited  
7 Century Court, Westcott,  
Aylesbury, Bucks, HP18 0XP (UK)  
Grossbritannien  
Tel +44 12 96 65 52 82  
E-Mail: [sales@ziebe.co.uk](mailto:sales@ziebe.co.uk)  
Internet: [www.ziebe.co.uk](http://www.ziebe.co.uk)

Förch Polska Sp. z o.o.  
Mikdyrzecze Gorne 379  
43-392 K/Bielska-Bialej  
Polen  
Tel. +48 338196000  
Fax. +48 338158548  
E-Mail: [info@forch.pl](mailto:info@forch.pl)  
Internet: [www.forch.pl](http://www.forch.pl)

Vardalis SM P.C.  
Ethnikis Antistasis 62  
57007 Chalkidona-Thessaloniki  
Griechenland  
Tel. +30 23910 21222  
Fax. +30 23910 21223  
E-Mail: [info@forch.gr](mailto:info@forch.gr)  
Internet: [www.forch.gr](http://www.forch.gr)

Förch Kereskedelmi Kft  
Börgöndi út 14  
8000 Székesfehérvár  
Ungarn  
Tel. +36 22 348348  
Fax. +36 22 348355  
E-Mail: [info@foerch.hu](mailto:info@foerch.hu)  
Internet: [www.foerch.hu](http://www.foerch.hu)

Förch S.r.l.  
Via Antonio Stradivari 4  
39100 Bolzano (BZ)  
Italien  
Tel: +39 0471 204330  
Fax: +39 0471 204290  
E-Mail: [info@forch.it](mailto:info@forch.it)  
Internet: [www.forch.it](http://www.forch.it)

Förch Nederland BV  
Twentepoort Oost 51  
7609 RG Almelo  
Niederlande  
Tel. +31 85 77 32 420  
E-Mail: [info@foerch.nl](mailto:info@foerch.nl)  
Internet: [www.foerch.nl](http://www.foerch.nl)

AB varahlutir ehf  
Funahöfði 9  
110 Reykjavík  
Tel. +354 567 6020  
E-mail: [ab@ab.is](mailto:ab@ab.is)  
Internet: [www.ab.is](http://www.ab.is)

Förch Slovensko s.r.o.  
Rosinská cesta 8  
010 08 Žilina  
Slowakei  
Tel +421 41 5002454  
E-Mail: [info@forch.sk](mailto:info@forch.sk)  
Internet: [www.forch.sk](http://www.forch.sk)

Förch Sverige AB  
Brännarevägen 1  
151 55 Södertälje  
Schweden  
Tel. +46 855089264  
E-mail: [info@foerch.se](mailto:info@foerch.se)  
Internet: [www.foerch.se](http://www.foerch.se)

Förch, s.r.o.  
 Dopravní 1314/1  
 104 00 Praha 10 – Uhřetíněves  
 Tschechien  
 Tel. +420 271 001 984-9  
 E-Mail: info@foerch.cz  
 Internet: www.foerch.cz

FORCH d.o.o.  
 Ljubljanska cesta 51A  
 1236 Trzin  
 Slowenien  
 Tel. +386 1 2442490  
 Fax. +386 1 2442492  
 E-Mail: info@foerch.si  
 Internet: www.foerch.si

Forch Australia  
 2 Forward Street  
 Gnangara WA 6077  
 Tel. +61 (08) 9303 9113  
 Fax. +61 (08) 9303 9114  
 Emergency telephone: +614 13 550 330  
 Email : sales@forch.com.au  
 Internet: www.forch.com.au

Troscoe Ltd  
 Unit 6, 13 Highbrook Drive  
 East Tamaki 2013, New Zealand  
 Tel: +64 21 081 30780 / +64 21 024 05583  
 Email:sales@forchnz.co.nz  
 Internet: www.forchnz.co.nz

Förch Portugal Lda  
 Centro Empresarial Sintra-Estoril III  
 Rua Pé de Mouro, N.º 33, Armazém J  
 2710-335 Sintra  
 Portugal  
 Tel. +351 917314442  
 E-Mail: info@forch.pt  
 Internet: www.forch.pt

Trigers SIA  
 Straupes iela 3  
 1073 Riga  
 Lettland  
 Tel. +371 6 7 90 25 15  
 Fax. +371 67 90 24 96  
 E-Mail: trigers@trigers.lv  
 Internet: www.trigers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.  
 Haramidere Mevkii Beysan Sanayi  
 Sitesi Birlık Caddesi No:6/3  
 34524 Beylikdüzü / Istanbul  
 Türkei  
 Tel. +90 (0)212 422 8744-45  
 Fax. +90 (0)212 422 8788  
 E-Mail: info@forch.com.tr  
 Internet: www.forch.com.tr

Total Consumables Ltd  
 Coolnafearagh  
 Monasterevin  
 Co. Kildare  
 W34 TX29  
 Irland  
 Tel. +353871271473

Venus Arma d.o.o.  
 Partner Theo Förch GmbH & Co. KG  
 Batajnicki drum 18a  
 11080 Zemun  
 Republika Srbija  
 Tel. +381 11 407-20-91  
 Fax. +381 11 407-20-91  
 E-Mail: office@foerch.rs  
 Internet: www.foerch.rs

### Any abbreviations and acronyms used in this document:

acc., acc. to	according, according to
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX	Adsorbable organic halogen compounds
approx.	approximately
Art., Art. no.	Article number
ASTM	ASTM International (American Society for Testing and Materials)
ATE	Acute Toxicity Estimate
BAM	Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF	Bioconcentration factor
BSEF	The International Bromine Council
bw	body weight
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, EbLx (x = 10, 50)	Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC	European Community
ECHA	European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)	Effect Concentration/Level for x % effect
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

Page 18 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 21.09.2022 / 0014  
 Replacing version dated / version: 01.11.2021 / 0013  
 Valid from: 21.09.2022  
 PDF print date: 24.09.2022  
 Diesel Conditioning and Anti - Gel  
 300 ml Art.: 6750 7023, Art.: 6754 7023

EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, E<sub>μ</sub>Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute for Occupational Safety and Health (USA)  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 OSHA Occupational Safety and Health Administration (USA)  
 PBT persistent, bioaccumulative and toxic  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 ppm parts per million  
 PVC Polyvinylchloride  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SVHC Substances of Very High Concern  
 Tel. Telephone  
 TOC Total organic carbon  
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
 VOC Volatile organic compounds  
 vPvB very persistent and very bioaccumulative  
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
 No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.