

Page 1 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

V-Belt Treatment P325

400 ml Art.: 6740 0400, Art.: 6744 0400

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant and greasing spray

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400



Danger

H315-Causes skin irritation. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves.
P312-Call a POISON CENTRE / doctor if you feel unwell.
P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C6, isoalkanes, <5% n-hexane

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	01-2119475514-35-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	921-024-6
CAS	---
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Butane	
Registration number (REACH)	---
Index	601-004-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	203-448-7
CAS	106-97-8
content %	20-40
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

Hydrocarbons, C6, isoalkanes, <5% n-hexane	
Registration number (REACH)	01-2119484651-34-XXXX
Index	---

Page 3 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0021
 Replacing version dated / version: 06.08.2018 / 0020
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 V-Belt Treatment P325
 400 ml Art.: 6740 0400, Art.: 6744 0400

EINECS, ELINCS, NLP, REACH-IT List-No.	931-254-9
CAS	(64742-49-0)
content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Propane	
Registration number (REACH)	---
Index	601-003-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	200-827-9
CAS	74-98-6
content %	5-25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.
 Danger of aspiration.
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effect on the central nervous system

Coordination disorders

Mental confusion

Ingestion:

Nausea

Vomiting

Danger of aspiration.

oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

5.1 Extinguishing media

Suitable extinguishing media

Foam
Dry extinguisher
CO₂

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Toxic gases
Danger of bursting (explosion) when heated
Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent surface and ground-water infiltration, as well as ground penetration.
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
Active substance:
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid inhalation of the vapours.
Keep away from sources of ignition - Do not smoke.
Do not use on hot surfaces.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Observe special regulations for aerosols!
Keep protected from direct sunlight and temperatures over 50°C.
Store in a well ventilated place.
Observe special storage conditions.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Content %:40-60
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Butane	Content %:20-40
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)	---
Monitoring procedures:	- Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993	
BMGV: ---	Other information: ---	

Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane	Content %:10-30
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Propane	Content %:5-25
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990	
BMGV: ---	Other information: ---	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	2035	mg/kg bw/day	

Page 6 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0021
 Replacing version dated / version: 06.08.2018 / 0020
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 V-Belt Treatment P325
 400 ml Art.: 6740 0400, Art.: 6744 0400

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Normally not necessary.

Skin protection - Hand protection:
 Normally not necessary.
 With long-term contact:
 Protective nitrile gloves (EN ISO 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 >= 480
 Protective hand cream recommended.

Skin protection - Other:
 Normally not necessary.

Respiratory protection:

Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0021

Replacing version dated / version: 06.08.2018 / 0020

Valid from: 01.11.2021

PDF print date: 01.11.2021

V-Belt Treatment P325

400 ml Art.: 6740 0400, Art.: 6744 0400

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Light yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	n.a.
Upper explosion limit:	n.a.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	3,2-3,7 bar (50°C)
Vapour pressure:	1,7-2,3 bar (20°C)
Density and/or relative density:	0,673 g/cm ³ (20°C)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	No
Solubility(ies):	Organic solvents
Solvents content:	70-75 %

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

Page 8 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

See also section 5.2
No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

V-Belt Treatment P325

400 ml Art.: 6740 0400, Art.: 6744 0400

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Product removes fat., Irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing
Specific target organ toxicity - single exposure (STOT-SE):						May cause respiratory irritation.
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Butane

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Skin Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Aspiration hazard:						Asp. Tox. 1
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		

Page 10 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

11.2. Information on other hazards

V-Belt Treatment P325 400 ml Art.: 6740 0400, Art.: 6744 0400						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

V-Belt Treatment P325 400 ml Art.: 6740 0400, Art.: 6744 0400							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.

12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Leuciscus idus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%			Readily biodegradable, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other information:	AOX		0	%			
Other information:	DOC						DOC-elimination degree (complexing organic substance) >= 80%/28d., n.a.

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Hydrocarbons, C6, isoalkanes, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOEC/NOEL	28d	4,09	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to fish:	EC50	96h	18,27	mg/l	Oncorhynchus mykiss		

Page 12 of 17
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0021
 Replacing version dated / version: 06.08.2018 / 0020
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 V-Belt Treatment P325
 400 ml Art.: 6740 0400, Art.: 6744 0400

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	7,14	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to daphnia:	LC50	48h	3,87	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	13,56	mg/l	Pseudokirchneriella subcapitata	QSAR	
12.1. Toxicity to algae:	ErL50	72h	55	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable (Analogous conclusion), Analogous conclusion
12.3. Bioaccumulative potential:	Log Kow		4				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
 The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.
 Do not perforate, cut up or weld uncleaned container.
 Residues may present a risk of explosion.
 15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):

14.4. Packing group:

Classification code:

2.1

-

5F



Page 13 of 17
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

LQ: 1 L
14.5. Environmental hazards: environmentally hazardous
Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name: AEROSOLS (HYDROCARBON MIXTURE)
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
EmS: F-D, S-U
Marine Pollutant: Yes
14.5. Environmental hazards: environmentally hazardous



Transport by air (IATA)

14.2. UN proper shipping name: Aerosols, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Regulation (EC) No 1907/2006, Annex XVII
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 657,5 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16
Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0021
Replacing version dated / version: 06.08.2018 / 0020
Valid from: 01.11.2021
PDF print date: 01.11.2021
V-Belt Treatment P325
400 ml Art.: 6740 0400, Art.: 6744 0400

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H220 Extremely flammable gas.

Skin Irrit. — Skin irritation
Asp. Tox. — Aspiration hazard
STOT SE — Specific target organ toxicity - single exposure - narcotic effects
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Aerosol — Aerosols
Flam. Liq. — Flammable liquid
Flam. Gas — Flammable gases - Flammable gas

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
ZAE Le Marchais Renard
CS 50125 Montereau-sur-le-Jard
77019 Melun Cedex
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

Förch SAS
17 rue de Marbourg
9764 MARNACH
Luxemburg
Tel. +352 269 03267
Fax +352 269 03368
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului nr.110
500407 Brasov
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 8262031
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0021

Replacing version dated / version: 06.08.2018 / 0020

Valid from: 01.11.2021

PDF print date: 01.11.2021

V-Belt Treatment P325

400 ml Art.: 6740 0400, Art.: 6744 0400

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Talleres S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

SKY NORD
Sofia Kovalevskaya ul.
D.1, ST.2, K.1
RUS 127247 MOSCOW
Russland
E-Mail: skynord.office@gmail.com

Förch Polska Sp. z o.o.
Międzyrzecz Górne 379
43-392 K/Bielska-Białej
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 12
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetěves
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Troscoe Ltd
Unit 6, 13 Highbrook Drive
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email: sales@forchnz.co.nz
Internet: www.forchnz.co.nz

Förch Portugal Lda
Rua República da Bolívia No. 69, 1 esq
1500-544 Lisboa
Portugal
Tel. +351 917314442
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes iela 3
1073 Rīga
Lettland
Tel. +371 6 7 90 25 15
Fax. +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Sti.
Haramidere Mevkii Beysan Sanayi
Sitesi Birlik Caddesi No:6/3
34524 Beylikdüzü / İstanbul
Türkei
Tel. +90 (0)212 422 8744-45
Fax. +90 (0)212 422 8788
E-Mail: info@forch.com.tr
Internet: www.forch.com.tr

Total Consumables Ltd
Coolnafeearagh
Monasterevin
Co. Kildare
W34 TX29
Irland
Tel. +353871271473

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
ATE Acute Toxicity Estimate
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
EC European Community
ECHA European Chemicals Agency
ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, EμCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0021

Replacing version dated / version: 06.08.2018 / 0020

Valid from: 01.11.2021

PDF print date: 01.11.2021

V-Belt Treatment P325

400 ml Art.: 6740 0400, Art.: 6744 0400

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.