

(B) —
 Page 1 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.02.2022 / 0013
 Replacing version dated / version: 01.11.2021 / 0012
 Valid from: 21.02.2022
 PDF print date: 21.02.2022
 PDF print date: 21.02.2022
 Professional Aluminium Contact Grease S424
 200 ml Art.: 6510 5005, Art.: 6514 5005

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant Uses advised against: No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body: $\ensuremath{\mathbb{R}}$

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week) +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixtureClassification according to Regulation (EC) 1272/2008 (CLP)Hazard classHazard categoryHazard statementAerosol3H229-Pressurised container: May burst if heated.

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)



B R
 Page 2 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

Warning

H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251-Do not pierce or burn, even after use. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly with soap and water.

Remove contaminated clothing immediately.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water. Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. eyes, reddened watering eyes reddening of the skin Dermatitis (skin inflammation) Allergic reaction

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.



(B) (RL

Page 3 of 13

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

CO2

Extinction powder Foam Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of carbon Oxides of phosphorus Oxides of sulphur Oxides of nitrogen Toxic gases Danger of bursting (explosion) when heated

5.3 Advice for firefighters

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13. Or

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations



Page 4 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

Avoid contact with eyes or skin. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Do not store with oxidizing agents. Observe special regulations for aerosols! Keep protected from direct sunlight and temperatures over 50°C. Store cool. Store in a dry place. **7.3 Specific end use(s)**

No information available at present.

(B) (RL)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Aluminium powder	(stabilised)		Content %:
WEL-TWA: 10 mg/m3 (total inh. du	ist), 4 mg/m3	WEL-STEL:		
(resp. dust)				
Monitoring procedures:		-		
BMGV:			Other information:	
Chemical Name	Aluminium powder	(stabilised)		Content %:
OELV-8h: 1 mg/m3 (R)		OELV-15min:		
Monitoring procedures:				
BLV:			Other information:	
Chemical Name	Stearates			Content %:
OELV-8h: 10 mg/m3 (except lead s	stearate)	OELV-15min:		
Monitoring procedures:		-		
BLV:			Other information:	

Aluminium powder (stabilised)						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,0749	mg/l	
	Environment - sewage		PNEC	20	mg/l	
	treatment plant					
Consumer	Human - oral	Long term, systemic	DNEL	3,95	mg/kg	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	3,72	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic	DNEL	3,72	mg/m3	
		effects				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.



GB (RL)

Page 5 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU. (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: With danger of contact with eyes. Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Chemical resistant protective gloves (EN ISO 374). Recommended Protective Neoprene® / polychloroprene gloves (EN ISO 374). Protective nitrile gloves (EN ISO 374). Minimum layer thickness in mm: >= 0,4 Permeation time (penetration time) in minutes: >= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

Additional information on hand protection - No tests have been performed. In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications. Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



(B) (RL) Page 6 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Physical state:

Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives: Oxidizing solids: Evaporation rate:

Paste, solid. The propellant is not released when used in accordance with the regulations. Silver, Grey Characteristic There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. >350 °C There is no information available on this parameter. Mixture is non-soluble (in water). >20,5 mm2/s (40°C) Not miscible Does not apply to mixtures. 0,1 hPa (20°C) Does not apply to aerosols. Does not apply to aerosols. Does not apply to aerosols.

Product is not explosive. No

n a

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested. **10.2 Chemical stability** Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7. Heating, open flame, ignition sources Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7. Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005



(B) (R)
Page 7 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013
Replacing version dated / version: 01.11.2021 / 0012
Valid from: 21.02.2022
PDF print date: 21.02.2022
PDF print date: 21.02.2022
Professional Aluminium Contact Grease S424
200 ml Art.: 6510 5005, Art.: 6514 5005

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Aluminium powder (stabilised)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	15900	mg/kg	Rat	OECD 401 (Acute Oral	Analogous
					Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		Dust, Mist
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin						No (skin contact)
sensitisation:						
Symptoms:						mucous
						membrane
						irritation

11.2. Information on other hazards

200 ml Art.: 6510 5005, Art.: 6514 5005						
oxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
ndocrine disrupting properties:						Does not apply
						to mixtures.
Other information:						No other
						relevant
						information
						available on
						adverse effects
						on health.

SECTION 12: Ecological information

	Possibly more information on environmental effects, see Section 2.1 (classification).						
Professional Aluminium		e S424					
200 ml Art.: 6510 5005, A	rt.: 6514 5005						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.



(B) (R)
Page 8 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013
Replacing version dated / version: 01.11.2021 / 0012
Valid from: 21.02.2022
PDF print date: 21.02.2022
PDF print date: 21.02.2022
Professional Aluminium Contact Grease S424
200 ml Art.: 6510 5005, Art.: 6514 5005

12.7. Other adverse effects:					No information available on other adverse effects on the environment.
Other information:					DOC-elimination degree(complexi ng organic substance)>= 80%/28d: n.a.
Other information:	AOX	0	%		According to the recipe, contains no AOX.

es
relevant for
ganic
stances.
st

SECTION 13: Disposal considerations

13.1 Waste treatment methods For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

12 01 12 spent waxes and fats

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements		
14.1. UN number or ID number:	1950	
Transport by road/by rail (ADR/RID)		
14.2. UN proper shipping name:		۵
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	•
Classification code:	5A	
LQ:	1 L	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	E	
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		
AEROSOLS		
14.3. Transport hazard class(es):	2.2	
14.4. Packing group:	-	*
EmS:	F-D, S-U	
Marine Pollutant:	n.a	
14.5. Environmental hazards:	Not applicable	
Transport by air (IATA)		
14.2. UN proper shipping name:		
17.2. On proper shipping name.		



(B) (RL)

Page 9 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

Aerosols, non-flammable 14.3. Transport hazard class(es): 14.4. Packing group: 14.5. Environmental hazards:

2.2

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable. Minimum amount regulations have not been taken into account. Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148. Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
25	Oxygen		200	2000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aerosol 3, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Aerosol — Aerosols

Key literature references and sources for data:



GB Page 10 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005 Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. GESTIS Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended. National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended. Förch SAS Förch SAS S.C. Foerch S.R.I. ZAE Le Marchais Renard 17 rue de Marbourg Str. Zizinului nr.110 CS 50125 Montereau-sur-le-Jard 9764 MARNACH 500407 Brasov 77019 Melun Cedex Rumänien Luxemburg Tel. +352 269 03267 Tel. +40 368 408192 Frankreich Tel. +33 1 64 14 48 48 Fax +352 269 03368 Fax. +40 368 408193 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr E-Mail: info@foerch.ro E-Mail: info@forch.fr Internet: www.forch.fr Internet: www.foerch.ro Internet: www.forch.fr Foerch AG Foerch Bulgaria EOOD Förch d.o.o. Muttenzerstrasse 143 475 Botevgradsko Shose Blvd. Buzinska cesta 58 BG 1517 Sofia, Bulgaria 4133 Pratteln 10010 Zagreb Tel. 00359 2 981 2841 Schweiz Kroatien Fax. 00359 982 10 30 86 Tel. +41 61 8262031 Tel. +385 1 2912900 Fax. +41 61 8262039 E-Mail: info@foerch.bg Fax. +385 1 2912901 E-Mail: info@foerch.ch E-Mail: info@foerch.hr internet: www.foerch.hr Internet: www.foerch.ch Theo Förch GmbH Förch Componentes para Taller S.L. Förch A/S Röcklbrunnstraße 39A Camino de San Antón, S/N Hagemannsvej 3 8600 Silkeborg 5020 Salzburg 18102 Ambroz (Granada) Österreich Spanien Dänemark Tel. +43 662 875574-0 Tel. +34 958 40 17 76 Tel. +45 86 823711 Fax +43 662 878677-21 Fax. +34 958 40 17 87 Fax. +45 86 800617 Verkauf Tel. +43 662 875574-900 E-Mail: info@forch.es E-Mail: info@foerch.dk Verkauf Fax +43 662 875574-30 Internet: www.forch.es Internet: www.foerch.dk E-Mail: info@foerch.at Internet: www.foerch.at Lhomme Tools & Fasteners BV Ziebe Limited SKY NORD Sofia Kovalevskaya ul. Seinhuisstraat 5 B4 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Poort 0331 D.1, ST.2, K.1 3600 Genk Grossbritannien RUS 127247 MOSCOW Tel +44 12 96 65 52 82 Belgien Russland Tel. +32 89 71 66 61 E-Mail: sales@ziebe.co.uk E-Mail: skynord.office@gmail.com E-Mail: info@lhommetools.be Internet: www.ziebe.co.uk Internet: www.lhommetools.be Förch Polska Sp. z.o.o Vardalis SM P.C. Förch Kereskedelmi Kft Ethnikis Antistasis 62 Miedzyrzecze Górne 379 Börgöndi út 14 43-392 K/Bielska-Bialej 8000 Székesfehérvár 57007 Chalkidona-Thessaloniki Polen Griechenland Ungarn Tel. +48 338196000 Tel. +36 22 348348 Tel. +30 23910 21222 Fax. +48 338158548 Fax. +30 23910 21223 Fax. +36 22 348355 E-Mail: info@forch.pl E-Mail: info@forch.gr E-Mail: info@foerch.hu Internet: www.forch.pl Internet: www.forch.gr Internet: www.foerch.hu



Page 11 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDE print date: 21.02.2022

PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

Förch S.r.l. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

(B) (RL)

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda Rua República da Bolivia No. 69, 1 esq 1500-544 Lisboa Portugal Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland Tel. +353871271473 Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl

Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114 Emergency telephone: +614 13 550 330 Email : sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

Förch, s.r.o. Dopravní 1314/1 104 00 Praha 10 – Uhříněves Tschechien Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583 Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul Türkei Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Article number Art., Art. no. ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA Bioconcentration factor BCF BSEF The International Bromine Council



(B) (RL) Page 12 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005 bw body weight CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) EC European Community ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC EINECS European Inventory of Existing Commercial Chemical Substances **ELINCS** European List of Notified Chemical Substances FN European Norms EPA United States Environmental Protection Agency (United States of America) ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) et cetera etc. EU European Union Ethylene-vinyl alcohol copolymer EVAL Fax number Fax. general gen. GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code) International Maritime Code for Dangerous Goods IMDG-code incl including, inclusive IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Logarithm of octanol-water partition coefficient Log Kow, Log Pow Limited Quantities LQ MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable not available n.av. not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NLP No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic ora. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PF Polyethylene PNEC Predicted No Effect Concentration ppm parts per million **PVC** Polyvinylchloride REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel. Telephone TOC Total organic carbon



Page 13 of 13 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.02.2022 / 0013 Replacing version dated / version: 01.11.2021 / 0012 Valid from: 21.02.2022 PDF print date: 21.02.2022 Professional Aluminium Contact Grease S424 200 ml Art.: 6510 5005, Art.: 6514 5005

 UN RTDG
 United Nations Recommendations on the Transport of Dangerous Goods

 VOC
 Volatile organic compounds

 vPvB
 very persistent and very bioaccumulative

 wwt
 wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility. These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

(B) (RL)