

Page 1 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

**1.1 Product identifier** 

(GB)

## UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture: Underfloor protection Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0 Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

**Telephone number of the company in case of emergencies:** +49 (0) 700 / 24 112 112 (TFC)

## **SECTION 2: Hazards identification**

	of the substance or mix ording to Regulation (E	
Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 23

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959



H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible. Solvent naphtha (petroleum), light arom. Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Hydrocarbons, C9, aromatics

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %). The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC)

I ne mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

Aerosol

#### 3.1 Substances

n.a. **3.2 Mixtures** 

Solvent naphtha (petroleum), light arom.	
Registration number (REACH)	
Index	649-356-00-4
EINECS, ELINCS, NLP, REACH-IT List-No.	265-199-0
CAS	64742-95-6
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 3, H226
	STOT SE 3, H335
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Registration number (REACH)	01-2119473851-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	920-750-0
CAS	
content %	10-<20
	· · · · · · · · · · · · · · · · · · ·



Page 3 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 2, H225
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411
Hydrocarbons, C9, aromatics	
Registration number (REACH)	01-2119455851-35-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	918-668-5
CAS	(64742-95-6)
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	Flam. Liq. 3, H226
	STOT SE 3 H335

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

(GB)

#### Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

#### Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water. Do not induce vomiting. Consult doctor immediately. Danger of aspiration.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur: Irritation of the respiratory tract Coughing Headaches Dizziness Effects/damages the central nervous system With long-term contact: Dermatitis (skin inflammation) Drying of the skin. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours. **4.3 Indication of any immediate medical attention and special treatment needed** 



Page 4 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

n.c.

(GB)

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media Suitable extinguishing media

Water jet spray CO2 Extinction powder Foam

#### Unsuitable extinguishing media High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop: Oxides of nitrogen Oxides of carbon Hydrocarbons Toxic gases Explosive vapour/air or gas/air mixtures. Danger of bursting (explosion) when heated Explosive vapour/air or gas/air mixtures.

#### **5.3 Advice for firefighters**

For personal protective equipment see Section 8. In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

#### SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

## Avoid inhalation, and contact with eyes or skin.

## 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### **6.2 Environmental precautions**

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.

Prevent surface and ground-water infiltration, as well as ground penetration.

## 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid inhalation of the vapours. Prevent long-term skin contact. Keep away from sources of ignition - Do not smoke.



Page 5 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells. Store product closed and only in original packing.

Observe special storage conditions.

(GB)

Observe special regulations for aerosols!

Keep protected from direct sunlight and temperatures over 50°C. Store in a well ventilated place.

## 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 600 mg/m3

Chemical Name	Solvent naphtha (petroleum), light arom.	
WEL-TWA: 500 mg/m3 (Aromatics)		
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (8<sup>-</sup></li> </ul>	
	<ul> <li>Draeger - Hydrocarbons 2/a (81 03</li> </ul>	581)
	- Compur - KITA-187 S (551 174)	
BMGV:		Other information:
Chemical Name	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
WEL-TWA: 1200 mg/m3	WEL-STEL:	
Monitoring procedures:	<ul> <li>Draeger - Hydrocarbons 0,1%/c (8<sup>-</sup></li> </ul>	03 571)
	<ul> <li>Draeger - Hydrocarbons 2/a (81 03</li> </ul>	581)
	<ul> <li>Compur - KITA-187 S (551 174)</li> </ul>	
BMGV:		Other information: (OEL acc. to RCP-method,
		paragraphs 84-87, EH40)
Chemical Name	Hydrocarbons, C9, aromatics	
WEL-TWA: 500 mg/m3 (Aromatics)		
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (8	03 571)
	- Draeger - Hydrocarbons 2/a (81 03	
	- Compur - KITA-187 S (551 174)	,
BMGV:		Other information:
Chemical Name	Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL:	
Monitoring procedures:	<ul> <li>Compur - KITA-125 SA (549 954)</li> </ul>	
	<ul> <li>OSHA PV2077 (Propane) - 1990</li> </ul>	
BMGV:		Other information:
Chemical Name	Asphalt	
WEL-TWA: 5 mg/m3 (Asphalt, petr	oleum fumes) WEL-STEL: 10 mg/m3 (Aspha	It, petroleum fumes)
Monitoring procedures:		
BMGV:		Other information:
Chemical Name	Calcium carbonate	
WEL-TWA: 4 mg/m3 (respirable du	ist), 10 mg/m3 WEL-STEL:	
(total inhalable dust)		
Monitoring procedures:		
BMGV:		Other information:
 ®		



	g to Regulation (EC) No 1907/2	2006, Annex II				
Revision date / version: 21. Replacing version dated / v						
/alid from: 21.09.2022						
PDF print date: 23.09.2022 JNDERBODY SEAL BLAC						
500 ml Art.: 6610 0959, Art.	: 6614 0959					
Chemical Name	Silica, amorphous					
WEL-TWA: 6 mg/m3 (tota (resp. dust)	al inh. dust), 2,4 mg/m3	WEL-STEL:				
Monitoring procedures:		-	T			
BMGV:			Other inforr	nation:	-	
Chemical Name WEL-TWA: 1000 ppm (E)	Isobutane () (ACGIH)	WEL-STEL:				
Monitoring procedures: BMGV:		ompur - KITA-113 SB(C) (549		n ation :		
-	Butane		Other inform	nation:	-	
Chemical Name WEL-TWA: 600 ppm (145)	50 mg/m3)	WEL-STEL: 750 ppm (1810				
Monitoring procedures:		ompur - KITA-221 SA (549 459 SHA PV2010 (n-Butane) - 199				
BMGV:	- 0	STA P 2010 (II-Butane) - 199	Other inforr	nation:	-	
Solvent naphtha (petroleu	ım), light arom.					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment					
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	
Area of application	Ikanes, isoalkanes, cyclics Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	Compartment Human - oral	Long term, systemic	DNEL	699	mg/kg bw/d	
Consumer	Human - dermal	effects Long term, systemic	DNEL	699	mg/kg bw/d	
		effects				
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m3	
Hydrocarbons, C9, aroma	tics					
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental compartment					
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
•	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer Workers / employees Workers / employees	Human - dermal Human - inhalation	Long term, systemic effects Long term, systemic	DNEL DNEL	25 150	mg/kg bw/day mg/m3	

œ



Page 7 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Asphalt						
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
Consumer	Human - inhalation	Long term, local effects	DNEL	0,6	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,9	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

(GB)

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection: Solvent resistant protective gloves (EN ISO 374). Recommended Protective gloves made of fluorocarbon rubber (EN ISO 374). Minimum layer thickness in mm: 0,4 Permeation time (penetration time) in minutes: 240

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: Normally not necessary. If OES or MEL is exceeded. Gas mask filter A (EN 14387), code colour brown Observe wearing time limitations for respiratory protection equipment.

Thermal hazards: Not applicable



Page 8 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

(GB)

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Melting point/freezing point: Boiling point or initial boiling point and boiling range: Flammability: Lower explosion limit: Upper explosion limit: Flash point: Auto-ignition temperature: Decomposition temperature: pH: Kinematic viscosity: Solubility: Partition coefficient n-octanol/water (log value): Vapour pressure: Density and/or relative density: Relative vapour density: Particle characteristics:

## 9.2 Other information

Explosives:

Oxidising liquids: Solvents content:

Aerosol. Active substance: liquid. Black Characteristic There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. There is no information available on this parameter. There is no information available on this parameter. Does not apply to aerosols. >200 °C There is no information available on this parameter. Mixture is non-soluble (in water). <20,5 mm2/s (40°C, Active substance ) Insoluble Does not apply to mixtures. There is no information available on this parameter. 0,828 g/ml Does not apply to aerosols. Does not apply to aerosols.

Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture. There is no information available on this parameter.

#### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

The product has not been tested.

#### **10.2 Chemical stability**

Stable with proper storage and handling.

#### **10.3 Possibility of hazardous reactions**

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Heating, open flame, ignition sources Pressure increase will result in danger of bursting. Electrostatic charge

#### **10.5 Incompatible materials**

Avoid contact with strong oxidizing agents.

#### **10.6 Hazardous decomposition products**

No decomposition when used as directed.

**SECTION 11: Toxicological information** 

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).



Safety data sheet according to R Revision date / version: 21.09.20			,			
Replacing version dated / versior	า: 01.11.2021	/ 0019				
/alid from: 21.09.2022						
PDF print date: 23.09.2022						
JNDERBODY SEAL BLACK						
500 ml Art.: 6610 0959, Art.: 661	4 0959					
JNDERBODY SEAL BLACK						
500 ml Art.: 6610 0959, Art.: 66				· • •		
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>5000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>5000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value
						Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value
			_			Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						11.0.0.
Germ cell mutagenicity:		-		+		n.d.a.
Carcinogenicity:	+					n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
epeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Solvent naphtha (petroleum), li	ight arom.					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:	2000		iiig/i/-iii	- Tut		Repeated
Skin conosion/initiation.						exposure may
						cause skin
						dryness or
						cracking.
Aspiration hazard:						Yes
Specific target organ toxicity -						Irritation of the
single exposure (STOT-SE),						respiratory tract
nhalative:						
lydrocarbons, C7-C9, n-alkane				·		<b>N</b> (
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>2800	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute	
<i>,, , </i>	-				Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,3	mg/l/4h	Rat	OECD 403 (Acute	Vapours
sette toxicity, by initiatution.					Inhalation Toxicity)	- apoulo
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
				Rabuit		Not initant
					Dermal	
<b>N N N N</b>					Irritation/Corrosion)	
Skin corrosion/irritation:						Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
,					Irritation/Corrosion)	
Respiratory or skin	1			Guinea pig	OECD 406 (Skin	Not sensitizising
sensitisation:	+				Sensitisation)	Nogotivo
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
			1	1	Chromosome	1
					Aberration Test)	



B Page 10 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Germ cell mutagenicity:		2000	mg/kg	Mouse	OECD 474 (Mammalian Erythrocyte	Negative
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
eenn een matagemety.					Reverse Mutation Test)	linguate
Reproductive toxicity:					OECD 414 (Prenatal	Negative
i ș					Developmental Toxicity	
					Study)	
Reproductive toxicity:	LOAEL	9000	ppm	Rat	OECD 416 (Two-	Negative
					generation	_
					Reproduction Toxicity	
					Study)	
Specific target organ toxicity -						STOT SE 3,
single exposure (STOT-SE):						H336
Specific target organ toxicity -					OECD 413 (Subchronic	Negative
repeated exposure (STOT-RE):					Inhalation Toxicity - 90-	
					Day Study)	
Aspiration hazard:						Yes
Symptoms:						drowsiness,
						unconsciousness
						,
						heart/circulatory
						disorders,
						headaches,
						cramps,
						drowsiness,
						mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	> 6,193	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative



B Page 11 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Germ cell mutagenicity:		OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative
Germ cell mutagenicity:	Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:			Negative
Reproductive toxicity:	Rat	OECD 421 (Reproduction/Developm ental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:		OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Reproductive toxicity:		OECD 416 (Two- generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):			STOT SE 3, H335, STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):		OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):		OECD 452 (Chronic Toxicity Studies)	Negative
Aspiration hazard:			Yes
Symptoms:			respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness , fever, ear noises, drying of the skin.

Propane Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
57 5						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	-
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Reproductive toxicity	NOAEC	21,641	mg/l		OECD 422 (Combined	
(Developmental toxicity):					Repeated Dose Tox.	
					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Aspiration hazard:						No



Page 12 of 23
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 23.09.2022
UNDERBODY SEAL BLACK
500 ml Art.: 6610 0959, Art.: 6614 0959

Symptoms:						breathing difficulties,
						unconsciousness , frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	· • · · · · · · · · · · · · · · · · · ·
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	> 94,4	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Reproductive toxicity:	NOAEL	1000	mg/kg bw/d	Rat	OECD 416 (Two- generation Reproduction Toxicity Study)	
Symptoms:						vomiting, mucous membrane irritation
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	> 2000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by oral route:	LD50	> 5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant



B Page 13 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Serious eye damage/irritation:	Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin			No (skin contact)
sensitisation:			
Germ cell mutagenicity:		in vitro	Negative
Carcinogenicity:			Negative,
			administered as
			Ca-lactate
Reproductive toxicity:			Negative,
			administered as
			Ca-carbonate

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Aspiration hazard:						No
Symptoms:						unconsciousnes , frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Aspiration hazard:						No
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	



 Page 14 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 UNDERBODY SEAL BLACK
 500 ml Art.: 6610 0959, Art.: 6614 0959

O manta ma		stavia kastkiaa
Symptoms:		ataxia, breathing
		difficulties,
		drowsiness,
		unconsciousness
		, frostbite,
		disturbed heart
		rhythm,
		headaches,
		cramps,
		intoxication,
		dizziness,
		nausea and
		vomiting.

## 11.2. Information on other hazards

UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes			
Endocrine disrupting properties:						Does not apply to mixtures.			
Other information:						No other relevant information available on adverse effects on health.			

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

UNDERBODY SEAL BLA	CK						
500 ml Art.: 6610 0959, A	rt.: 6614 0959						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							According to the
							recipe, contains
							no AOX.

Solvent naphtha (petroleum), light arom.										
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes			
12.1. Toxicity to fish:	LC50	96h	10	mg/l	Brachydanio rerio					
12.1. Toxicity to algae:	EC50	72h	10	mg/l						
12.5. Results of PBT							No PBT			
and vPvB assessment							substance, No			
							vPvB substance			
			•		·					
Libraha a a sha ha h	allianaa laaall	ana avall								

Toxicity / effect         Endpoint         Time         Value         Unit         Organism         Test method         Notes	Tyurocarbons, c7-c9, fraikanes, isoaikanes, cyclics									
	Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		



œ Page 15 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

12.7. Other adverse effects:							Product floats on the water
12.3. Bioaccumulative potential:							surface. Not to be expected(evapor
potential.							ation)
12.4. Mobility in soil:							Product is slightly volatile.
12.1. Toxicity to fish:	NOELR	28d	0,574		Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	3 - 10	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	4,6 - 10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	1 -1,6	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EL50	72h	10	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Completely biodegradable.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EL50	48h	11,14	mg/l			calculated value

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
2.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
2.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
2.2. Persistence and		28d	54-56	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	
2.2. Persistence and		28d	78	%	activated sludge	OECD 301 E	Readily
legradability:						(Ready	biodegradable
						Biodegradability -	
						Modified OECD	
				0/		Screening Test)	
2.2. Persistence and		28d	78	%		OECD 301 F	
legradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry Test)	



B Page 16 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

12.3. Bioaccumulative potential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	10min	>99	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Propane Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
	•	Time		Unit	Organishi	Test method	
12.3. Bioaccumulative	Log Pow		2,28				A notable
potential:	-						biological
							accumulation
							potential is not
							be expected
							(LogPow 1-3).
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Asphalt							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	> 1000	mg/l	Oncorhynchus mykiss	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	LL50	48h	> 1000	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to algae:	EL50	72h	> 1000	mg/l	Pseudokirchneriell a subcapitata	QSAR	Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	NOEC/NOEL	28d	>= 1000	mg/l	Oncorhynchus mykiss	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>= 1000	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.2. Persistence and degradability:							Not biodegradable

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:					Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	Negative
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Oncorhynchus mykiss		



 Page 17 of 23
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 23.09.2022
 UNDERBODY SEAL BLACK
 500 ml Art.: 6610 0959, Art.: 6614 0959

12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>200	mg/l	Desmodesmus		
					subspicatus		
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition	
					casopicatão	Test)	
12.2. Persistence and						,	Inorganic
degradability:							products cannot
							be eliminated
							from water
							through
							biological
							purification
							methods.
12.3. Bioaccumulative							Not relevant for
potential:							inorganic
							substances.
12.4. Mobility in soil:							Not relevant for
							inorganic
							substances.
12.5. Results of PBT							Not relevant for
and vPvB assessment							inorganic
							substances.

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

## For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)



Page 18 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

16 05 04 gases in pressure containers (including halons) containing hazardous substances 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances Recommendation:

Sewage disposal shall be discouraged.

(GB)

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations. Recommendation:

Do not perforate, cut up or weld uncleaned container.

#### **SECTION 14: Transport information**

General statements 14.1. UN number or ID number:	1950	
Transport by road/by rail (ADR/RID)		
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
Classification code:	5F	< <u>*</u> >
LQ:	1 L	$\sim$
14.5. Environmental hazards:	environmentally hazardous	
Tunnel restriction code:	D	
Transport by sea (IMDG-code)		
14.2. UN proper shipping name:		•
AEROSOLS (NAPHTHA (PETROLEUM))		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	¥
EmS: Marine Pollutant:	F-D, S-U Yes	
14.5. Environmental hazards:	environmentally hazardous	
	environmentally hazardous	
Transport by air (IATA)		
14.2. UN proper shipping name: Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	<b>(</b>
14.4. Packing group:	-	•
14.5. Environmental hazards:	Not applicable	
14.6. Special precautions for user		
Persons employed in transporting dangerous goods must be train	hed	
All persons involved in transporting must observe safety regulation		
Precautions must be taken to prevent damage.		
14.7. Maritime transport in bulk according to	IMO instruments	
Freighted as packaged goods rather than in bulk, therefore not a		
Minimum amount regulations have not been taken into account.	r F	
Danger code and packing code on request.		
Comply with special provisions		

Comply with special provisions.

## **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Regulation (EU) No 649/2012 'concerning the export and import of hazardous chemicals' must be adhered to, as the product contains a substance that falls within the scope of this Regulation.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):



Page 19 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
E2		200	500
P3a	11 1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the	Qualifying quantity (tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
10		19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

2

Revised sections:

(GB)

Employee training in handling dangerous goods is required. These details refer to the product as it is delivered. Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification based on test data.
Aerosol 1, H229	Classification based on test data.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3). H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects Aquatic Chronic — Hazardous to the aquatic environment - chronic Aerosol — Aerosols Flam. Liq. — Flammable liquid STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

62,4 %



Page 20 of 23

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

#### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended. Guidelines for the preparation of safety data sheets as amended (ECHA). Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA). Safety data sheets for the constituent substances. ECHA Homepage - Information about chemicals. GESTIS Substance Database (Germany). German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany). EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended National Lists of Occupational Exposure Limits for each country as amended. Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended. Förch SAS S.C. Foerch S.R.L. Foerch AG ZAE Le Marchais Renard Str. Zizinului nr.110 Muttenzerstrasse 143 CS 50125 Montereau-sur-le-Jard 500407 Brasov 4133 Pratteln 77019 Melun Cedex Rumänien Schweiz Tel. +40 368 408192 Frankreich Tel. +41 61 8262031

Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr Internet: www.forch.fr

Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg

Förch Componentes para Taller S.L. Camino de San Antón, S/N 18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es Internet: www.forch.es

Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82 E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien Tel. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr

Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711 Fax. +45 86 800617 E-Mail: info@foerch.dk Internet: www.foerch.dk

Førch Polska Sp. z.o.o Mikdzyrzecze Gorne 379 43-392 K/Bielska-Bialej Polen Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.l. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0 Fax +43 662 878677-21 Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30 E-Mail: info@foerch.at Internet: www.foerch.at

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be

Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechenland Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV **Twentepoort Oost 51** 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl



Page 21 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

(GB)

Förch, s.r.o. Dopravní 1314/1 104 00 Praha 10 – Uhøínives Tschechien Tel. +420 271 001 984-9 E-Mail: info@foerch.cz Internet: www.foerch.cz

Troscoe Ltd Unit 6, 13 Highbrook Drive East Tamaki 2013, New Zealand Tel: +64 21 081 30780 / +64 21 024 05583 Email:sales@forchnz.co.nz Internet: www.forchnz.co.nz

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3 34524 Beylikdüzü / Istanbul Türkei Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr Förch Slovensko s.r.o. Rosinská cesta 8 010 08 Žilina Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492 E-Mail: info@foerch.si Internet: www.foerch.si

Förch Portugal Lda Centro Empresarial Sintra-Estoril III Rua Pé de Mouro, Nr 33, Armazém J 2710-335 Sintra Portugal Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland Tel. +353871271473 Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114 Emergency telephone: +614 13 550 330 Email : sales@forch.com.au Internet: www.forch.com.au

Trigers SIA Straupes iela 3 1073 Riga Lettland Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv

Venus Arma d.o.o. Partner Theo Förch GmbH & Co. KG Batajnicki drum 18a 11080 Zemun Republika Srbija Tel. +381 11 407-20-91 Fax. +381 11 407-20-91 E-Mail: office@foerch.rs Internet: www.foerch.rs

#### Any abbreviations and acronyms used in this document:

according, according to acc., acc. to Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the ADR International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds approx. approximately Art., Art. no. Article number ASTM ASTM International (American Society for Testing and Materials) ATE Acute Toxicity Estimate Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BAuA **Bioconcentration factor** BCF BSEF The International Bromine Council bw body weight CAS **Chemical Abstracts Service** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances CLP and mixtures) CMR carcinogenic, mutagenic, reproductive toxic DMEL Derived Minimum Effect Level



(GB) Page 22 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959 DNEL Derived No Effect Level Dissolved organic carbon DOC dry weight dw for example (abbreviation of Latin 'exempli gratia'), for instance e.g. EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants) European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect European Economic Community EEC European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances ΕN European Norms United States Environmental Protection Agency (United States of America) FPA  $ErCx, E\mu Cx, ErLx (x = 10, 50)$ Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants) etc. et cetera EU **European Union** EVAL Ethylene-vinyl alcohol copolymer Fax number Fax. gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Adsorption coefficient of organic carbon in the soil Koc octanol-water partition coefficient Kow IARC International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code) IMDG-code International Maritime Code for Dangerous Goods including, inclusive incl. IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population LD50 Lethal Dose to 50% of a test population (Median Lethal Dose) Logarithm of adsorption coefficient of organic carbon in the soil Log Koc Logarithm of octanol-water partition coefficient Log Kow, Log Pow Limited Quantities 10 MARPOL International Convention for the Prevention of Marine Pollution from Ships not applicable n.a. n.av. not available not checked n.c. n.d.a. no data available NIOSH National Institute for Occupational Safety and Health (USA) NI P No-longer-Polymer NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development organic org. OSHA Occupational Safety and Health Administration (USA) PBT persistent, bioaccumulative and toxic PE Polyethylene PNEC Predicted No Effect Concentration parts per million ppm Polyvinylchloride PVC REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International RID Carriage of Dangerous Goods by Rail) SVHC Substances of Very High Concern Tel Telephone TOC Total organic carbon UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Volatile organic compounds VOC vPvB very persistent and very bioaccumulative wet weight wwt The statements made here should describe the product with regard to the necessary safety precautions - they are



œ Page 23 of 23 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 21.09.2022 / 0020 Replacing version dated / version: 01.11.2021 / 0019 Valid from: 21.09.2022 PDF print date: 23.09.2022 UNDERBODY SEAL BLACK 500 ml Art.: 6610 0959, Art.: 6614 0959

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 ${\ensuremath{\mathbb C}}$  by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.