

Page 1 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.01.2023 / 0030  
Replacing version dated / version: 21.09.2022 / 0029  
Valid from: 17.01.2023  
PDF print date: 17.01.2023  
Rust Off Super Rapid S410  
300 ml Art.: 6700 0026, Art.: 6704 0026

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Rust Off Super Rapid S410**  
**300 ml Art.: 6700 0026, Art.: 6704 0026**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Rust remover

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG  
Theo-Förch-Str. 11 – 15  
74196 Neuenstadt  
Tel.: 07139/95-0  
Fax: 07139/95-199  
Email: [info@foerch.de](mailto:info@foerch.de)  
Homepage: [www.foerch.com](http://www.foerch.com)

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (TFC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.  
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.  
 Distillates (petroleum), hydrotreated light naphthenic  
 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substances

n.a.

### 3.2 Mixtures

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-481-9
CAS	(64742-48-9)
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Distillates (petroleum), hydrotreated light naphthenic	
Registration number (REACH)	01-2119480375-34-XXXX
Index	649-466-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	265-156-6
CAS	64742-53-6
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

2-Butoxyethanol		Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475108-36-XXXX	
Index	603-014-00-0	
EINECS, ELINCS, NLP, REACH-IT List-No.	203-905-0	
CAS	111-76-2	
content %	1-5	

GB

Page 3 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Acute Tox. 3, H331 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
<b>Specific Concentration Limits and ATE</b>	ATE (oral): 1200 mg/kg ATE (as inhalation, Vapours): 3 mg/l

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.  
 Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."  
 Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Typically no exposure pathway.  
 Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.  
 Danger of aspiration.  
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

with long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

## SECTION 5: Firefighting measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.01.2023 / 0030  
Replacing version dated / version: 21.09.2022 / 0029  
Valid from: 17.01.2023  
PDF print date: 17.01.2023  
Rust Off Super Rapid S410  
300 ml Art.: 6700 0026, Art.: 6704 0026

## 5.1 Extinguishing media

### Suitable extinguishing media

CO<sub>2</sub>  
Extinction powder  
Water jet spray  
Alcohol resistant foam

### Unsuitable extinguishing media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Toxic gases  
Danger of bursting (explosion) when heated  
Explosive vapour/air or gas/air mixtures.

## 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

## 6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.  
Without adequate ventilation, formation of explosive mixtures may be possible.  
Active substance:  
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid inhalation of the vapours.  
Avoid contact with eyes or skin.  
Keep away from sources of ignition - Do not smoke.  
Take measures against electrostatic charging, if appropriate.  
Do not use on hot surfaces.

GB

Page 5 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Keep away from food, drink and animal feedingstuffs.  
 Do not store with flammable or self-igniting materials.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Observe special storage conditions.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 800 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
WEL-TWA: 800 mg/m <sup>3</sup>	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>		
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)		

Chemical Name	2-Butoxyethanol		
WEL-TWA: 25 ppm (123 mg/m <sup>3</sup> ) (WEL), 20 ppm (98 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 50 ppm (246 mg/m <sup>3</sup> ) (WEL, EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>		
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)		

Chemical Name	Butane		
WEL-TWA: 600 ppm (1450 mg/m <sup>3</sup> )	WEL-STEL: 750 ppm (1810 mg/m <sup>3</sup> )	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-221 SA (549 459)</li> <li>- OSHA PV2010 (n-Butane) - 1993</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name	Propane		
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-125 SA (549 954)</li> <li>- OSHA PV2077 (Propane) - 1990</li> </ul>		
BMGV: ---	Other information: ---		

Chemical Name	Isobutane		
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---	---	
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-113 SB(C) (549 368)</li> </ul>		
BMGV: ---	Other information: ---		

GB

GB

Page 6 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Chemical Name		Oil mist, mineral	
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---	
Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)			
BMGV: ---	Other information: ---		

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg	

Distillates (petroleum), hydrotreated light naphthenic						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	5,4	mg/m3	

2-Butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	
	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	

GB

Page 7 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m <sup>3</sup>	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 Recommended  
 Protective nitrile gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 >= 0,7  
 Permeation time (penetration time) in minutes:  
 >= 240  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Page 8 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Normally not necessary.  
 If OES or MEL is exceeded.  
 Filter A2 P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Grey
Odour:	Solvent
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	n.a.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	>200 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Not miscible
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	
Density and/or relative density:	0,69291 g/cm <sup>3</sup> (20°C)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

### 9.2 Other information

Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No
Evaporation rate:	n.a.
Bulk density:	n.a.
Solvents content:	85,5 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials



GB

Page 9 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### Rust Off Super Rapid S410

300 ml Art.: 6700 0026, Art.: 6704 0026

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Acute toxicity, by inhalation:	LC50	>5	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Analogous conclusion
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking., Product removes fat.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Analogous conclusion
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion

GB

Page 10 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEC	>= 5220	mg/m3	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion inhalation
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, Dermatitis (skin inflammation), Reddening, drying of the skin., mucous membrane irritation, nausea and vomiting., diarrhoea, lower abdominal pain

<b>Distillates (petroleum), hydrotreated light naphthenic</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	100				No indications of such an effect.
Aspiration hazard:						Yes

<b>2-Butoxyethanol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	ATE	3	mg/l			Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2

GB

Page 11 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

<b>Butane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

<b>Propane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		

GB

Page 12 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

Isobutane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						No
Symptoms:						unconsciousness, frostbite, headaches, cramps, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

## 11.2. Information on other hazards

Rust Off Super Rapid S410 300 ml Art.: 6700 0026, Art.: 6704 0026						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

GB

Page 13 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Distillates (petroleum), hydrotreated light naphthenic						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:	NOAEL	>2000	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Rust Off Super Rapid S410 300 ml Art.: 6700 0026, Art.: 6704 0026							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexing organic substance) $\geq$ 80%/28d: n.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,10	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

Page 14 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.7. Other adverse effects:							Product floats on the water surface.
Water solubility:			~10	mg/l			Slight

**Distillates (petroleum), hydrotreated light naphthenic**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	14d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.3. Bioaccumulative potential:	BCF		<500				Low
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	10	%			Not readily biodegradable
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable.
12.3. Bioaccumulative potential:	Log Pow		6,0				A notable biological accumulation potential has to be expected (LogPow > 3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:							Insoluble

**2-Butoxyethanol**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn- Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,00000 16	atm*m3/m ol			
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

**Butane**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Propane**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**Isobutane**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			

GB

Page 16 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

12.2. Persistence and degradability:							Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 14 06 03 other solvents and solvent mixtures  
 16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 Take full aerosol cans to problem waste collection.  
 Take emptied aerosol cans to valuable material collection.


#### For contaminated packing material

Pay attention to local and national official regulations.  
 Recommendation:  
 Do not perforate, cut up or weld uncleaned container.  
 Recycling  
 15 01 04 metallic packaging


## SECTION 14: Transport information

### General statements


#### Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:	UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	
Transport category:	2	

#### Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:	UN 1950 AEROSOLS	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	

#### Transport by air (IATA)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:	UN 1950 Aerosols, flammable	
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	

### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.



GB

Page 17 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Precautions must be taken to prevent damage.

### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Regulation (EC) No 1907/2006, Annex XVII  
 2-Butoxyethanol

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

85,5 %

### REGULATION (EC) No 648/2004

30 % and more  
 aliphatic hydrocarbons

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

3, 11, 12, 15

Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

**Classification in accordance with regulation (EC) No. 1272/2008 (CLP)**

**Evaluation method used**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 17.01.2023 / 0030  
 Replacing version dated / version: 21.09.2022 / 0029  
 Valid from: 17.01.2023  
 PDF print date: 17.01.2023  
 Rust Off Super Rapid S410  
 300 ml Art.: 6700 0026, Art.: 6704 0026

Asp. Tox. 1, H304	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard  
 Aerosol — Aerosols  
 Acute Tox. — Acute toxicity - inhalation  
 Acute Tox. — Acute toxicity - oral  
 Skin Irrit. — Skin irritation  
 Eye Irrit. — Eye irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
 Guidelines for the preparation of safety data sheets as amended (ECHA).  
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
 Safety data sheets for the constituent substances.  
 ECHA Homepage - Information about chemicals.  
 GESTIS Substance Database (Germany).  
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
 National Lists of Occupational Exposure Limits for each country as amended.  
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS  
 ZAE Le Marchais Renard  
 CS 50125 Montereau-sur-le-Jard  
 77019 Melun Cedex  
 Frankreich  
 Tel. +33 1 64 14 48 48  
 Fax. +33 1 64 14 48 49  
 E-Mail: info@forch.fr  
 Internet: www.forch.fr

FÖRCH S.R.L.  
 STR. ECOLOGISTILOR 43  
 RO - 505600 SACELE, JUD.BRASOV  
 Rumänien  
 Tel. +40 368 408192  
 Fax. +40 368 408193  
 E-Mail: info@foerch.ro  
 Internet: www.foerch.ro

Foerch AG  
 Muttenerstrasse 143  
 4133 Pratteln  
 Schweiz  
 Tel. +41 61 8262031  
 Fax. +41 61 8262039  
 E-Mail: info@foerch.ch  
 Internet: www.foerch.ch

Foerch Bulgaria EOOD  
 475 Botevgradsko Shose Blvd.  
 BG 1517 Sofia, Bulgaria  
 Tel. 00359 2 981 2841  
 Fax. 00359 982 10 30 86  
 E-Mail: info@foerch.bg

Förch d.o.o.  
 Buzinska cesta 58  
 10010 Zagreb  
 Kroatien  
 Tel. +385 1 2912900  
 Fax. +385 1 2912901  
 E-Mail: info@foerch.hr  
 internet: www.foerch.hr

Theo Förch GmbH  
 Röcklbrunnstraße 39A  
 5020 Salzburg  
 Österreich  
 Tel. +43 662 875574-0  
 Fax +43 662 878677-21  
 Verkauf Tel. +43 662 875574-900  
 Verkauf Fax +43 662 875574-30  
 E-Mail: info@foerch.at  
 Internet: www.foerch.at

Förch Componentes para Taller S.L.  
 Camino de San Antón, S/N  
 18102 Ambroz (Granada)  
 Spanien  
 Tel. +34 958 40 17 76  
 Fax. +34 958 40 17 87  
 E-Mail: info@forch.es  
 Internet: www.forch.es

Förch A/S  
 Hagemannsvej 3  
 8600 Silkeborg  
 Dänemark  
 Tel. +45 86 823711  
 Fax. +45 86 800617  
 E-Mail: info@foerch.dk  
 Internet: www.foerch.dk

Lhomme Tools & Fasteners BV  
 Seinhuisstraat 5 B4  
 Poort 0331  
 3600 Genk  
 Belgien  
 Tel. +32 89 71 66 61  
 E-Mail: info@lhommetools.be  
 Internet: www.lhommetools.be

Page 19 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.01.2023 / 0030  
Replacing version dated / version: 21.09.2022 / 0029  
Valid from: 17.01.2023  
PDF print date: 17.01.2023  
Rust Off Super Rapid S410  
300 ml Art.: 6700 0026, Art.: 6704 0026

Ziebe Limited  
7 Century Court, Westcott,  
Aylesbury, Bucks, HP18 0XP (UK)  
Grossbritannien  
Tel +44 12 96 65 52 82  
E-Mail: sales@ziebe.co.uk  
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.  
Mikdyrzecze Górne 379  
43-392 K/Bielska-Bialej  
Polen  
Tel. +48 338196000  
Fax. +48 338158548  
E-Mail: info@forch.pl  
Internet: www.forch.pl

Vardalis SM P.C.  
Ethnikis Antistasis 62  
57007 Chalkidona-Thessaloniki  
Griechenland  
Tel. +30 23910 21222  
Fax. +30 23910 21223  
E-Mail: info@forch.gr  
Internet: www.forch.gr

Förch Kereskedelmi Kft  
Börgöndi út 14  
8000 Székesfehérvár  
Ungarn  
Tel. +36 22 348348  
Fax. +36 22 348355  
E-Mail: info@foerch.hu  
Internet: www.foerch.hu

Förch S.r.l.  
Via Antonio Stradivari 4  
39100 Bolzano (BZ)  
Italien  
Tel: +39 0471 204330  
Fax: +39 0471 204290  
E-Mail: info@forch.it  
Internet: www.forch.it

Förch Nederland BV  
Twentepoort Oost 51  
7609 RG Almelo  
Niederlande  
Tel. +31 85 77 32 420  
E-Mail: info@foerch.nl  
Internet: www.foerch.nl

AB varahlutir ehf  
Funahöfði 9  
110 Reykjavík  
Tel. +354 567 6020  
E-mail: ab@ab.is  
Internet: www.ab.is

Förch Slovensko s.r.o.  
Rosinská cesta 8  
010 08 Žilina  
Slowakei  
Tel +421 41 5002454  
E-Mail: info@forch.sk  
Internet: www.forch.sk

Förch Sverige AB  
Brännarevägen 1  
151 55 Södertälje  
Schweden  
Tel. +46 855089264  
E-mail: info@foerch.se  
Internet: www.foerch.se

Förch, s.r.o.  
Dopravní 1314/1  
104 00 Praha 10 – Uhřetíněves  
Tschechien  
Tel. +420 271 001 984-9  
E-Mail: info@foerch.cz  
Internet: www.foerch.cz

FORCH d.o.o.  
Ljubljanska cesta 51A  
1236 Trzin  
Slowenien  
Tel. +386 1 2442490  
Fax. +386 1 2442492  
E-Mail: info@foerch.si  
Internet: www.foerch.si

Forch Australia  
2 Forward Street  
Gnangara WA 6077  
Tel. +61 (08) 9303 9113  
Fax. +61 (08) 9303 9114  
Emergency telephone: +614 13 550 330  
Email : sales@forch.com.au  
Internet: www.forch.com.au

Troscoe Ltd  
Unit 6, 13 Highbrook Drive  
East Tamaki 2013, New Zealand  
Tel: +64 21 081 30780 / +64 21 024 05583  
Email:sales@forchnz.co.nz  
Internet: www.forchnz.co.nz

Förch Portugal Lda  
Centro Empresarial Sintra-Estoril III  
Rua Pé de Mouro, Nr 33, Armazém J  
2710-335 Sintra  
Portugal  
Tel. +351 917314442  
E-Mail: info@forch.pt  
Internet: www.forch.pt

Trigers SIA  
Straupes iela 3  
1073 Rīga  
Lettland  
Tel. +371 6 7 90 25 15  
Fax. +371 67 90 24 96  
E-Mail: trigers@trigers.lv  
Internet: www.trigers.lv

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti.  
Haramidere Mevkii Beysan Sanayi  
Sitesi Birlik Caddesi No:6/3  
34524 Beylikdüzü / Istanbul  
Türkei  
Tel. +90 (0)212 422 8744-45  
Fax. +90 (0)212 422 8788  
E-Mail: info@forch.com.tr  
Internet: www.forch.com.tr

Total Consumables Ltd  
Coolnafearagh  
Monasterevin  
Co. Kildare  
W34 TX29  
Irland  
Tel. +353871271473

Venus Arma d.o.o.  
Partner Theo Förch GmbH & Co. KG  
Batajnicksi drum 18a  
11080 Zemun  
Republika Srbija  
Tel. +381 11 407-20-91  
Fax. +381 11 407-20-91  
E-Mail: office@foerch.rs  
Internet: www.foerch.rs

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute for Occupational Safety and Health (USA)  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 OSHA Occupational Safety and Health Administration (USA)  
 PBT persistent, bioaccumulative and toxic

Page 21 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 17.01.2023 / 0030  
Replacing version dated / version: 21.09.2022 / 0029  
Valid from: 17.01.2023  
PDF print date: 17.01.2023  
Rust Off Super Rapid S410  
300 ml Art.: 6700 0026, Art.: 6704 0026

PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
TOC Total organic carbon  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.