

Page 1 of 23  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0028  
Replacing version dated / version: 22.02.2019 / 0027  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Battery Terminal Spray Red  
150 ml Art.: 6710 0870, Art.: 6714 0870

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Battery Terminal Spray Red**  
**150 ml Art.: 6710 0870, Art.: 6714 0870**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Corrosion protection

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG  
Theo-Förch-Str. 11 – 15  
74196 Neuenstadt  
Tel.: 07139/95-0  
Fax: 07139/95-199  
Email: [info@foerch.de](mailto:info@foerch.de)  
Homepage: [www.foerch.com](http://www.foerch.com)

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (TFC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure (central nervous system).
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

## 2.2 Label elements

### Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H373-May cause damage to organs through prolonged or repeated exposure (central nervous system). H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P260-Do not breathe vapours or spray. P273-Avoid release to the environment.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.

EUH208-Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

Without adequate ventilation, formation of explosive mixtures may be possible.

Naphtha (petroleum), hydrodesulphurized heavy  
 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane  
 Hydrocarbons, C6, isoalkanes, <5% n-hexane  
 Pentane

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

Aerosol

### 3.1 Substances

n.a.

### 3.2 Mixtures

Pentane	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	601-006-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-692-4
CAS	109-66-0
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	
Registration number (REACH)	---
Index	---

Page 3 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	926-605-8
<b>CAS</b>	---
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

<b>Naphtha (petroleum), hydrodesulphurized heavy</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	649-330-00-2
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-185-4
<b>CAS</b>	64742-82-1
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 (central nervous system) Asp. Tox. 1, H304 Aquatic Chronic 2, H411

<b>Hydrocarbons, C6, isoalkanes, &lt;5% n-hexane</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	931-254-9
<b>CAS</b>	(64742-49-0)
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

<b>Naphtha (petroleum), hydrotreated heavy</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	649-327-00-6
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	265-150-3
<b>CAS</b>	64742-48-9
<b>content %</b>	1-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304

<b>Sulfonic acids, petroleum, calcium salts</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP, REACH-IT List-No.</b>	263-093-9
<b>CAS</b>	61789-86-4
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP), M-factors</b>	Skin Sens. 1B, H317
<b>Specific Concentration Limits and ATE</b>	Skin Sens. 1B, H317: >=10 %

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

## SECTION 4: First aid measures

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0028  
Replacing version dated / version: 22.02.2019 / 0027  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Battery Terminal Spray Red  
150 ml Art.: 6710 0870, Art.: 6714 0870

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

##### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

##### Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

##### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

##### Ingestion

Usual protective working garments  
Consult doctor immediately - keep Data Sheet available.  
Do not induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes  
Product removes fat.  
Dermatitis (skin inflammation)  
Dizziness  
Fatigue  
Ingestion:  
Danger of aspiration.  
Oedema of the lungs  
Lung damage

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

**Suitable extinguishing media**  
Water jet spray/foam/CO2/dry extinguisher

**Unsuitable extinguishing media**

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Toxic gases  
Danger of bursting (explosion) when heated  
Explosive vapour/air or gas/air mixtures.

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.

Page 5 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Leave the danger zone if possible, use existing emergency plans if necessary.  
 Remove possible causes of ignition - do not smoke.  
 Ensure sufficient supply of air.  
 Avoid inhalation, and contact with eyes or skin.

### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take measures against electrostatic charging, if appropriate.  
 Do not use on hot surfaces.  
 Avoid contact with eyes or skin.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Observe special regulations for aerosols!  
 Observe special storage conditions.  
 Do not store with flammable or self-igniting materials.  
 Keep protected from direct sunlight and temperatures over 50°C.  
 Store in a well ventilated place.  
 Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 600 mg/m<sup>3</sup>

(GB)	Chemical Name	Pentane	Content %:10- <20
	WEL-TWA: 1800 mg/m <sup>3</sup> (600 ppm) (WEL), 3000 mg/m <sup>3</sup> (1000 ppm) (EU)	WEL-STEL: ---	---
	Monitoring procedures:	- Draeger - Pentane 100/a (67 24 701) - Compur - KITA-113 SB(C) (549 368)	

Page 6 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

	DFG (D) (Lösungsmittelgemische Meth. Nr. 1), DFG (E) (Solvent mixtures 1) - 1998, - 2002 - NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996
BMGV: ---	Other information: ---

Chemical Name	Pentane	Content %:10- <20
OELV-8h: 1000 ppm (3000 mg/m3) (OELV-8h, EU)	OELV-15min: ---	---
Monitoring procedures:	- Draeger - Pentane 100/a (67 24 701) - Compur - KITA-113 SB(C) (549 368) - DFG (D) (Lösungsmittelgemische Meth. Nr. 1), DFG (E) (Solvent mixtures 1) - 1998, - 2002 - NIOSH 1500 (HYDROCARBONS, BP 36°-216 °C) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996	
BLV: ---	Other information: IOELV	

Chemical Name	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Content %:1-<10
WEL-TWA: 350 mg/m3 (cyclohexane)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: ---	

Chemical Name	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Content %:1-<10
OELV-8h: 100 ppm (573 mg/m3) ("Stoddard solvent", [White spirit])	OELV-15min: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BLV: ---	Other information: ---	

Chemical Name	Naphtha (petroleum), hydrodesulphurized heavy	Content %:1-<10
WEL-TWA: 600 mg/m3	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Naphtha (petroleum), hydrodesulphurized heavy	Content %:1-<10
OELV-8h: 100 ppm (573 mg/m3) ("Stoddard solvent", [White spirit])	OELV-15min: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BLV: ---	Other information: ---	

Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane	Content %:1-<10
WEL-TWA: 800 mg/m3	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Hydrocarbons, C6, isoalkanes, <5% n-hexane	Content %:1-<10
OELV-8h: 100 ppm (573 mg/m3) ("Stoddard solvent", [White spirit])	OELV-15min: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	
BLV: ---	Other information: ---	

Chemical Name	Naphtha (petroleum), hydrotreated heavy	Content %:1-<10
WEL-TWA: 1200 mg/m3 (>=C7 normal and branched chain alkanes)	WEL-STEL: ---	---
Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)	

Page 7 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

BMGV: ---	Other information: ---
-----------	------------------------

(IRL) <b>Chemical Name</b>	Naphtha (petroleum), hydrotreated heavy	Content %:1-<10
----------------------------	---	-----------------

OELV-8h: 100 ppm (573 mg/m3) ("Stoddard solvent", [White spirit])	OELV-15min: ---	---
---	-----------------	-----

Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571)
	- Draeger - Hydrocarbons 2/a (81 03 581)
	- Compur - KITA-187 S (551 174)

BLV: ---	Other information: ---
----------	------------------------

(GB) <b>Chemical Name</b>	Propane	Content %:
---------------------------	---------	------------

WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---	---
---------------------------	---------------	-----

Monitoring procedures:	- Compur - KITA-125 SA (549 954)
	- OSHA PV2077 (Propane) - 1990

BMGV: ---	Other information: ---
-----------	------------------------

(GB) <b>Chemical Name</b>	Paraffin wax, fume	Content %:
---------------------------	--------------------	------------

WEL-TWA: 2 mg/m3	WEL-STEL: 6 mg/m3	---
------------------	-------------------	-----

Monitoring procedures:	---
------------------------	-----

BMGV: ---	Other information: ---
-----------	------------------------

(IRL) <b>Chemical Name</b>	Paraffin wax, fume	Content %:
----------------------------	--------------------	------------

OELV-8h: 2 mg/m3	OELV-15min: 6 mg/m3	---
------------------	---------------------	-----

Monitoring procedures:	---
------------------------	-----

BLV: ---	Other information: ---
----------	------------------------

(GB) <b>Chemical Name</b>	Butane	Content %:
---------------------------	--------	------------

WEL-TWA: 600 ppm (1450 mg/m3)	WEL-STEL: 750 ppm (1810 mg/m3)	---
-------------------------------	--------------------------------	-----

Monitoring procedures:	- Compur - KITA-221 SA (549 459)
	- OSHA PV2010 (n-Butane) - 1993

BMGV: ---	Other information: ---
-----------	------------------------

(IRL) <b>Chemical Name</b>	Butane	Content %:
----------------------------	--------	------------

OELV-8h: ---	OELV-15min: 1000 ppm	---
--------------	----------------------	-----

Monitoring procedures:	- Compur - KITA-221 SA (549 459)
	- OSHA PV2010 (n-Butane) - 1993

BLV: ---	Other information: ---
----------	------------------------

Pentane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - water, sporadic (intermittent) release		PNEC	880	µg/l	
	Environment - freshwater		PNEC	230	µg/l	
	Environment - marine		PNEC	230	µg/l	
	Environment - sewage treatment plant		PNEC	3600	µg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg dw	
	Environment - sediment, marine		PNEC	1,2	mg/kg dw	
	Environment - soil		PNEC	0,55	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	214	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	214	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	643	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	3000	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	432	mg/kg bw/d	

<b>Hydrocarbons, C6-C7, isoalkanes, cyclics, &lt;5% n-hexane</b>
--



Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/kg	

Hydrocarbons, C6, isoalkanes, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	1301	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1377	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1131	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13964	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5306	mg/m3	

Naphtha (petroleum), hydrotreated heavy						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

(IRL) OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |



Page 9 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021

PDF print date: 01.11.2021

Battery Terminal Spray Red

150 ml Art.: 6710 0870, Art.: 6714 0870

OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |

BLV = Biological limit value |

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of splashes.

Skin protection - Hand protection:

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Protective PVC gloves (EN ISO 374).

Minimum layer thickness in mm:

0,6

Protective gloves made of polyvinyl alcohol (EN ISO 374).

Protective Viton® / fluoroelastomer gloves (EN ISO 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

>= 480 min

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

Page 10 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Aerosol. Active substance: liquid.
Colour:	Beige
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Does not apply to aerosols.
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	Does not apply to aerosols.
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Insoluble
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	2,6-3,2 bar (20°C)
Vapour pressure:	5,1-5,9 bar (50°C)
Density and/or relative density:	~0,64 g/ml
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.

### 9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidising liquids:	No

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources

Electrostatic charge

Pressure increase will result in danger of bursting.

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

**Battery Terminal Spray Red**  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.

Page 11 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

<b>Pentane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	5000	mg/kg	Mouse		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>100	mg/l/4h	Rat		
Skin corrosion/irritation:						Mild irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Mild irritant
Respiratory or skin sensitisation:						Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, vomiting, cramps, drowsiness, mucous membrane irritation

<b>Hydrocarbons, C6-C7, isoalkanes, cyclics, &lt;5% n-hexane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours, Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Drying of the skin.
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:					OECD 451 (Carcinogenicity Studies)	Negative

Page 12 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Yes
Aspiration hazard:						Yes
Symptoms:						respiratory distress, drying of the skin., drowsiness, annoyance, heart/circulatory disorders, coughing, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.

**Naphtha (petroleum), hydrodesulphurized heavy**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3400	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Repeated exposure may cause skin dryness or cracking.
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising, Analogous conclusion
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion

**Hydrocarbons, C6, isoalkanes, <5% n-hexane**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>16750	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3350	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	259354	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Skin Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Aspiration hazard:						Asp. Tox. 1

Page 13 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Naphtha (petroleum), hydrotreated heavy						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness

Sulfonic acids, petroleum, calcium salts						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No

Page 14 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

<b>Butane</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	

## 11.2. Information on other hazards

<b>Battery Terminal Spray Red</b> 150 ml Art.: 6710 0870, Art.: 6714 0870						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.



Page 15 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Other information:							No other relevant information available on adverse effects on health.
--------------------	--	--	--	--	--	--	---

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Battery Terminal Spray Red 150 ml Art.: 6710 0870, Art.: 6714 0870							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.

Pentane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	9,87	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	9,99	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	9,74	mg/l	Daphnia magna		
12.2. Persistence and degradability:		8d	70	%			
12.3. Bioaccumulative potential:	Log Pow		3,39				calculated value

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	12	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EL50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	30	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	



Page 17 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Sulfonic acids, petroleum, calcium salts							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Cyprinodon variegatus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	8,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

#### For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

Return to manufacturer with residual pressure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

## SECTION 14: Transport information

### General statements

14.1. UN number or ID number: 1950

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:  
 UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D



### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 AEROSOLS (PENTANES, HYDROCARBONS, C6)

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous



### Transport by air (IATA)

14.2. UN proper shipping name:  
 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

### 14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Page 19 of 23  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0028  
 Replacing version dated / version: 22.02.2019 / 0027  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Battery Terminal Spray Red  
 150 ml Art.: 6710 0870, Art.: 6714 0870

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 91,78 %  
**REGULATION (EC) No 648/2004**  
 n.a.

Observe incident regulations.

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 1-16  
 Employee training in handling dangerous goods is required.  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT RE 2, H373	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H317 May cause an allergic skin reaction.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

STOT RE — Specific target organ toxicity - repeated exposure  
 Asp. Tox. — Aspiration hazard  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Aerosol — Aerosols  
 Flam. Liq. — Flammable liquid  
 Skin Irrit. — Skin irritation  
 Skin Sens. — Skin sensitization

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0028  
Replacing version dated / version: 22.02.2019 / 0027  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Battery Terminal Spray Red  
150 ml Art.: 6710 0870, Art.: 6714 0870

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS  
ZAE Le Marchais Renard  
CS 50125 Montereau-sur-le-Jard  
77019 Melun Cedex  
Frankreich  
Tel. +33 1 64 14 48 48  
Fax. +33 1 64 14 48 49  
E-Mail: [info@forch.fr](mailto:info@forch.fr)  
Internet: [www.forch.fr](http://www.forch.fr)

Förch SAS  
17 rue de Marbourg  
9764 MARNACH  
Luxemburg  
Tel. +352 269 03267  
Fax +352 269 03368  
E-Mail: [info@forch.fr](mailto:info@forch.fr)  
Internet: [www.forch.fr](http://www.forch.fr)

S.C. Foerch S.R.L.  
Str. Zizinului nr.110  
500407 Brasov  
Rumänien  
Tel. +40 368 408192  
Fax. +40 368 408193  
E-Mail: [info@foerch.ro](mailto:info@foerch.ro)  
Internet: [www.foerch.ro](http://www.foerch.ro)

Foerch AG  
Muttenerstrasse 143  
4133 Pratteln  
Schweiz  
Tel. +41 61 8262031  
Fax. +41 61 8262039  
E-Mail: [info@foerch.ch](mailto:info@foerch.ch)  
Internet: [www.foerch.ch](http://www.foerch.ch)

Foerch Bulgaria EOOD  
475 Botevgradsko Shose Blvd.  
BG 1517 Sofia, Bulgaria  
Tel. 00359 2 981 2841  
Fax. 00359 982 10 30 86  
E-Mail: [info@foerch.bg](mailto:info@foerch.bg)

Förch d.o.o.  
Buzinska cesta 58  
10010 Zagreb  
Kroatien  
Tel. +385 1 2912900  
Fax. +385 1 2912901  
E-Mail: [info@foerch.hr](mailto:info@foerch.hr)  
internet: [www.foerch.hr](http://www.foerch.hr)

Theo Förch GmbH  
Röcklbrunnstraße 39A  
5020 Salzburg  
Österreich  
Tel. +43 662 875574-0  
Fax +43 662 878677-21  
Verkauf Tel. +43 662 875574-900  
Verkauf Fax +43 662 875574-30  
E-Mail: [info@foerch.at](mailto:info@foerch.at)  
Internet: [www.foerch.at](http://www.foerch.at)

Förch Componentes para Taller S.L.  
Camino de San Antón, S/N  
18102 Ambroz (Granada)  
Spanien  
Tel. +34 958 40 17 76  
Fax. +34 958 40 17 87  
E-Mail: [info@forch.es](mailto:info@forch.es)  
Internet: [www.forch.es](http://www.forch.es)

Förch A/S  
Hagemannsvej 3  
8600 Silkeborg  
Dänemark  
Tel. +45 86 823711  
Fax. +45 86 800617  
E-Mail: [info@foerch.dk](mailto:info@foerch.dk)  
Internet: [www.foerch.dk](http://www.foerch.dk)

Lhomme Tools & Fasteners BV  
Seinhuisstraat 5 B4  
Poort 0331  
3600 Genk  
Belgien  
Tel. +32 89 71 66 61  
E-Mail: [info@lhommetools.be](mailto:info@lhommetools.be)  
Internet: [www.lhommetools.be](http://www.lhommetools.be)

Ziebe Limited  
7 Century Court, Westcott,  
Aylesbury, Bucks, HP18 0XP (UK)  
Grossbritannien  
Tel +44 12 96 65 52 82  
E-Mail: [sales@ziebe.co.uk](mailto:sales@ziebe.co.uk)  
Internet: [www.ziebe.co.uk](http://www.ziebe.co.uk)

SKY NORD  
Sofia Kovalevskaya ul.  
D.1, ST.2, K.1  
RUS 127247 MOSCOW  
Russland  
E-Mail: [skynord.office@gmail.com](mailto:skynord.office@gmail.com)

Förch Polska Sp. z o.o  
Międzyrzecz Górze 379  
43-392 K/Bielska-Bialej  
Polen  
Tel. +48 338196000  
Fax. +48 338158548  
E-Mail: [info@forch.pl](mailto:info@forch.pl)  
Internet: [www.forch.pl](http://www.forch.pl)

Vardalis SM P.C.  
Ethnikis Antistasis 62  
57007 Chalkidona-Thessaloniki  
Griechenland  
Tel. +30 23910 21222  
Fax. +30 23910 21223  
E-Mail: [info@forch.gr](mailto:info@forch.gr)  
Internet: [www.forch.gr](http://www.forch.gr)

Förch Kereskedelmi Kft  
Börgöndi út 14  
8000 Székesfehérvár  
Ungarn  
Tel. +36 22 348348  
Fax. +36 22 348355  
E-Mail: [info@foerch.hu](mailto:info@foerch.hu)  
Internet: [www.foerch.hu](http://www.foerch.hu)



Förch S.r.l.  
Via Antonio Stradivari 4  
39100 Bolzano (BZ)  
Italien  
Tel: +39 0471 204330  
Fax: +39 0471 204290  
E-Mail: [info@forch.it](mailto:info@forch.it)  
Internet: [www.forch.it](http://www.forch.it)

Förch Nederland BV  
Twentepoort Oost 51  
7609 RG Almelo  
Niederlande  
Tel. +31 85 77 32 420  
E-Mail: [info@foerch.nl](mailto:info@foerch.nl)  
Internet: [www.foerch.nl](http://www.foerch.nl)

AB varahlutir ehf  
Funahöfði 9  
110 Reykjavík  
Tel. +354 567 6020  
E-mail: [ab@ab.is](mailto:ab@ab.is)  
Internet: [www.ab.is](http://www.ab.is)

Förch Slovensko s.r.o.  
Rosinská cesta 12  
010 08 Žilina  
Slowakei  
Tel +421 41 5002454  
E-Mail: [info@forch.sk](mailto:info@forch.sk)  
Internet: [www.forch.sk](http://www.forch.sk)

Förch Sverige AB  
Brännarevägen 1  
151 55 Södertälje  
Schweden  
Tel. +46 855089264  
E-mail: [info@foerch.se](mailto:info@foerch.se)  
Internet: [www.foerch.se](http://www.foerch.se)

Förch, s.r.o.  
Dopravní 1314/1  
104 00 Praha 10 – Uhřetěves  
Tschechien  
Tel. +420 271 001 984-9  
E-Mail: [info@foerch.cz](mailto:info@foerch.cz)  
Internet: [www.foerch.cz](http://www.foerch.cz)

FORCH d.o.o.  
Ljubljanska cesta 51A  
1236 Trzin  
Slowenien  
Tel. +386 1 2442490  
Fax. +386 1 2442492  
E-Mail: [info@foerch.si](mailto:info@foerch.si)  
Internet: [www.foerch.si](http://www.foerch.si)

Forch Australia  
2 Forward Street  
Gnangara WA 6077  
Tel. +61 (08) 9303 9113  
Fax. +61 (08) 9303 9114  
Emergency telephone: +614 13 550 330  
Email : [sales@forch.com.au](mailto:sales@forch.com.au)  
Internet: [www.forch.com.au](http://www.forch.com.au)

Troscoe Ltd  
Unit 6, 13 Highbrook Drive  
East Tamaki 2013, New Zealand  
Tel: +64 21 081 30780 / +64 21 024 05583  
Email:[sales@forchnz.co.nz](mailto:sales@forchnz.co.nz)  
Internet: [www.forchnz.co.nz](http://www.forchnz.co.nz)

Förch Portugal Lda  
Rua República da Bolívia No. 69, 1 esq  
1500-544 Lisboa  
Portugal  
Tel. +351 917314442  
E-Mail: [info@forch.pt](mailto:info@forch.pt)  
Internet: [www.forch.pt](http://www.forch.pt)

Trigers SIA  
Straupes iela 3  
1073 Rīga  
Lettland  
Tel. +371 6 7 90 25 15  
Fax. +371 67 90 24 96  
E-Mail: [trigers@trigers.lv](mailto:trigers@trigers.lv)  
Internet: [www.trigers.lv](http://www.trigers.lv)

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Sti.  
Haramidere Mevkii Beysan Sanayi  
Sitesi Birlik Caddesi No:6/3  
34524 Beylikdüzü / İstanbul  
Türkei  
Tel. +90 (0)212 422 8744-45  
Fax. +90 (0)212 422 8788  
E-Mail: [info@forch.com.tr](mailto:info@forch.com.tr)  
Internet: [www.forch.com.tr](http://www.forch.com.tr)

Total Consumables Ltd  
Coolnafearagh  
Monasterevin  
Co. Kildare  
W34 TX29  
Irland  
Tel. +353871271473

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

Page 22 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021

PDF print date: 01.11.2021

Battery Terminal Spray Red

150 ml Art.: 6710 0870, Art.: 6714 0870

BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EBLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute for Occupational Safety and Health (USA)  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 OSHA Occupational Safety and Health Administration (USA)  
 PBT persistent, bioaccumulative and toxic  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 ppm parts per million  
 PVC Polyvinylchloride  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SVHC Substances of Very High Concern

Page 23 of 23

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0028

Replacing version dated / version: 22.02.2019 / 0027

Valid from: 01.11.2021

PDF print date: 01.11.2021

Battery Terminal Spray Red

150 ml Art.: 6710 0870, Art.: 6714 0870

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.