

Œ

Page 1 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG Theo-Förch-Str. 11 – 15 74196 Neuenstadt Tel.: 07139/95-0

Tel.: 07139/95-0 Fax: 07139/95-199 Email: info@foerch.de Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).



Page 2 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 **Drilling and Cutting Paste**

500 g Art.: 6580 5820, Art.: 6584 5820

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Reaction mass of 4-tert-butylphenyl diphenyl phosphate and bis(4-tert-butylphenyl) phenyl phosphate and triphenyl phosphate	
Registration number (REACH)	01-2119519251-50-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	700-990-0
CAS	
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product. For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP, REACH-	Registration number (REACH)	Chemical name
IT List-No.		
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Ingestion:

Gastrointestinal disturbances



Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

 $\label{eq:prevent} \mbox{Prevent surface and ground-water infiltration, as well as ground penetration.}$

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.



· (B)

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Store cool.

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Paraffin wax, fume				Content %:
WEL-TWA: 2 mg/m3		WEL-STEL:	6 mg/m3		
Monitoring procedures:					
BMGV:				Other information: -	
@ OL : IN	1 1 (1) 3				0 + + 0/ -
© Chemical Name	general dust limit				Content %:
WEL-TWA: 10 mg/m3 (inhal. dus	t), 4 mg/m3 (respir.	WEL-STEL:			
dust)					
Monitoring procedures:	-				
BMGV:				Other information: -	
© Chemical Name	Paraffin waxes				Content %:
WEL-TWA: 2 mg/m3 (paraffin wa	x, fume)	WEL-STEL:	6 mg/m3 (paraffin	wax, fume)	
Monitoring procedures:	- (Compur - KITA-	187 S (551 174)		
BMGV:		-		Other information: -	 -

Baseoil - unspecified									
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note			
	Environment - oral (animal feed)		PNEC	9,33	mg/kg				
Consumer	Human - inhalation	Long term, local effects	DNEL	1,2	mg/m3				
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg				
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1	mg/kg				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,6	mg/m3				
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,7	mg/m3				

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU), 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).



(B)

Page 5 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Solid
Colour: Brown
Odour: Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

There is no information available on this parameter.

Flammability: Flammable



Page 6 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

pH:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density:

Relative vapour density:

9.2 Other information

Explosives:

Oxidizing solids:

·

Solvents content:

Does not apply to solids. Does not apply to solids.

>150 °C

No

There is no information available on this parameter.

Mixture is non-soluble (in water).

Does not apply to solids.

Insoluble

Does not apply to mixtures.

n.a.

There is no information available on this parameter.

Does not apply to solids.

Product is not explosive. When using: development of explosive

Test method

Notes

n.d.a.

vapour/air mixture possible.

There is no information available on this parameter.

0,21 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

500 g Art.: 6580 5820, Art.: 6584 5820

Specific target organ toxicity -

repeated exposure (STOT-RE):

single exposure (STOT-SE):
Specific target organ toxicity -

Aspiration hazard:

Symptoms:

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification). **Drilling and Cutting Paste**

Toxicity / effect Endpoint Value Unit Organism

Acute toxicity, by oral route:
Acute toxicity, by dermal route:
Acute toxicity, by inhalation:
Skin corrosion/irritation:
Serious eye damage/irritation:
Respiratory or skin sensitisation:
Germ cell mutagenicity:
Carcinogenicity:
Reproductive toxicity:

	Baseoil - unspecified						
l	Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



(B)

Page 7 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Respiratory or skin sensitisation:			Not sensitizising, Analogous conclusion
Aspiration hazard:			Yes
Symptoms:			mucous membrane irritation

11.2. Information on other hazards

Drilling and Cutting Paste										
500 g Ārt.: 6580 5820, Art.: 6584 5820										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Endocrine disrupting properties:						Does not apply				
						to mixtures.				
Other information:						No other				
						relevant				
						information				
						available on				
						adverse effects				
						on health.				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Drilling and Cutting Paste 500 g Art.: 6580 5820, Art.: 6584 5820 Unit Toxicity / effect Endpoint Time Value Organism Test method Notes 12.1. Toxicity to fish: n.d.a. 12.1. Toxicity to daphnia: n.d.a. 12.1. Toxicity to algae: n.d.a. 12.2. Persistence and n.d.a. degradability: 12.3. Bioaccumulative n.d.a. potential: 12.4. Mobility in soil: n.d.a. 12.5. Results of PBT n.d.a. and vPvB assessment 12.6. Endocrine Does not apply disrupting properties: to mixtures. 12.7. Other adverse No information effects: available on other adverse effects on the environment. Other information: Does not contain any organically bound halogens which can contribute to the AOX value in waste water. Other information: DOC-elimination degree(complexi ng organic substance)>= 80%/28d: n.a.

Baseoil - unspecified									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales				
					promelas				
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna				
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna				



Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

12 01 12 spent waxes and fats

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: n.a. **Transport by road/by rail (ADR/RID)**14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LO:n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Marine Pollutant:n.a.

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



Page 9 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0,21 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS ZAE Le Marchais Renard CS 50125 Montereau-sur-le-Jard 77019 Melun Cedex

Frankreich Tel. +33 1 64 14 48 48 Fax. +33 1 64 14 48 49 E-Mail: info@forch.fr

Internet: www.forch.fr

Foerch AG Muttenzerstrasse 143 4133 Pratteln

Schweiz

Tel. +41 61 8262031 Fax. +41 61 8262039 E-Mail: info@foerch.ch Internet: www.foerch.ch Förch SAS 17 rue de Marbourg 9764 MARNACH Luxemburg Tel. +352 269 03267

Fax +352 269 03267 Fax +352 269 03368 E-Mail: info@forch.fr Internet: www.forch.fr

Foerch Bulgaria EOOD 475 Botevgradsko Shose Blvd. BG 1517 Sofia, Bulgaria Tel. 00359 2 981 2841 Fax. 00359 982 10 30 86 E-Mail: info@foerch.bg S.C. Foerch S.R.L. Str. Zizinului nr.110 500407 Brasov Rumänien

Tel. +40 368 408192 Fax. +40 368 408193 E-Mail: info@foerch.ro Internet: www.foerch.ro

Förch d.o.o. Buzinska cesta 58 10010 Zagreb Kroatien

Tel. +385 1 2912900 Fax. +385 1 2912901 E-Mail: info@foerch.hr internet: www.foerch.hr



Page 10 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Theo Förch GmbH Röcklbrunnstraße 39A 5020 Salzburg Österreich Tel. +43 662 875574-0 Fax +43 662 878677-21

Verkauf Tel. +43 662 875574-900 Verkauf Fax +43 662 875574-30

E-Mail: info@foerch.at Internet: www.foerch.at

Lhomme Tools & Fasteners BV Seinhuisstraat 5 B4 Poort 0331 3600 Genk Belgien

Tel. +32 89 71 66 61 E-Mail: info@lhommetools.be Internet: www.lhommetools.be

Förch Polska Sp. z.o.o Międzyrzecze Górne 379 43-392 K/Bielska-Bialej

Polen

Tel. +48 338196000 Fax. +48 338158548 E-Mail: info@forch.pl Internet: www.forch.pl

Förch S.r.I. Via Antonio Stradivari 4 39100 Bolzano (BZ) Italien

Tel: +39 0471 204330 Fax: +39 0471 204290 E-Mail: info@forch.it Internet: www.forch.it

Förch Slovensko s.r.o. Rosinská cesta 12 010 08 Žilina Slowakei Tel +421 41 5002454 E-Mail: info@forch.sk

Internet: www.forch.sk

FORCH d.o.o. Ljubljanska cesta 51A 1236 Trzin Slowenien Tel. +386 1 2442490 Fax. +386 1 2442492

E-Mail: info@foerch.si Internet: www.foerch.si Förch Componentes para Taller S.L. Camino de San Antón, S/N

18102 Ambroz (Granada) Spanien Tel. +34 958 40 17 76 Fax. +34 958 40 17 87 E-Mail: info@forch.es

Internet: www.forch.es

Ziebe Limited 7 Century Court, Westcott, Aylesbury, Bucks, HP18 0XP (UK) Grossbritannien Tel +44 12 96 65 52 82 E-Mail: sales@ziebe.co.uk Internet: www.ziebe.co.uk

Vardalis SM P.C. Ethnikis Antistasis 62 57007 Chalkidona-Thessaloniki Griechenland Tel. +30 23910 21222 Fax. +30 23910 21223 E-Mail: info@forch.gr Internet: www.forch.gr

Förch Nederland BV Twentepoort Oost 51 7609 RG Almelo Niederlande Tel. +31 85 77 32 420 E-Mail: info@foerch.nl Internet: www.foerch.nl

Förch Sverige AB Brännarevägen 1 151 55 Södertälje Schweden Tel. +46 855089264 E-mail: info@foerch.se Internet: www.foerch.se

Forch Australia 2 Forward Street Gnangara WA 6077 Tel. +61 (08) 9303 9113 Fax. +61 (08) 9303 9114

Emergency telephone: +614 13 550 330

Email: sales@forch.com.au Internet: www.forch.com.au

Förch A/S Hagemannsvej 3 8600 Silkeborg Dänemark Tel. +45 86 823711 Fax. +45 86 800617

E-Mail: info@foerch.dk Internet: www.foerch.dk

SKY NORD Sofia Kovalevskaya ul. D.1, ST.2, K.1 RUS 127247 MOSCOW Russland

E-Mail: skynord.office@gmail.com

Förch Kereskedelmi Kft Börgöndi út 14 8000 Székesfehérvár Ungarn Tel. +36 22 348348 Fax. +36 22 348355

Fax. +36 22 348355 E-Mail: info@foerch.hu Internet: www.foerch.hu

AB varahlutir ehf Funahöfði 9 110 Reykjavík Tel. +354 567 6020 E-mail: ab@ab.is Internet: www.ab.is

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhříněves
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

Troscoe Ltd
Unit 6, 13 Highbrook Drive
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email:sales@forchnz.co.nz
Internet: www.forchnz.co.nz



Page 11 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

Förch Portugal Lda

Rua República da Bolivia No. 69, 1 esq

1500-544 Lisboa

Portugal

Tel. +351 917314442 E-Mail: info@forch.pt Internet: www.forch.pt Trigers SIA Straupes iela 3 1073 Riga Lettland

Tel. +371 6 7 90 25 15 Fax. +371 67 90 24 96 E-Mail: trigers@trigers.lv Internet: www.trigers.lv Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti. Haramidere Mevkii Beysan Sanayi Sitesi Birlik Caddesi No:6/3

Türkei

Tel. +90 (0)212 422 8744-45 Fax. +90 (0)212 422 8788 E-Mail: info@forch.com.tr Internet: www.forch.com.tr

34524 Beylikdüzü / Istanbul

Total Consumables Ltd Coolnafearagh Monasterevin Co. Kildare W34 TX29 Irland

Tel. +353871271473

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community
ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient



Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0007

Replacing version dated / version: 27.04.2021 / 0006

Valid from: 01.11.2021 PDF print date: 01.11.2021 Drilling and Cutting Paste

500 g Art.: 6580 5820, Art.: 6584 5820

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.