

Page 1 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Filler

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	3	H226-Flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
STOT RE	1	H372-Causes damage to organs through prolonged or repeated exposure.
Repr.	2	H361d-Suspected of damaging the unborn child.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.10.2022 / 0024

Replacing version dated / version: 31.05.2022 / 0023

Valid from: 05.10.2022

PDF print date: 05.10.2022

Multi System Filler L270

2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)


Danger

H226-Flammable liquid and vapour. H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H372-Causes damage to organs through prolonged or repeated exposure. H361d-Suspected of damaging the unborn child.

P201-Obtain special instructions before use. P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260-Do not breathe vapours. P280-Wear protective gloves / protective clothing and eye protection / face protection. P308+P313-If exposed or concerned: Get medical advice / attention.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Styrene

Maleic anhydride

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Styrene	
Registration number (REACH)	01-2119457861-32-XXXX
Index	601-026-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	202-851-5
CAS	100-42-5
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT SE 3, H335 STOT RE 1, H372 (organs of hearing) Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	---
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

Page 3 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Maleic anhydride	
Registration number (REACH)	01-2119472428-31-XXXX
Index	607-096-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	203-571-6
CAS	108-31-6
content %	0,001-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Sens. 1A, H317: >=0,001 %

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air. Call doctor immediately.
 Respiratory arrest - Artificial respiration apparatus necessary.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove mechanically.
 Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Do not induce vomiting.
 Consult doctor immediately - keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
 Dry extinguisher
 Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
 Oxides of carbon
 Fume
 Toxic gases
 Explosive vapour/air or gas/air mixtures.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.10.2022 / 0024

Replacing version dated / version: 31.05.2022 / 0023

Valid from: 05.10.2022

PDF print date: 05.10.2022

Multi System Filler L270

2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Or:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Only use explosion-proof equipment.

Use only explosion-protected tools.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

Pregnant women should avoid contact with this product.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep locked away.

Keep out of access to unauthorised individuals.

Observe special storage conditions.

Store product closed and only in original packing.

GB

Page 5 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Not to be stored in gangways or stair wells.
 Protect against moisture and store closed.
 Protect from direct sunlight and warming.
 Store cool.
 Do not store over 30°C.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB	Chemical Name	Styrene
	WEL-TWA: 430 mg/m ³ (100 ppm)	WEL-STEL: 1080 mg/m ³ (250 ppm) ---
	Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Styrene 10/a (67 23 301) - Draeger - Styrene 10/b (67 33 141) - Draeger - Styrene 50/a (CH 27 601) - Compur - KITA-158 S (550 218) - Compur - KITA-158 SB (549 278) - DFG Meth. Nr. 3 (D) (Styrol), DFG Method No. 3 (E) (Styrene) - 1994, 2002 - DFG Meth. Nr. 4 (D) (Styrol) - 1994 - NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 1014 (Styrene (Diffusive Samplers)) - 2009 - OSHA 89 (Divinylbenzene Ethylvinylbenzene Styrene) - 1991
	BMGV: ---	Other information: ---
GB	Chemical Name	Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)
	WEL-TWA: 10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust)	WEL-STEL: --- ---
	Monitoring procedures:	---
	BMGV: ---	Other information: ---
GB	Chemical Name	Maleic anhydride
	WEL-TWA: 1 mg/m ³	WEL-STEL: 3 mg/m ³ ---
	Monitoring procedures:	---
	BMGV: ---	Other information: Sen
GB	Chemical Name	Silicon dioxide
	WEL-TWA: 6 mg/m ³ (total inh. dust), 2,4 mg/m ³ (resp. dust)	WEL-STEL: --- ---
	Monitoring procedures:	---
	BMGV: ---	Other information: ---
GB	Chemical Name	Talc
	WEL-TWA: 1 mg/m ³ (res. dust)	WEL-STEL: --- ---
	Monitoring procedures:	---
	BMGV: ---	Other information: ---
GB	Chemical Name	Barium sulphate
	WEL-TWA: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust)	WEL-STEL: --- ---
	Monitoring procedures:	---
	BMGV: ---	Other information: ---

Styrene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,028	mg/l	
	Environment - marine		PNEC	0,014	mg/l	
	Environment - sediment, freshwater		PNEC	0,614	mg/kg dry weight	

	Environment - sediment, marine		PNEC	0,307	mg/kg dry weight	
	Environment - sporadic (intermittent) release		PNEC	0,04	mg/l	
	Environment - soil		PNEC	0,2	mg/kg dry weight	
	Environment - sewage treatment plant		PNEC	5	mg/l	
	Environment - periodic release		PNEC	0,04	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10,2	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174,25	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	182,75	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	406	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	85	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	306	mg/m3	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Maleic anhydride						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,04281	mg/l	
	Environment - marine		PNEC	0,004281	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,4281	mg/l	
	Environment - sediment, freshwater		PNEC	0,334	mg/kg	

Page 7 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

	Environment - sediment, marine		PNEC	0,0334	mg/kg	
	Environment - soil		PNEC	0,0415	mg/kg	
	Environment - sewage treatment plant		PNEC	44,6	mg/l	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,4	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,8	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,4	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,8	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,04	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,04	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	0,04	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, local effects	DNEL	0,04	mg/kg bw/d	

Silicon dioxide

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - oral (animal feed)		PNEC	60000	mg/kg feed	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

Barium sulphate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,115	mg/l	
	Environment - sediment, freshwater		PNEC	600,4	mg/kg dw	
	Environment - sewage treatment plant		PNEC	62,2	mg/l	
	Environment - soil		PNEC	207,7	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	13000	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

Page 8 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective gloves made of fluorocarbon rubber (EN ISO 374).
 Minimum layer thickness in mm:
 0,4
 Permeation time (penetration time) in minutes:
 >= 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 If OES or MEL is exceeded.
 Filter A P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Pastelike, Liquid
Colour:	Beige
Odour:	Characteristic
Melting point/freezing point:	-30 °C (Styrene)
Boiling point or initial boiling point and boiling range:	145 °C
Flammability:	Flammable
Lower explosion limit:	1,1 Vol-% (Styrene)
Upper explosion limit:	6,1 Vol-% (Styrene)
Flash point:	31 °C (DIN 53213 (Pensky-Martens, closed cup))
Auto-ignition temperature:	490 °C (Styrene)
Decomposition temperature:	There is no information available on this parameter.

Page 9 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

pH: Mixture is non-soluble (in water).
 Kinematic viscosity: >20,5 mm²/s (40°C)
 Solubility: 0,32 g/l (25°C, Styrene)
 Partition coefficient n-octanol/water (log value): Does not apply to mixtures.
 Vapour pressure: 6,67 hPa (20°C, Styrene)
 Density and/or relative density: ~1,8 g/ml (20°C)
 Relative vapour density: There is no information available on this parameter.
 Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.
 Oxidising liquids: No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.
 Heating, open flame, ignition sources
 Protect from humidity.

10.5 Incompatible materials

See also section 7.
 Avoid contact with oxidizing agents.
 Exothermic reaction possible with:
 Peroxides
 Radical former (Initiators)

10.6 Hazardous decomposition products

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Multi System Filler L270

2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Styrene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	5000	mg/kg	Rat		

Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	11,8	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit		Skin Irrit. 2
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative(6h)
Germ cell mutagenicity:				Mouse	OECD 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells In Vivo)	Negative
Carcinogenicity:	NOAEC	>=0,00434	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negativeinhalation
Reproductive toxicity (Developmental toxicity):	LOAEL	1,28	mg/l	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Positiveinhalation
6-15d						
Reproductive toxicity (Developmental toxicity):	NOAEC	1,08-2,15	mg/l	Rat		Positiveinhalation
> 50d						
Reproductive toxicity (Effects on fertility):	NOAEL	100-200	mg/kg bw/d	Rat		Positiveinhalation
60 d						
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,8	mg/l	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	
Symptoms:						drowsiness, headaches, fatigue, muscle weakness, mucous membrane irritation, dizziness, nausea and vomiting., mental confusion
Specific target organ toxicity - single exposure (STOT-SE), inhalative:				Mammalian		STOT SE 3, H335
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d			Positive
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	0,688-3,47	mg/l	Rat		Positive28d

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant

Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitizing
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		90d
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		90d

Maleic anhydride						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1090	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	2620	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4,35	mg/l/4h	Mouse		
Skin corrosion/irritation:				Human being		Corrosive
Skin corrosion/irritation:				Rat		Corrosive
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Sensitising (skin contact)
Respiratory or skin sensitisation:				Rat		Sensitising (inhalation)
Germ cell mutagenicity:					bacterial	References, Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Rat	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>100	mg/kg bw/d	Rat		oral

Page 12 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Reproductive toxicity:	NOAEC	650	mg/kg bw/d	Rat		
Reproductive toxicity:	NOAEL	55	mg/kg	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Symptoms:						asthmatic symptoms, breathing difficulties, respiratory distress, burning of the membranes of the nose and throat, blisters, coughing, headaches, gastrointestinal disturbances, mucous membrane irritation, watering eyes, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	10	mg/kg/d	Rat	OECD 452 (Chronic Toxicity Studies)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	3,3	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours

Silicon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		References
Acute toxicity, by inhalation:	LC50	>0,139	mg/l/4h	Rat		References, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Germ cell mutagenicity:						Negative
Carcinogenicity:						No indications of such an effect.
Reproductive toxicity (Developmental toxicity):						No indications of such an effect.
Symptoms:						eyes, reddened

Talc						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Not irritant

Page 13 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						mucous membrane irritation

Barium sulphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	
Acute toxicity, by dermal route:	LD50	>2000		Rat		Analogous conclusion
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:						Negative

11.2. Information on other hazards

Multi System Filler L270 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Multi System Filler L270 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.

Page 14 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexing organic substance) >= 80%/28d: n.a.

Styrene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,02-10	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	4,7	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	1,01	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	LC50	96h	9,5	mg/l			Hyalella azteca, EPA OTS 797.1300
12.1. Toxicity to algae:	EC10	96h	0,28	mg/l	Pseudokirchneriella subcapitata		EPA OTS 797.1050
12.1. Toxicity to algae:	EC50	72h	4,9	mg/l	Pseudokirchneriella subcapitata		EPA OTS 797.1050
12.2. Persistence and degradability:	ThOD		70,9	%	activated sludge	ISO 9408	Readily biodegradable
12.2. Persistence and degradability:		20d	87	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	References, Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,96			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	A notable biological accumulation potential is not to be expected (LogPow 1-3).25°C
12.3. Bioaccumulative potential:	BCF		13,49-74				Low
12.4. Mobility in soil:	Koc		352				
12.4. Mobility in soil:	Log Koc		2,55				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	30min	500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to annelids:	NOEC/NOEL	14d	34	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	

12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble 20°C

Maleic anhydride							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	75	mg/l	Oncorhynchus mykiss		EPA-660/3-75-009
12.1. Toxicity to fish:	LC50	96h	75	mg/l	Lepomis macrochirus		EPA-660/3-75-009
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	42,81	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	74,32	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC10	72h	11,8	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	29	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC10	72h	23	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		7d	98	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Hydrolysis
12.3. Bioaccumulative potential:	Log Pow		-2,61 - (-2,16)				Not to be expected
12.4. Mobility in soil:	Koc		1				Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	18h	44,6	mg/l	Pseudomonas putida	IUCLID Chem. Data Sheet (ESIS)	References
Other information:	Log Pow		1,62				

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 16 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	24h	>10000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>10000	mg/l		OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Abiotically degradable.
12.3. Bioaccumulative potential:							Not to be expected
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Talc							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:			<0,1	%			
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Barium sulphate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>3,5	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	33d	>1,26	mg/l	Brachydanio rerio	OECD 210 (Fish, Early-Life Stage Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	2,9	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	14,5	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.1. Toxicity to algae:	NOEC/NOEL	72h	>1,15	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:							Not relevant for inorganic substances., Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							n.a.

Page 17 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

07 02 08 other still bottoms and reaction residues

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 3269

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3269 POLYESTER RESIN KIT

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Classification code:

F3

LQ:

5 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

POLYESTER RESIN KIT

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

EmS:

F-E, S-D

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Polyester resin kit

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.



SECTION 15: Regulatory information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 15,3 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8

Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
STOT RE 1, H372	Classification according to calculation procedure.
Repr. 2, H361d	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H361d Suspected of damaging the unborn child.
H226 Flammable liquid and vapour.
H351 Suspected of causing cancer by inhalation.
H372 Causes damage to organs through prolonged or repeated exposure by inhalation.
H317 May cause an allergic skin reaction.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Page 19 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

EUH071 Corrosive to the respiratory tract.

Flam. Liq. — Flammable liquid
Eye Irrit. — Eye irritation
Skin Irrit. — Skin irritation
Skin Sens. — Skin sensitization
STOT RE — Specific target organ toxicity - repeated exposure
Repr. — Reproductive toxicity
Acute Tox. — Acute toxicity - inhalation
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Asp. Tox. — Aspiration hazard
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Carc. — Carcinogenicity
Acute Tox. — Acute toxicity - oral
Skin Corr. — Skin corrosion
Eye Dam. — Serious eye damage
Resp. Sens. — Respiratory sensitization

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
ZAE Le Marchais Renard
CS 50125 Montereau-sur-le-Jard
77019 Melun Cedex
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului nr.110
500407 Brasov
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 8262031
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Page 20 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 05.10.2022 / 0024
 Replacing version dated / version: 31.05.2022 / 0023
 Valid from: 05.10.2022
 PDF print date: 05.10.2022
 Multi System Filler L270
 2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Ziebe Limited
 7 Century Court, Westcott,
 Aylesbury, Bucks, HP18 0XP (UK)
 Grossbritannien
 Tel +44 12 96 65 52 82
 E-Mail: sales@ziebe.co.uk
 Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.
 Międzyrzecze Górne 379
 43-392 K/Bielska-Białej
 Polen
 Tel. +48 338196000
 Fax. +48 338158548
 E-Mail: info@forch.pl
 Internet: www.forch.pl

Vardalis SM P.C.
 Ethnikis Antistasis 62
 57007 Chalkidona-Thessaloniki
 Griechenland
 Tel. +30 23910 21222
 Fax. +30 23910 21223
 E-Mail: info@forch.gr
 Internet: www.forch.gr

Förch Kereskedelmi Kft
 Börgöndi út 14
 8000 Székesfehérvár
 Ungarn
 Tel. +36 22 348348
 Fax. +36 22 348355
 E-Mail: info@foerch.hu
 Internet: www.foerch.hu

Förch S.r.l.
 Via Antonio Stradivari 4
 39100 Bolzano (BZ)
 Italien
 Tel: +39 0471 204330
 Fax: +39 0471 204290
 E-Mail: info@forch.it
 Internet: www.forch.it

Förch Nederland BV
 Twentepoort Oost 51
 7609 RG Almelo
 Niederlande
 Tel. +31 85 77 32 420
 E-Mail: info@foerch.nl
 Internet: www.foerch.nl

AB varahlutir ehf
 Funahöfði 9
 110 Reykjavík
 Tel. +354 567 6020
 E-mail: ab@ab.is
 Internet: www.ab.is

Förch Slovensko s.r.o.
 Rosinská cesta 8
 010 08 Žilina
 Slowakei
 Tel +421 41 5002454
 E-Mail: info@forch.sk
 Internet: www.forch.sk

Förch Sverige AB
 Brännarevägen 1
 151 55 Södertälje
 Schweden
 Tel. +46 855089264
 E-mail: info@foerch.se
 Internet: www.foerch.se

Förch, s.r.o.
 Dopravní 1314/1
 104 00 Praha 10 – Uhřetín
 Tschechien
 Tel. +420 271 001 984-9
 E-Mail: info@foerch.cz
 Internet: www.foerch.cz

FORCH d.o.o.
 Ljubljanska cesta 51A
 1236 Trzin
 Slowenien
 Tel. +386 1 2442490
 Fax. +386 1 2442492
 E-Mail: info@foerch.si
 Internet: www.foerch.si

Forch Australia
 2 Forward Street
 Gungahlin WA 6077
 Tel. +61 (08) 9303 9113
 Fax. +61 (08) 9303 9114
 Emergency telephone: +614 13 550 330
 Email : sales@forch.com.au
 Internet: www.forch.com.au

Troscoe Ltd
 Unit 6, 13 Highbrook Drive
 East Tamaki 2013, New Zealand
 Tel: +64 21 081 30780 / +64 21 024 05583
 Email:sales@forchnz.co.nz
 Internet: www.forchnz.co.nz

Förch Portugal Lda
 Centro Empresarial Sintra-Estoril III
 Rua Pé de Mouro, Nr 33, Armazém J
 2710-335 Sintra
 Portugal
 Tel. +351 917314442
 E-Mail: info@forch.pt
 Internet: www.forch.pt

Trigers SIA
 Straupes iela 3
 1073 Riga
 Lettland
 Tel. +371 6 7 90 25 15
 Fax. +371 67 90 24 96
 E-Mail: triggers@triggers.lv
 Internet: www.triggers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.
 Haramidere Mevkii Beysan Sanayi
 Sitesi Birlik Caddesi No:6/3
 34524 Beylikdüzü / İstanbul
 Türkei
 Tel. +90 (0)212 422 8744-45
 Fax. +90 (0)212 422 8788
 E-Mail: info@forch.com.tr
 Internet: www.forch.com.tr

Total Consumables Ltd
 Coolnafearagh
 Monasterevin
 Co. Kildare
 W34 TX29
 Irland
 Tel. +353871271473

Venus Arma d.o.o.
 Partner Theo Förch GmbH & Co. KG
 Batajnicki drum 18a
 11080 Zemun
 Republika Srbija
 Tel. +381 11 407-20-91
 Fax. +381 11 407-20-91
 E-Mail: office@foerch.rs
 Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

Page 22 of 39

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 05.10.2022 / 0024

Replacing version dated / version: 31.05.2022 / 0023

Valid from: 05.10.2022

PDF print date: 05.10.2022

Multi System Filler L270

2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Page 23 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 05.10.2022 / 0024
Replacing version dated / version: 31.05.2022 / 0023
Valid from: 05.10.2022
PDF print date: 05.10.2022
Multi System Filler L270
2000 g Art.: 6260 2705 (A), Art.: 6264 2705 (A)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Multi System Filler L270
2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Hardener

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Acute	1	H400-Very toxic to aquatic life.
Org. Perox.	Type E	H242-Heating may cause a fire.
Aquatic Chronic	1	H410-Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0014

Replacing version dated / version: 23.03.2021 / 0013

Valid from: 01.11.2021

PDF print date: 01.11.2021

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)



Warning

H319-Causes serious eye irritation. H317-May cause an allergic skin reaction. H242-Heating may cause a fire. H410-Very toxic to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P234-Keep only in original packaging.

P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing and eye protection / face protection.

P314-Get medical advice / attention if you feel unwell.

P403-Store in a well-ventilated place. P411-Store at temperatures not exceeding 30 °C.

Dibenzoyl peroxide

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Can have a fire-promoting (oxidizing) effect due to oxygen release.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Dibenzoyl peroxide	
Registration number (REACH)	01-2119511472-50-XXXX
Index	617-008-00-0
EINECS, ELINCS, NLP, REACH-IT List-No.	202-327-6
CAS	94-36-0
content %	40-60
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Org. Perox. Type B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Ethanediol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119456816-28-XXXX
Index	603-027-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	203-473-3
CAS	107-21-1
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 STOT RE 2, H373

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

Page 25 of 39
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0014
Replacing version dated / version: 23.03.2021 / 0013
Valid from: 01.11.2021
PDF print date: 01.11.2021
Multi System Filler L270
2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.
Keep Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Extinction powder
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0014
Replacing version dated / version: 23.03.2021 / 0013
Valid from: 01.11.2021
PDF print date: 01.11.2021
Multi System Filler L270
2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Use no flammable substances.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Take precautions against electrostatic charges.
Avoid inhalation, and contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Carefully avoid contamination of the product with foreign substances.
Keep away from dirt, rust, alkalis, acids and accelerators.
Do not pour remainders back into the storage vessels.
Once product has been withdrawn it must under no circumstances be poured back into the vessel.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities



Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.
Do not store with highly flammable, flammable, or self-igniting materials.
Store upright.
Observe regulations for keeping separated.
Observe the special regulations for organic peroxides.
Protect against moisture and store closed.
Only store at temperatures from 5°C to 25°C.
Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	Chemical Name	Dibenzoyl peroxide		
WEL-TWA: 5 mg/m3		WEL-STEL: ---	---	
Monitoring procedures:		---		
BMGV: ---		Other information: ---		
	Chemical Name	Ethanediol		
WEL-TWA: 10 mg/m3 (particulate), 52 mg/m3 (vapour) (WEL), 20 ppm (52 mg/m3) (EU)		WEL-STEL: 104 mg/m3 (vapour) (WEL), 40 ppm (104 mg/m3) (EU)	---	
Monitoring procedures:		- Draeger - Ethylene Glycol 10 (5) (81 01 351)		

GB

Page 27 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0014
 Replacing version dated / version: 23.03.2021 / 0013
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Multi System Filler L270
 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

- Compur - KITA-232 SA (502 342)
- Compur - KITA-232 SB (550 267)
- NIOSH 5500 (ETHYLENE GLYCOL) - 1993
- NIOSH 5523 (GLYCOLS) - 1996
- OSHA PV2024 (Ethylene glycol) - 1999 - EU project BC/CEN/ENTR/000/2002-16 card 11-2 (2004)
- Draeger - Alcohol 100/a (CH 29 701)

BMGV: ---

Other information: Sk (particulate, vapour)

Chemical Name Dimethyl phthalate

WEL-TWA: 5 mg/m3

WEL-STEL: 10 mg/m3

Monitoring procedures: ---

BMGV: ---

Other information: ---

Dibenzoyl peroxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,00002	mg/l	
	Environment - marine		PNEC	0,000002	mg/l	
	Environment - sediment, freshwater		PNEC	0,013	mg/kg dw	
	Environment - sediment, marine		PNEC	0,001	mg/kg dw	
	Environment - sewage treatment plant		PNEC	0,35	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,000602	mg/l	
	Environment - soil		PNEC	0,0025	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	13,3	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	39	mg/m3	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,034	mg/cm2	

Ethanediol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	10	mg/l	
	Environment - marine		PNEC	1	mg/l	
	Environment - sporadic (intermittent) release		PNEC	10	mg/l	
	Environment - sewage treatment plant		PNEC	199,5	mg/l	
	Environment - sediment, freshwater		PNEC	37	mg/kg dw	
	Environment - soil		PNEC	1,53	mg/kg	
	Environment - sediment, marine		PNEC	3,7	mg/kg dw	
Industrial	Human - inhalation	Long term, local effects	DNEL	35	mg/m3	
Industrial	Human - dermal	Long term, systemic effects	DNEL	106	mg/kg bw/d	
Consumer	Human - inhalation	Long term, local effects	DNEL	7	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	53	mg/m3	

Dimethyl phthalate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,192	mg/l	
	Environment - marine		PNEC	0,0192	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,39	mg/l	
	Environment - sewage treatment plant		PNEC	4	mg/l	
	Environment - sediment, freshwater		PNEC	1,403	mg/kg	
	Environment - soil		PNEC	3,16	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	60	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	86,96	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	25	mg/kg	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	100	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	293,86	mg/m3	

(98) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).

(11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,14

Page 29 of 39

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0014

Replacing version dated / version: 23.03.2021 / 0013

Valid from: 01.11.2021

PDF print date: 01.11.2021

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Permeation time (penetration time) in minutes:

>= 30

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Paste, Solid, Thixotrope
Colour:	Red
Odour:	Slightly
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	Flammable
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	>50 °C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	50 °C (SADT)
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to solids.
Solubility:	Insoluble 20°C
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	1,15-1,25 g/cm3 (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	There is no information available on this parameter.

9.2 Other information

Explosives:	There is no information available on this parameter.
Oxidizing solids:	There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

Can have a fire-promoting (oxidizing) effect due to oxygen release.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Page 30 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0014
 Replacing version dated / version: 23.03.2021 / 0013
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Multi System Filler L270
 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Contact with incompatible substances can result in decomposition at or below the SADT (Self-Accelerating Decomposition Temperature).

10.4 Conditions to avoid

See also section 7.
 Protect from humidity.
 Heating, open flame, ignition sources
 Decomposition:
 SADT = 50°C

10.5 Incompatible materials

See also section 7.
 Avoid contact with other chemicals.
 Avoid contact with strong acids.
 Avoid contact with strong alkalis.
 Accelerators
 Heavy metal salts
 Rust
 Amines
 Iron
 Copper
 Reducing agent

10.6 Hazardous decomposition products

See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Dibenzoyl peroxide

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	>24,3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Yes (skin contact)
Germ cell mutagenicity:						Negative
Carcinogenicity:	NOAEL	1000	mg/kg			Negative29d

Symptoms:						cornea opacity, mucous membrane irritation
-----------	--	--	--	--	--	---

Ethanediol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	7712	mg/kg	Rat	IUCLID Chem. Data Sheet (ESIS)	Does not conform with EU classification.
Acute toxicity, by dermal route:	LD50	9530	mg/kg	Rabbit		
Acute toxicity, by dermal route:	LD50	>3500	mg/kg	Mouse		
Acute toxicity, by inhalation:	LC50	>2,5	mg/l/6h	Rat		
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Human being	(Patch-Test)	Negative
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Rat		Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg	Rat		
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	150	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	~2200	mg/kg/d	Dog	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	
Symptoms:						ataxia, breathing difficulties, unconsciousness, cramps, fatigue

Dimethyl phthalate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	6800	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>10000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	9300	mg/m3			6,5 h
Skin corrosion/irritation:						Slightly irritant
Serious eye damage/irritation:						Slightly irritant
Symptoms:						abdominal pain, burning of the membranes of the nose and throat, diarrhoea, coughing, itching, salivation, watering eyes, nausea and vomiting.

11.2. Information on other hazards

Multi System Filler L270 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.

Page 32 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0014
 Replacing version dated / version: 23.03.2021 / 0013
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Multi System Filler L270
 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Other information:						No other relevant information available on adverse effects on health.
--------------------	--	--	--	--	--	---

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Multi System Filler L270 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:							According to the recipe, contains no AOX.
Other information:							DOC-elimination degree (complexing organic substance) >= 80%/28d: n.a.

Dibenzoyl peroxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,0602	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	96h	0,0316	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	0,11	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>0,001	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	0,0711	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	0,02	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	68-71	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable

12.3. Bioaccumulative potential:	BCF		66,6			OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	Log Pow		3,2			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	22 °C
12.4. Mobility in soil:	Log Koc		3,8			OECD 121 (Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using HPLC)	
Toxicity to bacteria:	EC50	30min	35	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Ethanediol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.4. Mobility in soil:	Log Koc		0				calculated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Pimephales promelas	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to fish:	LC50	96h	40761	mg/l	Oncorhynchus mykiss		References
12.1. Toxicity to daphnia:	EC50	48h	41100	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	7d	8590	mg/l	Ceriodaphnia spec.		
12.1. Toxicity to algae:	EC50	96h	6500-7500	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	IC5	7d	> 10000	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	90-100	%	activated sludge	OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	56	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.3. Bioaccumulative potential:	Log Pow		-1,36				Not to be expected
Toxicity to bacteria:	EC20	30min	>10000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	BOD5		0,78	g/g			IUCLID
Other information:	COD		1,19	g/g			IUCLID
Other information:	ThOD		1,29	g/g			IUCLID

Dimethyl phthalate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

Page 34 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0014
 Replacing version dated / version: 23.03.2021 / 0013
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Multi System Filler L270
 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

12.1. Toxicity to fish:	NOEC/NOEL	>60d	11	mg/l	Oncorhynchus mykiss	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL		9,6	mg/l	Daphnia magna		
12.1. Toxicity to fish:	LC50	96h	>100- <200	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	56	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	330	mg/l			
12.1. Toxicity to algae:	EC50	72h	204	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:			>70	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		5,4				
Toxicity to bacteria:	EC50	17h	>3000	mg/l	Pseudomonas putida		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:
 The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 E.g. dispose at suitable refuse site.
 E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 3108

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 3108 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

Classification code: P1

LQ: 500 g

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code: D

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

EmS: F-J, S-R

Marine Pollutant: Yes



Page 35 of 39
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 01.11.2021 / 0014
 Replacing version dated / version: 23.03.2021 / 0013
 Valid from: 01.11.2021
 PDF print date: 01.11.2021
 Multi System Filler L270
 2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:
 Organic peroxide type E, solid (DIBENZOYL PEROXIDE)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E1		100	200
P6b		50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 0 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1-16
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Acute 1, H400	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0014
Replacing version dated / version: 23.03.2021 / 0013
Valid from: 01.11.2021
PDF print date: 01.11.2021
Multi System Filler L270
2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Org. Perox. Type E, H242	Classification based on test data.
Aquatic Chronic 1, H410	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H241 Heating may cause a fire or explosion.
H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation
Skin Sens. — Skin sensitization
Aquatic Acute — Hazardous to the aquatic environment - acute
Org. Perox. — Organic peroxide
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Acute Tox. — Acute toxicity - oral
STOT RE — Specific target organ toxicity - repeated exposure

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EC) No 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
ZAE Le Marchais Renard
CS 50125 Montereau-sur-le-Jard
77019 Melun Cedex
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

S.C. Foerch S.R.L.
Str. Zizinului nr.110
500407 Brasov
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 8262031
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
475 Botevgradsko Shose Blvd.
BG 1517 Sofia, Bulgaria
Tel. 00359 2 981 2841
Fax. 00359 982 10 30 86
E-Mail: info@foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Page 37 of 39

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0014

Replacing version dated / version: 23.03.2021 / 0013

Valid from: 01.11.2021

PDF print date: 01.11.2021

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Förch Componentes para Taller S.L.
Camino de San Antón, S/N
18102 Ambroz (Granada)
Spanien
Tel. +34 958 40 17 76
Fax. +34 958 40 17 87
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
Seinhuisstraat 5 B4
Poort 0331
3600 Genk
Belgien
Tel. +32 89 71 66 61
E-Mail: info@lhommetools.be
Internet: www.lhommetools.be

Ziebe Limited
7 Century Court, Westcott,
Aylesbury, Bucks, HP18 0XP (UK)
Grossbritannien
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.
Mikdyrzecze Górne 379
43-392 K/Bielska-Biala
Polen
Tel. +48 338196000
Fax. +48 338158548
E-Mail: info@forch.pl
Internet: www.forch.pl

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 8
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetíněves
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@forch.com.au
Internet: www.forch.com.au

Troscoe Ltd
Unit 6, 13 Highbrook Drive
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email: sales@forchnz.co.nz
Internet: www.forchnz.co.nz

Förch Portugal Lda
Centro Empresarial Sintra-Estoril III
Rua Pé de Mouro, Nr 33, Armazém J
2710-335 Sintra
Portugal
Tel. +351 917314442
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes iela 3
1073 Riga
Lettland
Tel. +371 6 7 90 25 15
Fax. +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Page 38 of 39

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0014

Replacing version dated / version: 23.03.2021 / 0013

Valid from: 01.11.2021

PDF print date: 01.11.2021

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.

Haramidere Mevkii Beysan Sanayi

Sitesi Birlik Caddesi No:6/3

34524 Beylikdüzü / İstanbul

Türkei

Tel. +90 (0)212 422 8744-45

Fax. +90 (0)212 422 8788

E-Mail: info@forch.com.tr

Internet: www.forch.com.tr

Total Consumables Ltd

Coolnafeearagh

Monasterevin

Co. Kildare

W34 TX29

İrland

Tel. +353871271473

Venus Arma d.o.o.

Partner Theo Förch GmbH & Co. KG

Batajnicksi drum 18a

11080 Zemun

Republika Srbija

Tel. +381 11 407-20-91

Fax. +381 11 407-20-91

E-Mail: office@foerch.rs

Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, ElCx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EpCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

Page 39 of 39

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0014

Replacing version dated / version: 23.03.2021 / 0013

Valid from: 01.11.2021

PDF print date: 01.11.2021

Multi System Filler L270

2000 g Art.: 6260 2705 (B), Art.: 6264 2705 (B)

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.