

Page 1 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Primer/adhesion promoter

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
 Theo-Förch-Str. 11 – 15
 74196 Neuenstadt
 Tel.: 07139/95-0
 Fax: 07139/95-199
 Email: info@foerch.de
 Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Flam. Liq. | 3 | H226-Flammable liquid and vapour. |
| STOT SE | 3 | H335-May cause respiratory irritation. |
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |
| STOT SE | 3 | H336-May cause drowsiness or dizziness. |
| Aquatic Chronic | 3 | H412-Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910



Danger

H226-Flammable liquid and vapour. H335-May cause respiratory irritation. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment.
P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Hydrocarbons, C9, aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| Hydrocarbons, C9, aromatics | |
|--|--|
| Registration number (REACH) | 01-2119455851-35-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 918-668-5 |
| CAS | (64742-95-6) |
| content % | 5-<25 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | EUH066 Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 |

| 4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine | |
|--|---|
| Registration number (REACH) | --- |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 221-133-2 |
| CAS | 3010-23-9 |
| content % | 0,1-<1 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) |

Page 3 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.
If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
Do not induce vomiting. Consult doctor immediately.
Danger of aspiration.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher
Cool container at risk with water.

Unsuitable extinguishing media

n.c.
High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:
Oxides of carbon
Toxic gases
Flammable vapour/air mixtures

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Page 4 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
 Ensure sufficient ventilation, remove sources of ignition.
 Avoid dust formation with solid or powder products.
 Leave the danger zone if possible, use existing emergency plans if necessary.
 Remove possible causes of ignition - do not smoke.
 Ensure sufficient supply of air.
 Avoid inhalation, and contact with eyes or skin.
 If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
 Resolve leaks if this possible without risk.
 Prevent from entering drainage system.
 Prevent surface and ground-water infiltration, as well as ground penetration.
 If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
 Avoid inhalation of the vapours.
 Keep away from sources of ignition - Do not smoke.
 Avoid contact with eyes or skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Observe directions on label and instructions for use.
 Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Observe special storage conditions.
 Under all circumstances prevent penetration into the soil.
 Protect from direct sunlight and warming.
 Store in a well-ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 500 mg/m³

| Chemical Name | | Hydrocarbons, C9, aromatics | |
|------------------------|-----------------------------------|--|-----|
| WEL-TWA: | 500 mg/m ³ (Aromatics) | WEL-STEL: | --- |
| Monitoring procedures: | | - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) | |

GB

Page 5 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

| | |
|-----------|------------------------|
| BMGV: --- | Other information: --- |
|-----------|------------------------|

| Chemical Name | Silicon dioxide |
|--|------------------------|
| WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust) | WEL-STEL: --- |
| Monitoring procedures: --- | |
| BMGV: --- | Other information: --- |

| Chemical Name | Aluminium powder (stabilised) |
|---|-------------------------------|
| WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (resp. dust) | WEL-STEL: --- |
| Monitoring procedures: --- | |
| BMGV: --- | Other information: --- |

| Chemical Name | Graphite |
|--|------------------------|
| WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (res. dust) | WEL-STEL: --- |
| Monitoring procedures: --- | |
| BMGV: --- | Other information: --- |

| Chemical Name | Asphalt |
|---|---|
| WEL-TWA: 5 mg/m3 (Asphalt, petroleum fumes) | WEL-STEL: 10 mg/m3 (Asphalt, petroleum fumes) |
| Monitoring procedures: --- | |
| BMGV: --- | Other information: --- |

| Chemical Name | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics |
|----------------------------|--|
| WEL-TWA: 800 mg/m3 | WEL-STEL: --- |
| Monitoring procedures: --- | <ul style="list-style-type: none"> - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) |
| BMGV: --- | Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40) |

| Hydrocarbons, C9, aromatics | | | | | | |
|-----------------------------|--|-----------------------------|------------|-------|--------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 32 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 11 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 11 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 25 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 150 | mg/m3 | |

| Silicon dioxide | | | | | | |
|---------------------|--|--------------------------|------------|-------|------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - oral (animal feed) | | PNEC | 60000 | mg/kg feed | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 4 | mg/m3 | |

| Aluminium powder (stabilised) | | | | | | |
|-------------------------------|--|-----------------------------|------------|--------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,0749 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 20 | mg/l | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 3,95 | mg/kg | |

Page 6 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|-------|--|
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 3,72 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 3,72 | mg/m3 | |

| Asphalt | | | | | | |
|---------------------|--|--------------------------|------------|-------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 0,6 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 2,9 | mg/m3 | |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|--|-----------------------------|------------|-------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 300 | mg/kg | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 300 | mg/kg | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 900 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 300 | mg/kg | |

(GB) WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective gloves in butyl rubber (EN ISO 374).
 Minimum layer thickness in mm:
 >= 0,4
 Permeation time (penetration time) in minutes:

Page 7 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

<= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A (EN 14387), code colour brown

If applicable

Protective respirator with independent air supply.

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Liquid |
| Colour: | Light brown |
| Odour: | Characteristic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | 160 °C |
| Flammability: | Flammable |
| Lower explosion limit: | 0,5 Vol-% |
| Upper explosion limit: | 6,5 Vol-% |
| Flash point: | 56 °C |
| Auto-ignition temperature: | 210 °C |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | Mixture is non-soluble (in water). |
| Kinematic viscosity: | There is no information available on this parameter. |
| Solubility: | Insoluble |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | 2 hPa (20°C) |
| Density and/or relative density: | 0,98 g/ml (20°C) |
| Relative vapour density: | There is no information available on this parameter. |
| Particle characteristics: | Does not apply to liquids. |

9.2 Other information

| | |
|--------------------|---------------------------------------|
| Explosives: | Product is not explosive. |
| Oxidising liquids: | No |
| Solvents content: | 35,45 % (Directive 2010/75/EU (VOC)) |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Welding Primer L208

500 ml Art.: 6730 0910, Art.: 6734 0910

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|-------|----------|-------------|------------------|
| Acute toxicity, by oral route: | ATE | >2000 | mg/kg | | | calculated value |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Hydrocarbons, C9, aromatics

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|---------|---------|------------|---|---|
| Acute toxicity, by oral route: | LD50 | 3492 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >3160 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5,693 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Analogous conclusion |
| Acute toxicity, by inhalation: | LC50 | > 6,193 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test) | Negative |

Page 9 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | |
|---|--|--|--|------------------------|---|--|
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | | | Negative |
| Reproductive toxicity: | | | | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Reproductive toxicity: | | | | | OECD 416 (Two-generation Reproduction Toxicity Study) | Negative |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | STOT SE 3, H335, STOT SE 3, H336 |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 452 (Chronic Toxicity Studies) | Negative |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | respiratory distress, coughing, burning of the membranes of the nose and throat, drowsiness, dizziness, headaches, nausea, unconsciousness, fever, ear noises, drying of the skin. |

| 4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine | | | | | | |
|--|----------|-------|-------|----------|---|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Skin corrosion/irritation: | | | | Rabbit | | Irritant, Analogous conclusion |
| Skin corrosion/irritation: | | | | | | Corrosive, Analogous conclusion, Experiences on persons. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Risk of serious damage to eyes., Analogous conclusion |

Page 10 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | |
|-----------|--|--|--|--|--|-------------------------------|
| Symptoms: | | | | | | gastrointestinal disturbances |
|-----------|--|--|--|--|--|-------------------------------|

| Silicon dioxide | | | | | | |
|---|----------|--------|---------|------------|--------------------------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | References |
| Acute toxicity, by inhalation: | LC50 | >0,139 | mg/l/4h | Rat | | References, Maximum achievable concentration. |
| Skin corrosion/irritation: | | | | Rabbit | | Not irritant, References |
| Serious eye damage/irritation: | | | | Rabbit | | Not irritant, Mechanical irritation possible., References |
| Respiratory or skin sensitisation: | | | | Guinea pig | | Not sensitising |
| Germ cell mutagenicity: | | | | | | Negative |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity (Developmental toxicity): | | | | | | No indications of such an effect. |
| Symptoms: | | | | | | eyes, reddened |

| Aluminium powder (stabilised) | | | | | | |
|------------------------------------|----------|-------|---------|----------|--------------------------------|----------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 15900 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Acute toxicity, by inhalation: | LC50 | >5 | mg/l/4h | Rat | | Dust, Mist |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Respiratory or skin sensitisation: | | | | | | No (skin contact) |
| Symptoms: | | | | | | mucous membrane irritation |

| Graphite | | | | | | |
|------------------------------------|----------|-------|----------|------------------------|--|-----------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by inhalation: | NOAEC | >2000 | mg/m3/4h | Rat | OECD 412 (Subacute Inhalation Toxicity - 28-Day Study) | |
| Acute toxicity, by inhalation: | LC50 | >2000 | mg/m3/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Not sensitising |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |

Page 11 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | |
|------------------------|-------|-----|-------|-----|--|------------------------|
| Reproductive toxicity: | NOAEL | 813 | mg/kg | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Symptoms: | | | | | | breathing difficulties |

| Asphalt | | | | | | |
|---|----------|--------|------------|------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | > 5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | > 2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LD50 | > 94,4 | mg/m3 | Rat | OECD 403 (Acute Inhalation Toxicity) | Analogous conclusion |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative Chinese hamster |
| Reproductive toxicity: | NOAEL | 1000 | mg/kg bw/d | Rat | OECD 416 (Two-generation Reproduction Toxicity Study) | |
| Symptoms: | | | | | | vomiting, mucous membrane irritation |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | > 2000 | mg/kg bw/d | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|----------|-------|----------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5000 | mg/m3/8h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Acute toxicity, by inhalation: | LC50 | >5 | mg/m3/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours, Analogous conclusion |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking., Product removes fat. |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Analogous conclusion |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |

Page 12 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 21.09.2022 / 0020
Replacing version dated / version: 01.11.2021 / 0019
Valid from: 21.09.2022
PDF print date: 24.09.2022
Welding Primer L208
500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | |
|---|-------|---------|-------|-------|--|--|
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion |
| Reproductive toxicity: | NOAEC | >= 5220 | mg/m3 | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion in inhalation |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | No indications of such an effect., Analogous conclusion |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | unconsciousness, headaches, dizziness, Dermatitis (skin inflammation), Reddening, drying of the skin., mucous membrane irritation, nausea and vomiting., diarrhoea, lower abdominal pain |

11.2. Information on other hazards

| Welding Primer L208 500 ml Art.: 6730 0910, Art.: 6734 0910 | | | | | | |
|--|----------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Endocrine disrupting properties: | | | | | | Does not apply to mixtures. |
| Other information: | | | | | | No other relevant information available on adverse effects on health. |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Welding Primer L208 500 ml Art.: 6730 0910, Art.: 6734 0910 | | | | | | | |
|--|----------|------|-------|------|----------|-------------|-------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | Product is slightly volatile. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |

Page 13 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

| | | | | | | | |
|--|--|--|--|--|--|--|---|
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |
| Other information: | | | | | | | According to the recipe, contains no AOX. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

| Hydrocarbons, C9, aromatics | | | | | | | |
|--|----------|-------|-----------|------|---------------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 9,2 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 3,2 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | ErL50 | 72h | 2,9 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 54-56 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | |
| 12.2. Persistence and degradability: | | 28d | 78 | % | activated sludge | OECD 301 E (Ready Biodegradability - Modified OECD Screening Test) | Readily biodegradable |
| 12.2. Persistence and degradability: | | 28d | 78 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | |
| 12.3. Bioaccumulative potential: | Log Pow | | 3,7 - 4,5 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC50 | 10min | >99 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |

| 4,5-dihydro-2-heptadecyl-1H-imidazole-1-ethylamine | | | | | | | |
|--|----------|------|-------|------|----------|--------------------------------------|----------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 0,35 | mg/l | | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |

| | | | | | | | |
|--------------------------------------|------|-----|----------|------|---------------|--|---------------------------|
| 12.1. Toxicity to daphnia: | EC50 | 48h | 0,29 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.2. Persistence and degradability: | | | | | | OECD 301 (Ready Biodegradability) | Not readily biodegradable |
| Other information: | COD | | 2704,000 | mg/l | | DIN 38409-H41 | |

Silicon dioxide

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|--------|------|-------------------|--|-------------------------------------|
| 12.1. Toxicity to fish: | LC50 | 96h | >10000 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 24h | >10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | >10000 | mg/l | | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Abiotically degradable. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Aluminium powder (stabilised)

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|----------|------|-------|------|----------|-------------|--|
| 12.5. Results of PBT and vPvB assessment | | | | | | | Not relevant for inorganic substances. |

Graphite

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--------------------------------------|----------|------|-------|------|---------------------------------|--|---|
| 12.2. Persistence and degradability: | | | | | | | Inorganic products cannot be eliminated from water through biological purification methods. |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | IC50 | 72h | 100 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| Water solubility: | | | | | | | Insoluble |

Asphalt

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|-------------------|----------|------|-------|------|----------|-------------|-------|
|-------------------|----------|------|-------|------|----------|-------------|-------|

| | | | | | | | |
|--|-----------|-----|---------|------|---------------------------------|------|-------------------------------------|
| 12.1. Toxicity to fish: | LL50 | 96h | > 1000 | mg/l | Oncorhynchus mykiss | QSAR | Analogous conclusion |
| 12.1. Toxicity to daphnia: | LL50 | 48h | > 1000 | mg/l | Daphnia magna | QSAR | Analogous conclusion |
| 12.1. Toxicity to algae: | EL50 | 72h | > 1000 | mg/l | Pseudokirchneriella subcapitata | QSAR | Analogous conclusion |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to fish: | NOEC/NOEL | 28d | >= 1000 | mg/l | Oncorhynchus mykiss | QSAR | Analogous conclusion |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | >= 1000 | mg/l | Daphnia magna | QSAR | Analogous conclusion |
| 12.2. Persistence and degradability: | | | | | | | Not biodegradable |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|--|----------|------|---------|------|---------------------------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,10 | mg/l | Oncorhynchus mykiss | QSAR | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 0,18 | mg/l | Daphnia magna | QSAR | |
| 12.1. Toxicity to algae: | ErL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOELR | 72h | 1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 80 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 5,5-7,2 | | | | |
| 12.4. Mobility in soil: | Log Koc | | >3 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.7. Other adverse effects: | | | | | | | Product floats on the water surface. |
| Water solubility: | | | ~10 | mg/l | | | Slight |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 08 discarded organic chemicals consisting of or containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

Page 16 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

E.g. suitable incineration plant.
For contaminated packing material
 Pay attention to local and national official regulations.
 Empty container completely.
 Uncontaminated packaging can be recycled.
 Dispose of packaging that cannot be cleaned in the same manner as the substance.
 15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1993

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 1993 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9, AROMATICS)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Classification code: F1

LQ: 5 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D/E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9, AROMATICS)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

EmS: F-E, S-E

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Flammable liquid, n.o.s. (HYDROCARBONS, C9, AROMATICS)

14.3. Transport hazard class(es): 3

14.4. Packing group: III

14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!
 This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.
 For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| | | | |

Page 17 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

| | | |
|-----|------|-------|
| P5c | 5000 | 50000 |
|-----|------|-------|

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 24,34 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Flam. Liq. 3, H226 | Classification based on test data. |
| STOT SE 3, H335 | Classification according to calculation procedure. |
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| STOT SE 3, H336 | Classification according to calculation procedure. |
| Aquatic Chronic 3, H412 | Classification based on test data. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Flam. Liq. — Flammable liquid
 STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Asp. Tox. — Aspiration hazard
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects
 Aquatic Chronic — Hazardous to the aquatic environment - chronic
 Skin Corr. — Skin corrosion
 Eye Dam. — Serious eye damage
 Aquatic Acute — Hazardous to the aquatic environment - acute

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

Page 18 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 21.09.2022 / 0020
 Replacing version dated / version: 01.11.2021 / 0019
 Valid from: 21.09.2022
 PDF print date: 24.09.2022
 Welding Primer L208
 500 ml Art.: 6730 0910, Art.: 6734 0910

National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
 ZAE Le Marchais Renard
 CS 50125 Montereau-sur-le-Jard
 77019 Melun Cedex
 Frankreich
 Tel. +33 1 64 14 48 48
 Fax. +33 1 64 14 48 49
 E-Mail: info@forch.fr
 Internet: www.forch.fr

S.C. Foerch S.R.L.
 Str. Zizinului nr.110
 500407 Brasov
 Rumänien
 Tel. +40 368 408192
 Fax. +40 368 408193
 E-Mail: info@foerch.ro
 Internet: www.foerch.ro

Foerch AG
 Muttenerstrasse 143
 4133 Pratteln
 Schweiz
 Tel. +41 61 8262031
 Fax. +41 61 8262039
 E-Mail: info@foerch.ch
 Internet: www.foerch.ch

Foerch Bulgaria EOOD
 475 Botevgradsko Shose Blvd.
 BG 1517 Sofia, Bulgaria
 Tel. 00359 2 981 2841
 Fax. 00359 982 10 30 86
 E-Mail: info@foerch.bg

Förch d.o.o.
 Buzinska cesta 58
 10010 Zagreb
 Kroatien
 Tel. +385 1 2912900
 Fax. +385 1 2912901
 E-Mail: info@foerch.hr
 internet: www.foerch.hr

Theo Förch GmbH
 Röcklbrunnstraße 39A
 5020 Salzburg
 Österreich
 Tel. +43 662 875574-0
 Fax +43 662 878677-21
 Verkauf Tel. +43 662 875574-900
 Verkauf Fax +43 662 875574-30
 E-Mail: info@foerch.at
 Internet: www.foerch.at

Förch Componentes para Taller S.L.
 Camino de San Antón, S/N
 18102 Ambroz (Granada)
 Spanien
 Tel. +34 958 40 17 76
 Fax. +34 958 40 17 87
 E-Mail: info@forch.es
 Internet: www.forch.es

Förch A/S
 Hagemannsvej 3
 8600 Silkeborg
 Danmark
 Tel. +45 86 823711
 Fax. +45 86 800617
 E-Mail: info@foerch.dk
 Internet: www.foerch.dk

Lhomme Tools & Fasteners BV
 Seinhuistraat 5 B4
 Poort 0331
 3600 Genk
 Belgien
 Tel. +32 89 71 66 61
 E-Mail: info@lhommetools.be
 Internet: www.lhommetools.be

Ziebe Limited
 7 Century Court, Westcott,
 Aylesbury, Bucks, HP18 0XP (UK)
 Grossbritannien
 Tel +44 12 96 65 52 82
 E-Mail: sales@ziebe.co.uk
 Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.
 Mikdyrzecze Górne 379
 43-392 K/Bielska-Biala
 Polen
 Tel. +48 338196000
 Fax. +48 338158548
 E-Mail: info@forch.pl
 Internet: www.forch.pl

Vardalis SM P.C.
 Ethnikis Antistasis 62
 57007 Chalkidona-Thessaloniki
 Griechenland
 Tel. +30 23910 21222
 Fax. +30 23910 21223
 E-Mail: info@forch.gr
 Internet: www.forch.gr

Förch Kereskedelmi Kft
 Börgöndi út 14
 8000 Székesfehérvár
 Ungarn
 Tel. +36 22 348348
 Fax. +36 22 348355
 E-Mail: info@foerch.hu
 Internet: www.foerch.hu

Förch S.r.l.
 Via Antonio Stradivari 4
 39100 Bolzano (BZ)
 Italien
 Tel: +39 0471 204330
 Fax: +39 0471 204290
 E-Mail: info@forch.it
 Internet: www.forch.it

Förch Nederland BV
 Twentepoort Oost 51
 7609 RG Almelo
 Niederlande
 Tel. +31 85 77 32 420
 E-Mail: info@foerch.nl
 Internet: www.foerch.nl

AB varahlutir ehf
 Funahöfði 9
 110 Reykjavík
 Tel. +354 567 6020
 E-mail: ab@ab.is
 Internet: www.ab.is

Förch Slovensko s.r.o.
 Rosinská cesta 8
 010 08 Žilina
 Slowakei
 Tel +421 41 5002454
 E-Mail: info@forch.sk
 Internet: www.forch.sk

Förch Sverige AB
 Brännarevägen 1
 151 55 Södertälje
 Schweden
 Tel. +46 855089264
 E-mail: info@foerch.se
 Internet: www.foerch.se

Page 19 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.09.2022 / 0020

Replacing version dated / version: 01.11.2021 / 0019

Valid from: 21.09.2022

PDF print date: 24.09.2022

Welding Primer L208

500 ml Art.: 6730 0910, Art.: 6734 0910

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetín
Tschechien
Tel. +420 271 001 984-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 13 550 330
Email : sales@foerch.com.au
Internet: www.foerch.com.au

Troscoe Ltd
Unit 6, 13 Highbrook Drive
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email:sales@forchnz.co.nz
Internet: www.forchnz.co.nz

Förch Portugal Lda
Centro Empresarial Sintra-Estoril III
Rua Pé de Mouro, N.º 33, Armazém J
2710-335 Sintra
Portugal
Tel. +351 917314442
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes iela 3
1073 Riga
Lettland
Tel. +371 6 7 90 25 15
Fax. +371 67 90 24 96
E-Mail: triggers@triggers.lv
Internet: www.triggers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.
Haramidere Mevkii Beysan Sanayi
Sitesi Birlık Caddesi No:6/3
34524 Beylikdüzü / İstanbul
Türkei
Tel. +90 (0)212 422 8744-45
Fax. +90 (0)212 422 8788
E-Mail: info@forch.com.tr
Internet: www.forch.com.tr

Total Consumables Ltd
Coolnafearagh
Monasterevin
Co. Kildare
W34 TX29
Irland
Tel. +353871271473

Venus Arma d.o.o.
Partner Theo Förch GmbH & Co. KG
Batajnıckı drum 18a
11080 Zemare
Republika Srbija
Tel. +381 11 407-20-91
Fax. +381 11 407-20-91
E-Mail: office@foerch.rs
Internet: www.foerch.rs

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

Page 20 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 21.09.2022 / 0020

Replacing version dated / version: 01.11.2021 / 0019

Valid from: 21.09.2022

PDF print date: 24.09.2022

Welding Primer L208

500 ml Art.: 6730 0910, Art.: 6734 0910

EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ErCx, E_uCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
Koc Adsorption coefficient of organic carbon in the soil
Kow octanol-water partition coefficient
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.